



Rich Communication Suite

Management Objects

Release 1

Document Version 1.1

August 31, 2009

This is a binding/non-binding permanent reference document of the GSM Association.

Security Classification: This document contains non-confidential GSMA information

Copyright Notice

Copyright © 2009 GSM Association

Antitrust Notice

The information contain herein is in full compliance with the GSM Association's antitrust compliance policy.

Table of Contents

1	INTRODUCTION	3
1.1	Scope	3
1.2	References	3
2	Management object parameters	3
2.1	General.....	3
2.2	Presence related configuration	4
2.2.1	<i>RCS endorsement of OMA Presence Client provisioning parameters</i>	<i>4</i>
2.2.2	<i>Specific RCS Client provisioning parameters linked with Presence.....</i>	<i>4</i>
2.3	XDM related configuration	5
2.3.1	<i>RCS endorsement of OMA XDM Client provisioning parameters</i>	<i>5</i>
2.3.2	<i>Specific RCS Client provisioning parameters linked with XDM.....</i>	<i>6</i>
2.4	IM related configuration	6
2.4.1	<i>RCS endorsement of OMA IM Client provisioning parameters</i>	<i>6</i>
2.4.2	<i>Specific RCS Client provisioning parameters linked with IM.....</i>	<i>7</i>
2.5	File transfer related configuration	7
2.5.1	<i>Specific RCS Client provisioning parameters linked with File transfer....</i>	<i>7</i>
2.6	IMS Core /SIP related configuration	7
2.6.1	<i>General.....</i>	<i>7</i>
2.6.2	<i>RCS endorsement of 3GPP IMS Management Object (MO)</i>	<i>7</i>
2.6.3	<i>Specific RCS Client provisioning parameters linked with SIP/IMS</i>	<i>7</i>
2.7	Configuration related with Address book Back-up/Restore	8
2.7.1	<i>General.....</i>	<i>8</i>
3	Technical support for the configuration of data on a RCS terminal...9	
3.1	General.....	9
3.2	Parameters specific to RCS	9
	DOCUMENT MANAGEMENT	10

1 INTRODUCTION

1.1 Scope

The service definition of RCS does not require end user to manually configure any settings in order to use RCS services. This document defines which parameters are to be configured by the network onto an RCS terminal as well as how they are configured.

The scope of this document is RCS Release 1.

1.2 References

[FUNCDESC]	RCS Release 1 Functional Description
[TECHREAL]	RCS Release 1 Technical Realization
[IMENDORSE]	RCS Release 1 Endorsement of OMA SIP/SIMPLE IM 1.0
[SIMPLEIM]	Instant Messaging using SIMPLE, 1.0, http://www.openmobilealliance.org/
[OMADSDM]	OMA-TS-DS_MO-V1_0-20090212-C http://www.openmobilealliance.org
[PRESENCE]	Presence SIMPLE Specification, 1.1, http://www.openmobilealliance.org
[PRESENCEIG]	Implementation Guidelines for OMA Presence SIMPLE v1.1 Presence, http://www.openmobilealliance.org
[PRESENCEMO]	OMA Management Object for Presence SIMPLE 1.1, http://www.openmobilealliance.org
[XDM1.1_Core]	XML Document Management (XDM) Specification 1.1, XML Document Management (XDM) Specification
[XDMIG]	Implementation Guidelines for OMA XDM v1.1 Presence, http://www.openmobilealliance.org
[XDMMO]	OMA Management Object for XML Document Management 1.1, http://www.openmobilealliance.org
[33.978]	3GPP TS 33.978 Security aspects of early IP Multimedia Subsystem (IMS), http://www.3gpp.org
[24.167]	3GPP TS 24.167 IMS 3GPP IMS Management Object (MO), http://www.3gpp.org
[24.229]	3GPP TS 24.229 IMS Call Control based on SIP and SDP, http://www.3gpp.org

2 MANAGEMENT OBJECT PARAMETERS

2.1 General

Unless otherwise specified (i.e. unless a RCS client configuration parameter is explicitly mentioned as subject of possible user modification), the RCS related parameters described in this document are locked from end-user modification. They may be set at initial start-up of the RCS client or modified (while the client is running) via network OMA procedures initiated by the Device Management Server of the RCS operator

This section describes the parameters needed to configure an RCS client for the initiation of RCS service and for a continuous provisioning by RCS service provider.

- When suitable Managed Objects (MO) exist in OMA documentation, RCS client configuration parameters correspond to the endorsement of such MO, e.g. Device Management Object in [XDMMO], [PRESENCEMO], [24.167] and [IMENDORSE] respectively.
- When RCS specific parameters are required (no suitable parameter has been defined by OMA) such parameters are described in a dedicated section of this document and defined as extensions of the relevant OMA MO

In the following sections,

- “M” stands for “Support Mandatory in an RCS terminal”
- “N.A.” stands for “Not Applicable for RCS”

2.2 Presence related configuration

2.2.1 RCS endorsement of OMA Presence Client provisioning parameters

OMA Presence Client provisioning parameters are defined in [PRESENCEMO]. Table 1 lists the OMA Presence parameters applicable to RCS.

Parameter Name	Description		Support in RCS
CLIENT-OBJ-DATA-LIMIT	maximum size of the MIME object in SIP PUBLISH request		M
CONTENT-SERVER-URI	HTTP URI of the content server to be used for content indirection		N. A.
SOURCE-THROTTLE-PUBLISH	minimum time interval (in seconds) between two consecutive publications		M
MAX-NUMBER-OF-SUBSCRIPTIONS-IN-PRESENCE-LIST	Limits the number of back-end subscriptions allowed for a presence list. This parameter applies to the “rcs” list (as described in section 4.4.2 in [TECHREAL])		M
SERVICE-URI-TEMPLATE	syntax of the service URI		M, with value “<xui>;pres-list=<id>” according to section 5.5.1 in [PRESENCEMO]

Table 1 RCS Endorsed OMA Presence Parameters

2.2.2 Specific RCS Client provisioning parameters linked with Presence

Following RCS specific parameters shall be possible to configure on the UE

- Parameters associated with the Hyper-Availability attribute (as described in section 2.1.3.1 in [FUNCDESC] and section 4.2.2 in [TECHREAL])
 - "HyperAvailability Period" (as described in section 2.1.3.1 in [FUNCDESC] and section 4.2.2 in [TECHREAL])

- Parameters associated with the favourite Link attribute (as described in section 2.1.3.2 in [FUNCDESC])
 - Automatic / manual mode for the favourite link.
 - In the case automatic mode is activated, there is additional parameter “list of pre-defined Favourite link URIs” to be configured
 Favourite link attribute parameter SHALL NOT BE LOCKED
- Parameters associated with the Presence (Portrait) Icon attribute (as described in section 4.8.1 in [TECHREAL])
 - Icon maximum size in bytes (maximum 200Kb)
- Parameters associated with the Note attribute (as described in section 4.2.2 in [TECHREAL])
 - Maximal length of presence tagline at Presentity side. The reason to have at Presentity side a configurable attribute on the RCS client to control the maximum size of the Note is to make the end user aware of what the limit is (when typing the content of the Note/free text) and thus to avoid that enforcement of this limit at Network / watcher side would lead to truncating the note. This value should have a lower value than the one defined at watcher side in the OMA Presence Implementation guideline [PRESENCEIG].
- Parameters associated with the Operator restriction on the publication and display of service capabilities (as described in section 2.1.7 in [FUNCDESC] and section 4.9 in [TECHREAL])
 - Control on the retrieval of service capabilities via an anonymous presence fetch: When the retrieval is set to “Not Allowed”, the RCS rule for anonymous fetch of Presence Information is set by the UE to provide an empty document (at least telling the fetching terminal that the contact address supports Presence). Thus, in this case, only “buddies” of a user can get the “capabilities” information (together with the Presence Social Information) on this user.
 - Use of the anonymous fetch operation by the device (“Allowed” or “Not Allowed”).
 - Display of the ability of user’s contacts to share Social Presence Information (“Allowed” or “Not Allowed”).
 -
 - Default expiry time of PUBLISH (as described in section 4.6 and 4.7 in [TECHREAL])

2.3 XDM related configuration

2.3.1 RCS endorsement of OMA XDM Client provisioning parameters

OMA XDM Client provisioning parameters are defined in [XDMMO]. Table 2 lists the OMA XDM parameters applicable to RCS.

Parameter Name	Description		RCS usage
XCAP Root URI	The root of all XCAP resources (which points to the Aggregation Proxy address). This is used when accessing via XCAP.		M
XCAP Authentication user name	HTTP digest “username”, for accessing an XDMS using the XCAP protocol		O ⁽³⁾
XCAP Authentication Secret	HTTP digest password		O ⁽³⁾
XCAP Authentication type	Authentication method for XDMS over XCAP. Possible values: Early IMS ^{(1), (2)} or Digest		M

Table 2 RCS Endorsed OMA XDM Parameters

Notes:

1. The Early IMS value is a specific RCS value that is not defined in OMA
2. Support of Early IMS authentication for XCAP according to of section 6.3 of [33.978] and sections 6.3 and 6.4 in [XDM1.1_Core], by in the HTTP GET request to the Aggregation Proxy supplying the "X-3GPP-Intended-Identity" header to indicate the user identity.
3. In case of Early IMS, the XCAP Authentication user name and password is not needed.

2.3.2 Specific RCS Client provisioning parameters linked with XDM

Following RCS specific parameters shall be possible to configure on the UE

- Parameters associated with the "rcs_revokedcontacts" list (as described in section 2.1.4.6 in [FUNCDESC] and section 4.4.4 in [TECHREAL])
 - Duration that a contact should remain in this list

2.4 IM related configuration

2.4.1 RCS endorsement of OMA IM Client provisioning parameters

Note: OMA IM Client provisioning parameters are defined in [SIMPLEIM]. This Table 3 only lists which of those IM application parameters are applicable.

Parameter Name	Description		RCS usage
PRES-SRV-CAP	flag used for the IM Server to indicate the Presence publish capability of a Presence information element of the IM Server on behalf of the IM Client		N.A. Set to the OMA value indicating that the capability is not supported in the network
MAX_AD-HOC_GROUP_SIZE	Maximum number of Participants allowed for an Ad-hoc IM Group Session		M
CONF-FCTY-URI	SIP URI used for setting up an Ad-hoc IM Group or 1-1 IM Session		M
EXPLODER-URI	SIP URI used for sending SIP MESSAGE e.g. Sending SIP MESSAGE to an Ad hoc Group		N.A. ⁽¹⁾
CONV-HIST-FUNC-URI	SIP URI for IM user's conversation history storage		N.A.
DEFERRED-MSG-FUNC-URI / MSG-STORE-URI	SIP-URI used for IM User's message-store account for deferred messaging		N.A.
DELETE-URI	SIP URI used when message(s) are to be deleted		N.A.

Table 3 RCS Endorsed OMA IM Parameters

Notes:

1. For RCS these are populated with the sip URI= "sip:foo@bar" which is assumed to be a dumb value

2.4.2 Specific RCS Client provisioning parameters linked with IM

Following RCS specific parameters shall be possible to configure on the UE

- Parameters associated with the Chat service (as described in section 2.4.2 in [FUNCDESC] and section 8.2 in [TECHREAL])
 - Enable/Disable the Chat service
 - Enabling sending of message via legacy messaging when chat invite fails
 - Automatic or manual accept of a incoming 1-to-1 IM session request (default value = auto-accept,)
 - Maximum size of the content sent within a 1-to-1 chat session
 - Maximum size of the content sent in a group chat session
 - Timer for termination of inactive (idle) chat session (recommended value 30 minutes, no timeout shall also be possible)

2.5 File transfer related configuration

2.5.1 Specific RCS Client provisioning parameters linked with File transfer

Following RCS specific parameters shall be possible to configure on the UE

- Parameters associated with the File transfer service (as described in section 2.3 in [FUNCDESC] and section 7 in [TECHREAL])
 - Maximum file size allowed for a File Transfer

2.6 IMS Core /SIP related configuration

2.6.1 General

Settings for SIP and IMS Core related parameters.

2.6.2 RCS endorsement of 3GPP IMS Management Object (MO)

Basic IMS/SIP Client parameters are defined in 3GPP TS "IMS 3GPP IMS Management Object (MO)" [24.167]. They do not direct depend on RCS, but correct settings of these parameters are essential for RCS operation. They are populated by the operator according to the deployment conditions of the IMS Core network providing access to RCS services.

2.6.3 Specific RCS Client provisioning parameters linked with SIP/IMS

This section lists additional SIP and IMS Core level parameters that are applicable for an RCS client.

Parameter Name	Description	RCS usage
IMS Mode Authentication Type	Specifies the type of authentication support for SIP. Note: In "IETF" Digest	M

	authentication is assumed. Accepted values are: • Early IMS • IMS AKA • SIP DIGEST (without TLS)	
Realm	Realm to use for authentication (Digest mode only)	O M if Digest mode used
Realm User Name	Realm username to use for authentication (Digest mode only)	O M if Digest mode used
Realm User Password	Realm user password to use for authentication (Digest mode only)	O M if Digest mode used
TEL or SIP URI – international	Specifies whether telephone numbers in international format shall in outgoing SIP requests be sent as TEL URIs [RFC3966] or as SIP URIs with “user”-parameter set to “phone” [RFC3261] Reference: [TECHREAL] section 3.1.3	M
TEL or SIP URI - for non international format	Specifies whether telephone numbers in non international format shall in outgoing SIP requests be sent as TEL URIs [RFC3966] or as SIP URIs with “user”-parameter set to “phone” [RFC3261] Reference: [TECHREAL] section 3.1.3	M
Register Q-value	Q-value in Contact parameter in SIP Register Required in a multi-terminal deployment to control forking of incoming SIP requests	M Recommended value: 0.5

Table 4 RCS recommendation for SIP/IMS Parameters

2.7 Configuration related with Address book Back-up/Restore

2.7.1 General

For the proper operation of the Address Book Back-up/restore feature, the parameters described in [OMADSDM] need to be supported by a RCS terminal.

3 TECHNICAL SUPPORT FOR THE CONFIGURATION OF DATA ON A RCS TERMINAL

3.1 General

OMA DM v1.2 is used to configure the objects listed in this document.

3.2 Parameters specific to RCS

For parameters specific to RCS (for which there exist no OMA DM object), the extension capability of existing OMA DM objects is used as follows:

- Specific RCS Client provisioning parameters linked with Presence and defined in section 2.2.2 correspond to extension (EXT) of [PRESENCEMO].
- Specific RCS Client provisioning parameters linked with XDM and defined in section 2.3.2 correspond to extension (EXT) of [XDMMO].
- Specific RCS Client provisioning parameters linked with IM and with File transfer and defined in section 2.4.2 and section 2.5.1 correspond to extension (EXT) of [SIMPLEIM].
- Specific RCS Client provisioning parameters linked with IMS Core / sip and defined in section 2.6.3 correspond to extension (EXT) of the 3GPP IMS MO [24.167].

Editor's Note: Those extensions correspond to the "RCS" vendor name.

DOCUMENT MANAGEMENT

Document History

Version	Date	Brief Description of Change	Approval Authority	Editor / Company
0.1	15.01.2009	Baseline document created with the adoption of the document "RCS Client Provisioning Parameters_v0_0 7.doc"	RCS programme	Adamu Haruna/Nokia
0.1	03.03.2009	Incorporated "2009-DM0001- Removing 3gpp IMS MO-v0.0.doc"	RCS programme	Adamu Haruna/Nokia
1.0.2	12.05.2009	Incorporated 1. "2009-DM0002R7- RCS specific parameters configured on RCS clients" 2. "2009-DM0004R4- Locking "RCS parameters and Automatic Settings" 3. 2009-DM0006R1- Editing RCS specific parameters"	RCS programme	Adamu Haruna/Nokia
1.0.3	05.06.2009	Incorporated 1. RCS1_BF0025R1- Updating DM baseline Document.doc 2. 2009-DM0007_Clarification_on_service_capabilities_MO.doc	RCS programme	Adamu Haruna/Nokia
1.0.4	22.06.2009	consistency review R1 : Review report : SPEC DOC RCS SPEC R1_006 https://infocentre.gsm.org/cgi-bin/docindex.cgi?33476 Page 2 Added, needed for DAG approval	RCS programme	Dirk Raeymaekers/NSN
1.0.5	25.06.2009	Accept changes front pages & grammar/spelling check	RCS programme	Dirk Raeymaekers/NSN
1.0.6	12.08.2009	Removed reference to Release 2 in tracking page	RCS programme	Mark Hogan/GSMA
1.1	31.08.2009	DAG & EMC approved and version updated to V1.1	DAG&EMC	Dirk Raeymaekers/NSN

Other Information

Type	Description
Document Owner	Rich Communications Suite Programme
Editor / Company	Adamu Haruna / Nokia