



## IoT Big Data Harmonised Data Model

Version 2.0

04 September 2017

*This is a Non-binding Permanent Reference Document of the GSMA*

---

### **Security Classification: Non-confidential**

Access to and distribution of this document is restricted to the persons permitted by the security classification. This document is confidential to the Association and is subject to copyright protection. This document is to be used only for the purposes for which it has been supplied and information contained in it must not be disclosed or in any other way made available, in whole or in part, to persons other than those permitted under the security classification without the prior written approval of the Association.

### **Copyright Notice**

Copyright © 2017 GSM Association

### **Disclaimer**

The GSM Association ("Association") makes no representation, warranty or undertaking (express or implied) with respect to and does not accept any responsibility for, and hereby disclaims liability for the accuracy or completeness or timeliness of the information contained in this document. The information contained in this document may be subject to change without prior notice.

### **Antitrust Notice**

The information contain herein is in full compliance with the GSM Association's antitrust compliance policy.

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Overview	4
1.2	Scope	4
1.3	Abbreviations	4
1.4	Unit Codes	5
1.5	References	5
<b>2</b>	<b>Harmonised Data Models</b>	<b>6</b>
2.1	Vertical Segments	6
2.2	Attribute types	6
2.2.1	ExtQuantitativeValue Attribute type	8
2.3	Generic Entity Data Model	9
2.3.1	AgriCrop	10
2.3.2	AgriGreenHouse	14
2.3.3	AgriParcel	18
2.3.4	AgriParcelOperation	21
2.3.5	AgriParcelRecord	24
2.3.6	AgriPest	28
2.3.7	AgriProductType	30
2.3.8	AgriSoil	32
2.3.9	AirQualityObserved	35
2.3.10	Building	41
2.3.11	BuildingOperation	46
2.3.12	BuildingType	50
2.3.13	Device	52
2.3.14	DeviceModel	58
2.3.15	DeviceOperation	60
2.3.16	EnvironmentObserved	65
2.3.17	Machine	67
2.3.18	MachineModel	72
2.3.19	MachineOperation	76
2.3.20	PointOfInterest	79
2.3.21	Product	82
2.3.22	ProductRecord	87
2.3.23	ProductType	92
2.3.24	Road	95
2.3.25	RoadSegment	98
2.3.26	Subscriber	100
2.3.27	SubscriptionService	104
2.3.28	Vehicle	105
2.3.29	VehicleFault	109
2.3.30	VehicleType	112
2.3.31	WaterQualityObserved	113
2.3.32	WeatherForecast	121

2.3.33	WeatherObserved	126
<b>Annex A</b>	<b>ExtQuantitativeValue and NGSiv2 metadata compatibility (Informative)</b>	<b>132</b>
<b>Annex B</b>	<b>Referenced Schema.org entities (Informative)</b>	<b>133</b>
B.1	Schema.org entity descriptions: Offer	133
B.2	Schema.org entity descriptions: Organisation	138
B.3	Schema.org entity descriptions: Person	141
B.4	Schema.org entity descriptions: PostalAddress	145
B.5	Schema.org entity descriptions: Product	146
B.6	Schema.org entity descriptions: QuantitativeValue	149
B.7	Schema.org entity descriptions: Vehicle	150
<b>Annex C</b>	<b>Document Management</b>	<b>154</b>
C.1	Document History	154
C.2	Other Information	155

# 1 Introduction

## 1.1 Overview

Data interoperability has been identified [1] as a technical barrier that prohibits the realisation of the full potential value of IoT Big Data. To help address that problem, in this document data models are defined of entities or things that are commonly used in IoT Big Data applications. The definitions of the data entities have been developed through contributions from participating mobile operators and aligned with existing industry work and namespaces where possible, for example, oneM2M in Smart Home [2], OASC for Smart Cities [3] and schema.org [4] for generic entities.

These collaboratively developed harmonised data models, together with the accompanying documents “IoT Big Data Framework Architecture” [9] and “IoT Big Data NGSiv2 Profile” [10], aim to define a framework of how mobile operators can approach the delivery of IoT Big Data services.

All sections and appendixes, except “Scope” and “Introduction”, are normative, unless they are explicitly indicated to be informative.

## 1.2 Scope

This document specifies harmonised data models that are approved for use by all the participants of the IoT Big Data Ecosystem Project.

The harmonised data models are expected to evolve over time, potentially new entities will be added and entity definitions changed. The harmonised entity definitions defined within this document will be published and accessible via the GSMA IoT Big Data API Directory and will be developed and maintained in a collaborative manner. Contributions are welcome from the wider IoT community to develop and update the data entities. In the short to medium term, these changes will be managed through the standard GSMA PRD process with the IoT Big Data project Technology Group being the approval authority.

## 1.3 Abbreviations

Term	Description
3D	Three Dimensional
CAM	Computer Aided Manufacturing
CNC	Computer Numerical Control
DTC	Diagnostic Trouble Codes
GPC	Global Product Classification
GTIN	Global Trade Item Number
IoT	Internet of Things
IoTBD	Internet of Things Big Data
JSON	JavaScript Object Notation
UN/CEFACT	United Nations Centre for Trade Facilitation and Electronic Business
URL	Uniform Resource Locator
US EPA	United States Environmental Protection Agency

Term	Description
UTC	Universal Time Coordinated
UV	Ultra Violet
VIN	vehicle identification number

## 1.4 Unit Codes

Unit Code	Description
CEL <sup>[11]</sup>	Degree Celsius
FTU <sup>[11]</sup>	Formazin Turbidity Unit
GQ <sup>[11]</sup>	microgram per cubic metre
H29 <sup>[11]</sup>	microgram per litre
kg	kilogrammes
KMT <sup>[11]</sup>	kilometres
kW/m <sup>2</sup>	kilo watts per square metre
M1 <sup>[11]</sup>	milligrammes per litre
mg/L	miligrammes per litre
m/s	meters per second
mV	milliVolts
ppb	parts per billion
ppt	parts per thousand
ppm	parts per million
RFU <sup>[11]</sup>	relative fluorescence units
SMI <sup>[11]</sup>	miles
S/m	Siemens per meter

## 1.5 References

Ref	Doc Number	Title
[1]		Unlocking the Value of IoT Through Big Data. <a href="http://www.gsma.com/connectedliving/unlocking-the-value-of-iot-through-big-data/">http://www.gsma.com/connectedliving/unlocking-the-value-of-iot-through-big-data/</a>
[2]	oneM2M	<a href="http://www.onem2m.org/">http://www.onem2m.org/</a>
[3]	OASC	<a href="http://oascities.org/">http://oascities.org/</a>
[4]	Schema.org	<a href="http://schema.org/">http://schema.org/</a>
[5]	JSON	<a href="http://www.json.org/">http://www.json.org/</a>
[6]	FIWARE NGSIv2	FIWARE-NGSIv2 Specification available at <a href="http://fiware.github.io/specifications/ngsiv2/stable/">http://fiware.github.io/specifications/ngsiv2/stable/</a>
[7]	FIWARE DataModels	<a href="http://fiware-datamodels.readthedocs.io/en/latest/">http://fiware-datamodels.readthedocs.io/en/latest/</a>

Ref	Doc Number	Title
[8]	Lower camel case	<a href="https://en.wikipedia.org/wiki/CamelCase">https://en.wikipedia.org/wiki/CamelCase</a>
[9]	GSMA PRD CLP.25	IoT Big Data Framework Architecture
[10]	GSMA PRD CLP.24	IoT Big Data NGSIv2 Profile
[11]	UN/CEFA CT Unit Codes	<a href="https://www.unece.org/fileadmin/DAM/cefact/recommendations/rec20/rec20_rev3_Annex2e.pdf">https://www.unece.org/fileadmin/DAM/cefact/recommendations/rec20/rec20_rev3_Annex2e.pdf</a>

## 2 Harmonised Data Models

### 2.1 Vertical Segments

The harmonised data entities contained in this document originate from and are used in the following industry verticals (or IoT Domains):

- Agriculture
- Automotive
- Environment
- Industry
- Smart City
- Smart Home

The data entity definitions include a list of the applicable industry verticals to assist with entity classification and discovery.

### 2.2 Attribute types

Attribute types used within this document broadly follow the JSON (JavaScript Object Notation) type specification [5], the NGSIv2 [6] type specification and the schema.org type specification [4] as tabulated below:

Attribute Type name	Usage
List	An ordered list of values that are referenced by numerical index. Lists
Boolean	Logical value of <b>true</b> or <b>false</b> .
Date	A sequence of characters using ISO 8601 encoding to represent a Date. <a href="https://schema.org/Date">https://schema.org/Date</a>
DateTime	A sequence of characters using ISO 8601 encoding to represent a timestamp (date plus time). <a href="https://schema.org/DateTime">https://schema.org/DateTime</a>

ExtQuantitativeValue	An extended collection of key value pairs describing a point value characteristic of an entity.  Specifically adding a <b>timestamp</b> (the date and time or the observation) to the existing Quantitative Value as defined by schema.org.  ( <a href="https://schema.org/QuantitativeValue">https://schema.org/QuantitativeValue</a> )
geo:json	Defines a location specified using geo:json encoding. ( <a href="https://tools.ietf.org/html/rfc7946">https://tools.ietf.org/html/rfc7946</a> )
Number	An integer or floating point number. ( <a href="https://schema.org/Number">https://schema.org/Number</a> )
Offer	An offer definition for goods or services as defined by schema.org. ( <a href="https://schema.org/Offer">https://schema.org/Offer</a> )
Organization	An organisation definition as defined by schema.org. ( <a href="https://schema.org/Organization">https://schema.org/Organization</a> )
Person	A person definition as defined by schema.org. ( <a href="https://schema.org/Person">https://schema.org/Person</a> )
Place	A place definition as defined by schema.org. ( <a href="https://schema.org/Place">https://schema.org/Place</a> )
PostalAddress	A Postal Address of an item as defined by schema.org. ( <a href="https://schema.org/PostalAddress">https://schema.org/PostalAddress</a> )
Product	A product definition as defined by schema.org. ( <a href="https://schema.org/Product">https://schema.org/Product</a> )
QuantitativeValue	A collection of key value pairs describing a point value characteristic of an entity or attribute as defined by schema.org. ( <a href="https://schema.org/QuantitativeValue">https://schema.org/QuantitativeValue</a> )
Reference	A sequence of characters which represents a reference to another entity.
StructuredValue	A collection of key value pairs. Values may themselves be a Text, Number, Boolean, Array, StructuredValue or DateTime as defined by schema.org. ( <a href="https://schema.org/StructuredValue">https://schema.org/StructuredValue</a> )
Text	A sequence of characters. ( <a href="https://schema.org/Text">https://schema.org/Text</a> )
Time	A sequence of characters using ISO 8601 encoding to represent a Time. ( <a href="https://schema.org/Time">https://schema.org/Time</a> )
URL	A sequence of characters. Defining a URL. ( <a href="https://schema.org/URL">https://schema.org/URL</a> )

In addition, all the entities defined in this document are valid attribute types.

## 2.2.1 ExtQuantitativeValue Attribute type

The ExtQuantitativeValue attribute type is defined below:

Property	Expected Type	Description
<b>Properties from <u>ExtQuantitativeValue</u></b>		
<b><u>additionalProperty</u></b>	<u>PropertyValue</u>	A property-value pair representing an additional characteristics of the entity, e.g. a product feature or another characteristic for which there is no matching property in schema.org. Note: Publishers should be aware that applications designed to use specific schema.org properties (e.g. <a href="http://schema.org/width">http://schema.org/width</a> , <a href="http://schema.org/color">http://schema.org/color</a> , <a href="http://schema.org/qtin13">http://schema.org/qtin13</a> , ...) will typically expect such data to be provided using those properties, rather than using the generic property/value mechanism.
<b><u>maxValue</u></b>	<u>Number</u>	The upper value of some characteristic or property.
<b><u>minValue</u></b>	<u>Number</u>	The lower value of some characteristic or property.
<b><u>timestamp</u>*</b>	<u>DateTime</u>	The ISO8601 sequence of characters at which date and time the observation was made in UTC.
<b><u>unitCode</u></b>	<u>Text</u> <u>URL</u>	or The unit of measurement given using the UN/CEFACT Common Code (3 characters) or a URL. Other codes than the UN/CEFACT Common Code may be used with a prefix followed by a colon.
<b><u>unitText</u></b>	<u>Text</u>	A string or text indicating the unit of measurement. Useful if you cannot provide a standard unit code for <u>unitCode</u> .
<b><u>value</u></b>	<u>Boolean</u> <u>Number</u> <u>StructuredValue</u> <u>Text</u>	or or or The value of the quantitative value or property value node. • For <u>QuantitativeValue</u> and <u>MonetaryAmount</u> , the recommended type for values is 'Number'. • For <u>PropertyValue</u> , it can be 'Text;', 'Number', 'Boolean', or 'StructuredValue'.
<b><u>valueReference</u></b>	<u>Enumeration</u> <u>PropertyValue</u> <u>QualitativeValue</u> <u>QuantitativeValue</u> <u>StructuredValue</u>	or or or A pointer to a secondary value that provides additional information on the original value, e.g. a reference temperature.

\*the timestamp field is the only additional property to the schema.org QuantitativeValue

The ExtQuantitativeValue attribute type has an equivalent format rendered using NGSiv2 attribute value and metadata, the alternate format, equivalence and compatibility are explained in further details in Annex A

## 2.3 Generic Entity Data Model

This generic entity Data Model enables each instance of an entity or thing to be uniquely described using an agreed set of harmonised attributes in a uniform and consistent way. All the entities defined in this section are normative.

In this document we follow this entity definition convention:

Common mandatory attributes are always presented first and by definition are included in all entities. These are followed by entity specific mandatory attributes and finally entity specific optional attributes. Attribute naming will follow the lower camel case convention [8]. Generic entity definitions are taken from the schema.org [3] vocabulary wherever possible.

<Entity Name><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity. A globally unique reference to this entity instance.  It is recommended ids comply with RFC4122.	M	N
type	Text	The type of the entity. A choice of one of the entity types defined in this document.	M	N
dateCreated	DateTime	Entity creation timestamp. This will usually be allocated by the storage platform.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity. This will usually be allocated by the storage platform. A null value in this field or a value equivalent to dateCreated means the entity has not been modified since being created.	O	Y
source	URL	A sequence of characters giving the original source of the entity data as a URL. Recommended to be the fully qualified domain name of the source provider, or the URL to the source object.	R	Y
dataProvider	Text	A sequence of characters identifying the provider of the harmonised data entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an	R	Y

		external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"		
--	--	--	--	--

In addition to the generic entity attributes which are common to all entities, there are a set of entity specific attributes. In this document the entity specific attributes are listed for convenience in a separate table per entity as shown below:

<Entity Name><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
specificMan1	A valid attribute type	Some text describing a mandatory attribute which may not be null.	M	N
specificOptN	A valid attribute type	Some text describing an optional attribute which may be null.	O	Y

The combination of <Entity Name><Generic Attributes> and <Entity Name><Entity Specific Attributes> provides the definition of the complete harmonised data model of an Entity.

**Note:** That individual data providers may provide extensions to the harmonised data model which are specific to their implementations/ markets. Applications should therefore be written to accept additional attributes without throwing an error, and developers should consult implementation notes from data publishers to see if there are any extensions available to the harmonised data models.

### 2.3.1 AgriCrop

This entity contains a harmonised description of a generic crop. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriCrop><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null

id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriCrop".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	URL	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<AgriCrop><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this crop.	M	N
alternateName	Text	An alternative name for this crop.	O	Y
description	Text	A description of this crop.	R	Y
refAgriSoil	List of Reference	A List containing a JSON encoded sequence of characters that reference the unique Ids of the recommended soil(s).	O	Y
refAgriFertilizer	List of Reference	A List containing a JSON encoded sequence of characters that reference the unique Ids of the recommended fertiliser product(s).	O	Y
refAgriPest	List of	A List containing a JSON encoded sequence of characters that	O	Y

	Reference	reference the unique Ids of the pest(s) known to attack this crop.		
plantingFrom	List	<p>A List containing a JSON encoded sequence of characters of the recommended planting interval date(s) for this crop. Using The ISO8601 sequence of characters for each repeating date interval:</p> <p><b>interval, description</b></p> <p>Where <b>interval</b> is in the form of</p> <p>start date/end date</p> <p>--MM-DD/--MM-DD</p> <p>Meaning repeat each year from this start date to this end date.</p>	O	Y
harvestingInterval	List	<p>A list containing a JSON encoded sequence of characters of the recommended harvesting interval date(s) for this crop. Using The ISO8601 sequence of characters for each repeating date interval:</p> <p><b>interval , description</b></p> <p>Where <b>interval</b> is in the form of</p> <p>start date/end date</p> <p>--MM-DD/--MM-DD</p> <p>Meaning repeat each year between the specified start date and the specified end date.</p>	O	Y
wateringFrequency	Text	<p>A description of the recommended watering schedule. A choice from an enumerated list. One of:</p> <p><b>daily, weekly, biweekly, monthly, onDemand, other</b></p>	O	Y

### AgriCrop JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/c02633ceaab7f18afd489b559d2ab0f4>

```
{
  "id": "df72dc57-1eb9-42a3-88a9-8647ecc954b4",
  "type": "AgriCrop",
```

```
"dateCreated": {
  "value": "2016-08-22T19:20+00:00",
  "type": "DateTime"
},
"dateModified": {
  "value": "2016-08-22T19:20+00:00",
  "type": "DateTime"
},
"source": {
  "value": "http://www.samplefarmproduct.com",
  "type": "URL"
},
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"name": {
  "value": "Wheat",
  "type": "Text"
},
"alternateName": {
  "value": "Triticum aestivum",
  "type": "Text"
},
"description": {
  "value": "Spring wheat",
  "type": "Text"
},
"refAgriSoil": {
  "value": [
    "00411b56-bd1b-4551-96e0-a6e7fde9c840",
    "e8a8389a-edf5-4345-8d2c-b98ac1ce8e2a"
  ],
  "type": "List"
},
"refAgriFertilizer": {
  "value": [
    "1b0d6cf7-320c-4a2b-b2f1-4575ea850c73",
    "380973c8-4d3b-4723-a899-0c0c5cc63e7e"
  ],
  "type": "List"
},
"refAgriPest": {
  "value": [
    "10b52f07-079a-4390-8237-bf6a1c049a85",
    "66bdb09b-4fe0-4932-a267-f9eda4474d2a"
  ],
  "type": "List"
},
```

```

    "plantingFrom": {
      "value": [
        "-09-28/-10-12, Best Season",
        "-10-11/-10-18, Season OK"
      ],
      "type": "List"
    },
    "harvestingInterval": {
      "value": [
        "-03-21/-04-01, Best Season",
        "-04-02/-04-15, Season OK"
      ],
      "type": "List"
    },
    "wateringFrequency": {
      "value": "weekly",
      "type": "Text"
    }
  }
}
    
```

### 2.3.2 AgriGreenHouse

This entity contains a harmonised description of the conditions recorded within a generic greenhouse, a type of AgriParcel. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriGreenHouse><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to <b>"AgriGreenHouse"</b>	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	URL	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the	R	Y

		form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"		
--	--	--	--	--

<AgriGreenHouse><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refAgriParcel	Reference	Reference to the Unique id of the AgriParcel to which this record relates.	M	N
refWeatherObserved	Reference	A JSON encoded sequence of characters that reference the unique id of the related weather observed record.	O	Y
relativeHumidity	ExtQuantitativeValue (Number)	The inside relative humidity expressed as a number between 0 and 1 representing the range 0% to 100 (%).  $0 \leq \text{relativeHumidity} \leq 1$  Encoded as a ExtQuantitativeValue	R	Y
refAgriParcelRecord	List of Reference	Related AgriParcelRecords for this greenhouse.	O	Y
leafTemperature	ExtQuantitativeValue (Number)	The average greenhouse air temperature in degrees centigrade.  Encoded as a ExtQuantitativeValue.	R	Y
co2	ExtQuantitativeValue (Number)	The inside CO2 concentration in mg/L.  Encoded as a ExtQuantitativeValue.	O	Y
dailyLight	ExtQuantitativeValue (Number)	Daily Accumulated light measured in kW/m <sup>2</sup>  Encoded as a ExtQuantitativeValue.	O	Y
drainFlow	ExtQuantitativeValue (Number)	The observed drain flow rate in litres per second encoded as a ExtQuantitativeValue.	O	Y

refWaterQualityObserved	List of Reference	Reference to the id(s) of the WaterQualityObserved records relating to this greenhouse.	O	Y
-------------------------	-------------------	---	---	---

### 2.3.2.1 AgriGreenHouse JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/7936c30b050b698eed3fecfe43773b7a>

```
{
  "id": "ad500806-05ea-4ab6-812a-7a315d98e88d",
  "type": "AgriGreenHouse",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refAgriParcel": {
    "value": "c8b475e5-84a8-4346-ad79-cde1d2a4028b",
    "type": "Reference"
  },
  "refWeatherObserved": {
    "value": "c720cec5-ac6f-40b7-8e89-becb75702d0d",
    "type": "Reference"
  },
  "relativeHumidity": {
    "value": {
      "value": 0.40,
      "unitCode": "C62",
      "timestamp": "2016-08-22T19:20+00:00"
    },
    "type": "ExtQuantitativeValue"
  },
  "refAgriParcelRecord": {
    "value": [
      "8c3a525d-b42e-4048-bcdd-a119d8ddb0a5",

```

```
        "178d74c1-e6fe-4042-b955-2c164fc90b83"  
    ],  
    "type": "List"  
},  
"leafTemperature": {  
    "value": {  
        "value": 22,  
        "unitCode": "CEL",  
        "timestamp": "2016-08-22T19:20+00:00"  
    },  
    "type": "ExtQuantitativeValue"  
},  
"co2": {  
    "value": {  
        "value": 28,  
        "unitCode": "M1",  
        "timestamp": "2016-08-22T19:20+00:00"  
    },  
    "type": "ExtQuantitativeValue"  
},  
"dailyLight": {  
    "value": {  
        "value": 24,  
        "unitCode": "N78",  
        "timestamp": "2016-08-22T19:20+00:00"  
    },  
    "type": "ExtQuantitativeValue"  
},  
"drainFlow": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
        "value": 33,  
        "maxValue": 50,  
        "minValue": 25,  
        "unitCode": "G51",  
        "unitText": "Litre per second",  
        "timestamp": "2016-08-22T19:20+00:00"  
    }  
},  
"refWaterQualityObserved": {  
    "value": [  
        "49f86e0b-bb90-4751-a1c3-d5a891920807"  
    ],  
    "type": "List"  
}  
}
```

### 2.3.3 AgriParcel

This entity contains a harmonised description of a generic parcel of land. This entity is primarily associated with the agricultural vertical and related IoT applications.

#### <AgriParcel><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriParcel".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <AgriParcel><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
location	geo:json	The geo:json encoded polygon describing this parcel.	M	N
area	Number or ExtQuantitativeValue	The area of the parcel in square meters encoded as a Number or a ExtQuantitativeValue.	M	N

	(Number)			
description	Text	A description of the parcel.	R	Y
category	List	A choice of one or more values from an enumerated list describing the parcel category. <b>greenhouse, irrigated, rainfed.</b>	R	Y
refAgriCrop	Reference	A reference to the unique id of the AgriCrop associated with this Parcel.	M	N
cropStatus	Text	A choice from an enumerated list describing the crop planting status One of: <b>seeded, justBorn, growing, maturing, readyForHarvesting.</b>	R	Y
refAgriSoil	Reference	A reference to the unique id of the soil associated with this Parcel.	O	Y
dateLastPlanted	DateTime	The ISO8601 sequence of characters at which date and time the AgriCrop was planted in UTC.	R	Y
refDevice	List of Reference	A reference to the unique ids of the Devices used to monitor this parcel.	O	Y

### 2.3.3.1 AgriParcel JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/b82444f8ace1a379215b0b70a93d0bf5>

```
{
  "id": "72d9fb43-53f8-4ec8-a33c-fa931360259a",
  "type": "AgriParcel",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z ",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z ",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  }
}
```

```
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "location": {
    "value": {
      "type": "Polygon",
      "coordinates": [
        [100,0],
        [101,0],
        [101,1],
        [100,1],
        [100,0]
      ]
    },
    "type": "geo:json"
  },
  "area": {
    "value": 2000,
    "type": "Number"
  },
  "description": {
    "value": "North greenhouse (glass)",
    "type": "Text"
  },
  "category": {
    "value": [
      "greenhouse"
    ],
    "type": "List"
  },
  "refAgriCrop": {
    "value": "af3b2a4f-3133-4747-8e00-ba5e4cf1708b",
    "type": "Reference"
  },
  "cropStatus": {
    "value": "seeded",
    "type": "Text"
  },
  "refAgriSoil": {
    "value": "791f80c4-d621-4686-9bc0-84487084b9cf",
    "type": "Reference"
  },
  "dateLastPlanted": {
    "value": "2016-08-09T10:18:16Z",
    "type": "DateTime"
  },
  "refDevice": {
    "value": [
      "276805ff-d3fb-41bf-9714-ed0ecf2ee12b",
      "59b241f5-2827-44ea-bd1f-938567d271ea"
    ],
  },
```

```

        "type": "List"
    }
}
    
```

### 2.3.4 AgriParcelOperation

This entity contains a harmonised description of a generic operations performed on a parcel of land. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriParcelOperation><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriParcelOperation".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<AgriParcelOperation><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
----------------	----------------	-------------	----------------------------------	-------------

refAgriParcel	Reference	A reference to the unique id of the AgriParcel related to this operation.	M	N
operationType	Text	A choice from an enumerated list describing the operation performed on the parcel. One of:  <b>fertiliser, inspection, pesticide, water, other.</b>	R	Y
description	Text	A description of the operation.	R	Y
result	Text	A description of the results of the operation. One of:  <b>ok, aborted, failed.</b>	R	Y
startDate	DateTime	The planned start timestamp for the operation.	M	N
endDate	DateTime	The planned end timestamp for the operation.  Note that this is advisory and the actual time the operation finishes may be before or after the planned endDate.	M	N
status	Text	A choice from an enumerated list describing the status. One of:  <b>planned, ongoing, finished, scheduled, cancelled.</b>	R	Y
operator	Person	The operator performing this action encoded as a Schema.org person.  <a href="https://schema.org/Person">https://schema.org/Person</a>	O	Y
dateStarted	DateTime	Timestamp when the operation actually started to be performed.	R	Y
dateFinished	DateTime	Timestamp when the operation actually finished.	R	Y
refAgriProduct	Reference	A reference to the unique id of the AgriProduct used.	O	Y
quantity	ExtQuantitativeValue(Num ber)	The amount of water or product used encoded as a ExtQuantitativeValue.	O	Y
waterSource	Text	A choice from an enumerated list describing the water source. One of:	O	Y

		rainfall, watering.		
--	--	---------------------	--	--

### 2.3.4.1 AgriParcelOperation JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/6901c2e6f42ac5d21a8c5bbc7d8eb6fa>

```
{
  "id": "e1e9d3a3-074f-46f1-9375-52000d05a62b",
  "type": "AgriParcelOperation",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refAgriParcel": {
    "value": "318366a9-7643-4d8e-9a11-c76a8c29d8eb",
    "type": "Reference"
  },
  "operationType": {
    "value": "fertiliser",
    "type": "Text"
  },
  "description": {
    "value": "Monthly fertiliser application",
    "type": "Text"
  },
  "result": {
    "value": "ok",
    "type": "Text"
  },
  "startDate": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "endDate": {
    "value": "2016-08-28T10:18:16Z",

```

```

        "type": "DateTime"
    },
    "status": {
        "value": "ongoing",
        "type": "Text"
    },
    "operator": {
        "value": {
            "givenName": "John Smith",
            "jobTitle": "Tractor Operator"
        },
        "type": "Person"
    },
    "dateStarted": {
        "value": "2016-08-22T10:18:16Z",
        "type": "DateTime"
    },
    "dateFinished": {
        "value": "2016-08-28T10:18:16Z",
        "type": "DateTime"
    },
    "refAgriProduct": {
        "value": "a8f616b8-13fb-473a-8e61-b7a80c6c93ec",
        "type": "Reference"
    },
    "quantity": {
        "value": {
            "value": 40,
            "unitCode": "GM"
        },
        "type": "ExtQuantitativeValue"
    },
    "waterSource": {
        "value": "watering",
        "type": "Text"
    }
}
    
```

### 2.3.5 AgriParcelRecord

This entity contains a harmonised description of the conditions recorded on a generic parcel of land. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriParcelRecord><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N

type	Text	Must be equal to "AgriParcelRecord".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<AgriParcelRecord><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refAgriParcel	Reference	Unique id of the AgriParcel to which this record relates.	M	N
location	geo:json	The geo:json encoded polygon of this AgriParcelRecord.	M	N
soilTemperature	ExtQuantitativeValue(Number)	The observed soil temperature in degrees centigrade encoded as a ExtQuantitativeValue.	O	Y
temperature	ExtQuantitativeValue(Number)	The observed air temperature in degrees centigrade encoded as a ExtQuantitativeValue.	R	Y
soilMoistureVwc	ExtQuantitativeValue(Number)	Measured as Volumetric Water Content, VWC as a percentage.  $0 \leq \text{soilMoistureVwc} \leq 1$ encoded as a ExtQuantitativeValue	O	Y

soilMoistureEc	ExtQuantitativeValue(Number)	Measured as Electrical Conductivity, EC in units of Siemens per meter (S/m) encoded as a ExtQuantitativeValue	O	Y
solarRadiation	ExtQuantitativeValue(Number)	Measured in kW/m <sup>2</sup> encoded as a ExtQuantitativeValue.	O	Y
relativeHumidity	ExtQuantitativeValue(Number)	Relative Humidity a number between 0 and 1 representing the range of 0% to 100%  0 ≤ relativeHumidity ≤ 1 encoded as a ExtQuantitativeValue.	R	Y
atmosphericPressure	ExtQuantitativeValue(Number)	Atmospheric Pressure in units of hecto Pascals encoded as a ExtQuantitativeValue.	O	Y
description	Text	Description of this AgriParcelRecord.	R	Y

### 2.3.5.1 AgriParcelRecord JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/fbd5aeff87e6b73322bea447d5b0bb94>

```
{
  "id": "8f5445e6-f49b-496e-833b-e65fc97fcab7",
  "type": "AgriParcelRecord",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refAgriParcel": {
    "value": "d3676010-d815-468c-9e01-25739c5a25ed",
    "type": "Reference"
  }
}
```

```
},
"location": {
  "value": {
    "type": "Polygon",
    "coordinates": [
      [100, 0],
      [101, 0],
      [101, 1],
      [100, 1],
      [100, 0]
    ]
  },
  "type": "geo:json"
},
"soilTemperature": {
  "value": {
    "value": 27,
    "unitCode": "CEL"
  },
  "type": "ExtQuantitativeValue"
},
"temperature": {
  "value": {
    "value": 33,
    "unitCode": "CEL"
  },
  "type": "ExtQuantitativeValue"
},
"soilMoistureVwc": {
  "value": {
    "value": 0.08,
    "unitCode": "C62"
  },
  "type": "ExtQuantitativeValue"
},
"soilMoistureEc": {
  "value": {
    "value": 17,
    "unitCode": "D10"
  },
  "type": "ExtQuantitativeValue"
},
"solarRadiation": {
  "value": {
    "value": 15,
    "unitCode": "N78"
  },
  "type": "ExtQuantitativeValue"
},
"relativeHumidity": {
  "value": {
    "value": 0.15,
    "unitCode": "C62"
  }
}
```

```

    },
    "type": "ExtQuantitativeValue"
  },
  "atmosphericPressure": {
    "value": {
      "value": 1013.25,
      "unitCode": "A97"
    },
    "type": "ExtQuantitativeValue"
  },
  "description": {
    "value": "North greenhouse. Planting zone A ",
    "type": "Text"
  }
}

```

### 2.3.6 AgriPest

This entity contains a harmonised description of a generic agricultural pest. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriPest><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriPest".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version	R	Y

		of "1.0"		
--	--	----------	--	--

<AgriPest><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this agricultural pest.	M	N
alternateName	Text	Alternative name of this agricultural pest.	O	Y
description	Text	A description of this agricultural pest.	R	Y
refAgriProduct	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique ids of the recommended AgriProduct pesticide(s).	O	Y

### 2.3.6.1 AgriPest JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/df22eca28701a239b49cc744be8eb1ad>

```
{
  "id": "fb3f1295-500c-4aa3-b995-c909097d5c01",
  "type": "AgriPest",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "name": {
    "value": "Grasshopper",
```

```

        "type": "Text"
    },
    "alternateName": {
        "value": "Chorthippus parallelus",
        "type": "Text"
    },
    "description": {
        "value": "Common European grasshopper",
        "type": "Text"
    },
    "refAgriProduct": {
        "value": [
            "7f1d962b-0d14-479b-a50a-baaef261263a"
        ],
        "type": "List"
    }
}
    
```

### 2.3.7 AgriProductType

This entity contains a harmonised description of a generic agricultural product type. This entity is primarily associated with the agricultural vertical and related IoT applications. The AgriProductType includes a hierarchical structure that allows product types to be grouped in a flexible way.

<AgriProductType><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriProductType".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the	R	Y

		form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"		
--	--	--	--	--

<AgriProductType><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this AgriProductType.	M	N
description	Text	A description of this AgriProductType.	M	N
root	Boolean	A logical indicator that this product is the root of a AgriProductType hierarchy. Logical TRUE indicates it is a root.	M	N
refParentType	List of Reference	A JSON encoded sequence of characters referencing the unique ids of the AgriProductType groupings this AgriProductType is a member of.	O	Y

### 2.3.7.1 AgriProductType JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/6f5b29763c09d621f7e154e69d18a02c>

```
{
  "id": "398aa5f4-6a81-4dea-9f85-e9869441a257",
  "type": "AgriProductType",
  "dateCreated": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  }
}
```

```

    },
    "schemaVersion": {
      "value": "1.0",
      "type": "Text"
    },
    },
    "name": {
      "value": "Soft Fruits",
      "type": "Text"
    },
    },
    "description": {
      "value": "Soft edible fruits",
      "type": "Text"
    },
    },
    "root": {
      "value": false,
      "type": "Boolean"
    },
    },
    "refParentType": {
      "value": [
        "b99c940d-7156-4280-9a2b-4a9e533cd20e"
      ],
      "type": "List"
    }
  }
}

```

### 2.3.8 AgriSoil

This entity contains a harmonised description of soil. This entity is primarily associated with the agricultural vertical and related IoT applications.

<AgriSoil><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "AgriSoil".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y

schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y
---------------	-------------	---	---	---

<AgriSoil><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this soil type.	M	N
alternateName	Text	Alternative name of this soil type.	O	Y
description	Text	A description of this soil.	R	Y
refAgriProduct	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique ids of the recommended AgriProduct fertiliser (or other) product(s).	O	Y

### 2.3.8.1 AgriSoil JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/a3eae9503c856c835b56c8c98603cd5f>

```
{
  "id": "789363b4-c771-43d6-8505-ca582efe8fcd",
  "type": "AgriSoil",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.samplefarmproduct.com",
    "type": "URL"
  },
}
```

```
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"name": {
  "value": "Clay",
  "type": "Text"
},
"alternateName": {
  "value": "Heavy soil",
  "type": "Text"
},
"description": {
  "value": "Fine grained, poor draining soil. Particle size less than
0.002mm",
  "type": "Text"
},
"refAgriProduct": {
  "value": [
    "ea54eedf-d5a7-4e44-bddd-50e9935237c0",
    "275b4c08-5e52-4bb7-8523-74ce5d0007de"
  ],
  "type": "List"
}
}
```

### 2.3.9 AirQualityObserved

This entity contains a harmonised description of the air quality observed at a particular location and time. This entity is primarily associated with the vertical segment of the environment and may also be used in smart homes, smart cities, agriculture, industry and related IoT applications.

<AirQualityObserved><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>AirQualityObserved</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<AirQualityObserved><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refPOI	Reference	A reference to the unique ids of the Point of Interest (monitoring station) that originated this observation.	O	Y

refDevice	List of Reference	A list of references to the unique ids of the devices that originated this observation.	O	Y
location	geo:json	The geo:json encoded polygon or point location, of this observation.	M	N
dateObserved	DateTime	The date and time of this observation in ISO8601 UTC format.	R	Y
PM2.5	ExtQuantitativeValue	value --- Measured value timestamp --- date and time when measurement was taken unitCode --- normally GQ unitText --- normally microgram per cubic metre	O	Y
PM10	ExtQuantitativeValue	value --- Measured value timestamp --- date and time when measurement was taken unitCode --- normally GQ unitText --- normally microgram per cubic metre	O	Y
CO	ExtQuantitativeValue	value --- Measured value timestamp --- date and time when measurement was taken unitCode --- normally GQ unitText --- normally microgram per cubic metre	O	Y
O3	ExtQuantitativeValue	value --- Measured value timestamp --- date and time when measurement was taken unitCode --- normally GQ	O	Y

		<p>unitText ---                  normally microgram per                  cubic metre</p>		
SO2	ExtQuantitativeValue	<p>value ---                  Measured value</p> <p>timestamp --- date                  and time when measurement                  was taken</p> <p>unitCode ---                  normally GQ</p> <p>unitText ---                  normally microgram per                  cubic metre</p>	O	Y
NO	ExtQuantitativeValue	<p>value ---                  Measured value</p> <p>timestamp --- date                  and time when measurement                  was taken</p> <p>unitCode ---                  normally GQ</p> <p>unitText ---                  normally microgram per                  cubic metre</p>	O	Y
NO2	ExtQuantitativeValue	<p>value ---                  Measured value</p> <p>timestamp --- date                  and time when measurement                  was taken</p> <p>unitCode ---                  normally GQ</p> <p>unitText ---                  normally microgram per                  cubic metre</p>	O	Y
NOx	ExtQuantitativeValue	<p>value ---                  Measured value</p> <p>timestamp --- date                  and time when measurement                  was taken</p> <p>unitCode ---                  normally GQ</p> <p>unitText ---                  normally microgram per                  cubic metre</p>	O	Y

AQI	Number	Air Quality Index calculated according to the US EPA standard <sup>1</sup>	O	Y
-----	--------	--	---	---

### 2.3.9.1 AirQualityObserved JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/d1e46adc706d986ee9e752a5b425bcc>

```
{
  "id": "c9f32b35-a185-48e2-835f-c521efc294ab",
  "type": "AirQualityObserved",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refPOI": {
    "value": [
      "cdfd9cb8-ae2b-47cb-a43a-b9767ffd5c84"
    ],
    "type": "List"
  },
  "refDevice": [
    "5c9fb9dd-fc13-4fda-8f4c-f99a04f6f858"
  ],
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    }
  },
}
```

<sup>1</sup> <https://cfpub.epa.gov/airnow/index.cfm?action=aqibasics.aqi>

```
    "type": "geo:json"  
  },  
  "dateObserved": {  
    "value": "2016-08-08T10:18:16Z",  
    "type": "DateTime"  
  },  
  "PM2.5": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 187,  
      "unitCode": "GQ"  
    }  
  },  
  "PM10": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 50,  
      "unitCode": "GQ"  
    }  
  },  
  "CO": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 0.8,  
      "unitCode": "GQ"  
    }  
  },  
  "O3": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 300,  
      "unitCode": "GQ"  
    }  
  },  
  "SO2": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 7,  
      "unitCode": "GQ"  
    }  
  },  
  "NO": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 137,  
      "unitCode": "GQ"  
    }  
  },  
  "NO2": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 63,  
      "unitCode": "GQ"  
    }  
  }  
}
```

```
    }  
  },  
  "NOx": {  
    "type": "ExtQuantitativeValue",  
    "value": {  
      "value": 273,  
      "unitCode": "GQ"  
    }  
  },  
  "AQI": {  
    "type": "Number",  
    "value": 238  
  }  
}
```

### 2.3.10 Building

This entity contains a harmonised description of a building. This entity is associated with the vertical segments of smart homes, smart cities, industry and related IoT applications.

#### <Building><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>Building</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <Building><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refBuildingType	Reference	Refers to the buildingType that this building is an instance of.	M	N
category	List	One or more categories relevant to the building with choices based on for example <a href="http://wiki.openstreetmap.org/wiki/Ma">http://wiki.openstreetmap.org/wiki/Ma</a>	R	Y

		<a href="#">p_Features#Building</a>		
containedInPlace	geo:json	The geo:json encoded polygon of the building plot in which this building sits.	R	Y
location	geo:json	The geo:json encoded polygon of this building.	M	N
address	PostalAddress	The building PostalAddress encoded as a Schema.org PostalAddress.  <a href="https://schema.org/PostalAddress">https://schema.org/PostalAddress</a>	R	Y
owner	List of references to Person(s) or Organization(s)	A List containing a JSON encoded sequence of characters referencing the unique Ids of the owner(s).  Related to a Schema.org person or organization.  <a href="https://schema.org/Person">https://schema.org/Person</a>  <a href="https://schema.org/Organization">https://schema.org/Organization</a>	R	Y
occupier	List of references to Person(s) or Organization(s)	A List containing a JSON encoded sequence of characters referencing the unique Ids of the occupiers(s).  Related to a Schema.org person or organization.  <a href="https://schema.org/Person">https://schema.org/Person</a>  <a href="https://schema.org/Organization">https://schema.org/Organization</a>	R	Y
refSubscriptionService	List of Reference	A List containing a JSON encoded sequence of characters of the unique Ids of the subscription service(s) related to this building.	O	Y
floorsAboveGround	Number	The number of floors above ground level in this building.	O	Y
floorsBelowGround	Number	The number of floors below ground level in this building.	O	Y
description	Text	An optional description of the entity.	R	Y
mapUrl	URL	A URL to a mapping service which shows the location of the building.	O	Y
notes	List	Free format notes relating to the building e.g. published occupants, opening hours etc.	O	Y

### 2.3.10.1 Building JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/69f8893b605894640e3b99f82c3f20ed>

```
{
  "id": "f95c06e3-776e-4a57-9b00-a85e3da145c1",
  "type": "Building",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refBuildingType": {
    "value": "8b1f2bf0-5093-4182-ad4b-224182bb3b9f",
    "type": "Reference"
  },
  "category": {
    "value": [
      "house"
    ],
    "type": "List"
  },
  "containedInPlace": {
    "value": {
      "type": "Polygon",
      "coordinates": [
        [100, 0],
        [101, 0],
        [101, 1],
        [100, 1],
        [100, 0]
      ]
    },
    "type": "geo:json"
  },
  "location": {
```

```
"value": {
  "type": "Polygon",
  "coordinates": [
    [100, 0],
    [101, 0],
    [101, 1],
    [100, 1],
    [100, 0]
  ]
},
"type": "geo:json"
},
"address": {
  "type": "PostalAddress",
  "value": {
    "addressLocality": "London",
    "postalCode": "EC4N 8AF",
    "streetAddress": "25 Walbrook"
  }
},
"owner": {
  "value": [
    "cdfd9cb8-ae2b-47cb-a43a-b9767ffd5c84",
    "1be9cd61-ef59-421f-a326-4b6c84411ad4"
  ],
  "type": "List"
},
"occupier": {
  "value": [
    "9830f692-7677-11e6-838b-4f9fb3dc5a4f"
  ],
  "type": "List"
},
"refSubscriptionService": {
  "value": [
    "b4fb8bff-1a8f-455f-8cc0-ca43c069f865onService1",
    "55c24793-3437-4157-9bda-667c9e1531fc"
  ],
  "type": "List"
},
"floorsAboveGround": {
  "value": 7,
  "type": "Number"
},
"floorsBelowGround": {
  "value": 0,
  "type": "Number"
},
"description": {
  "value": "Multi-tenant office block",
  "type": "Text"
},
"mapUrl": {
```

```
    "value":  
    "https://www.google.co.uk/maps/place/The+Walbrook,+Walbrook,+London+EC4N+8A  
F/@51.5120758,-0.0920769",  
    "type": "URL"  
  },  
  "notes": {  
    "value": ["Intelligent entry barrier system", "Intelligent air  
conditioning units", "Normal opening 07:00 - 20:00"],  
    "type": "List"  
  }  
}
```

### 2.3.11 BuildingOperation

This entity contains a harmonised description of a generic operation (related to smart buildings) applied to the referenced building. The building operation contains dynamic data reported by, or associated with a building or operations applicable to the building. This entity is associated with the vertical segments of smart homes, smart cities, industry and related IoT applications.

#### <BuildingOperation><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>BuildingOperation</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <BuildingOperation><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refBuilding	Reference	Refers to the unique entity Id of the building to which this building record	M	N

		relates.		
operationType	Text	Defines the type of operation conducted/ requested. This will be one of a defined list of operation types specific to the building.	R	Y
description	Text	A description of the operation.	R	Y
result	Text	A description of the results of the operation. One of  <b>ok, aborted, failed</b>	R	Y
startDate	DateTime	The planned start timestamp for the operation.	M	N
endDate	DateTime	The planned end timestamp for the operation.  Note that this is advisory and the actual time the operation finishes may be before or after the planned endDate.	M	N
status	Text	A choice from an enumerated list describing the status. One of:  <b>planned, ongoing, finished, scheduled, cancelled</b>	R	Y
operator	Person	The operator performing this action encoded as a Schema.org person.  <a href="https://schema.org/Person">https://schema.org/Person</a>	O	Y
dateStarted	DateTime	Timestamp when the operation actually started to be performed.	R	Y
dateFinished	DateTime	Timestamp when the operation actually finished.	R	Y
operationSequence	Text	The sequence of operations executed/ requested for the building in a representation format relevant to the building.	O	Y
refRelatedBuilding Operation	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique ids of any related building operations.	O	Y
refRelatedOperation	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique ids of any related operations (device, machine or	O	Y

		other).		
--	--	---------	--	--

### 2.3.11.1 BuildingOperation JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/2c15fe4070fbbf5ed5227ccabf19b639>

```
{
  "id": "57b912ab-eb47-4cd5-bc9d-73abece1f1b3",
  "type": "BuildingOperation",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refBuilding": {
    "value": "f59e2074-0032-4ccd-b0dd-f06370ffb6af",
    "type": "Reference"
  },
  "operationType": {
    "value": "Air Conditioning Switch To Low Power",
    "type": "Text"
  },
  "description": {
    "value": "Air conditioning levels reduced due to out of hours",
    "type": "Text"
  },
  "result": {
    "value": "Operation successful",
    "type": "Text"
  },
  "startDate": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "endDate": {
    "value": "2016-08-20T10:18:16Z",
```

```
    "type": "DateTime"
  },
  "status": {
    "value": "planned",
    "type": "Text"
  },
  "dateStarted": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateFinished": {
    "value": "2016-08-20T10:18:16Z",
    "type": "DateTime"
  },
  "operationSequence": {
    "value": "Fan levels reduced to minimum. Target temperature set to 24
degrees Celsius. ",
    "type": "Text"
  },
  "refRelatedBuildingOperation": {
    "value": [
      "b4fb8bff-1a8f-455f-8cc0-ca43c069f865onService1",
      "55c24793-3437-4157-9bda-667c9e1531fc"
    ],
    "type": "List"
  },
  "refRelatedOperation": {
    "value": [
      "36744245-6716-4a28-84c7-0e3d7520f143",
      "33b2b713-9223-40a5-87a0-3f80a1264a6c"
    ],
    "type": "List"
  }
}
```

### 2.3.12 BuildingType

This entity contains a harmonised description of a generic building type. This entity is associated with the vertical segments of smart home, smart cities, industry and related IoT applications. The building type includes a hierarchical structure that allows building types to be grouped in a flexible way.

#### <BuildingType><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>BuildingType</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <BuildingType><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this BuildingType.	M	N
description	Text	A description of this type.	R	Y

root	Boolean	A logical indicator that this is the root of a BuildingType hierarchy. TRUE indicates it is the root, FALSE indicates that it is not the root.	M	Y
refParentType	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique Ids of the building type groupings this BuildingType is a member of.	O	Y

### 2.3.12.1 BuildingType JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/8e82b3af9d333ca56658acff1a6f20ca>

```
{
  "id": "57b912ab-eb47-4cd5-bc9d-73abece1f1b3",
  "type": "BuildingType",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "name": {
    "value": "House",
    "type": "Text"
  },
  "description": {
    "value": "Standard building type definition for a domestic house",
    "type": "Text"
  },
  "root": {
    "value": false,
    "type": "Boolean"
  },
  "refParentType": {
    "value": [
```

```

        "4146335f-839f-4ff9-a575-6b4e6232b734",
        "c44fc765-51a7-4f71-bf1e-22e874c35180"
    ],
    "type": "List"
}
}
    
```

### 2.3.13 Device

This entity contains a harmonised description of a generic device. This entity provides an essentially static description of a generic device and is therefore applicable to all IoT segments and related IoT applications.

<Device><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "Device".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Device><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refDeviceModel	Reference	Unique id of this device model selected from DeviceModel.	M	N
serialNumber	Text	The serial number assigned by the manufacturer.	M	N
supplierName	Text	The details of the supplier of this device.	R	Y
manufacturerCountry	Text	The country where this device was manufactured.	R	Y
factory	Text	The factory name/code manufacturing this device.	O	Y
dateManufactured	DateTime	The ISO8601 sequence of characters at which date and time the device was manufactured in UTC.	M	N
description	Text	An optional description of this device.	R	Y
owner	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique Ids of the owner(s).  Related to a Schema.org person or organization.  <a href="https://schema.org/Person">https://schema.org/Person</a>  <a href="https://schema.org/Organization">https://schema.org/Organization</a>	O	Y
dateInstalled	DateTime	The ISO8601 sequence of characters at which date and time the device was installed in UTC.	R	N
dateFirstUsed	DateTime	The ISO8601 sequence of characters at which date and time the device was first used in UTC.	R	N
hardwareVersion	Text	The hardware version of this device.	R	N
firmwareVersion	Text	The firmware version of this device.	R	N
softwareVersion	Text	The software version of this device.	R	N
osVersion	Text	The operating system version of this device.	R	N

supportedProtocol	List	A List element per supported communication protocol.	O	N
location	geo:json	The geo:json encoded location, of this device.	O	Y
online	Boolean	The communication status of this device. A logical representation of Offline (false) or Online (true).	O	N
status	Text	The text format (current) device status code or description. Expected to be the manufacturer or device specific status code generated by the device.	R	Y
dateLastCalibration	DateTime	The date this device was last calibrated.	O	Y
batteryLevel	ExtQuantitativeValue (Number)	Battery level. It must be equal to: 1.0 When the battery charge is full. 0.0 When the battery charge empty. Null when it cannot be determined.  Normally encoded as an ExtQuantitativeValue.	O	Y
value	ExtQuantitativeValue (Number)	The observed or reported value of the device. For control applications the value can be updated to change the device/ actuator setting. The value is encoded as an ExtQuantitativeValue.	R	Y

### 2.3.13.1 Device JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/b29f6f3841d778d455e58fcad74c637d>

```
{
  "id": "ba2d4fd9-f57f-4610-a589-2d52670d14f3",
  "type": "Device",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
}
```

```
"source": {
  "value": "http://www.example.com",
  "type": "URL"
},
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"refDeviceModel": {
  "value": "d1be2e61-d9e7-43cd-9c68-51e0861b3a49",
  "type": "Reference"
},
"serialNumber": {
  "value": "123456789",
  "type": "Text"
},
"supplierName": {
  "value": "ACME Direct, Inc.",
  "type": "Text"
},
"manufacturerCountry": {
  "value": "UK",
  "type": "Text"
},
"factory": {
  "value": "56A8",
  "type": "Text"
},
"dateManufactured": {
  "value": "2016-08-21T10:18:16Z",
  "type": "DateTime"
},
"description": {
  "value": "Thermocouple",
  "type": "Text"
},
"owner": {
  "value": [
    "43c46ff2-b0f7-4e4f-838a-adeelc9cae88",
    "ebf421c9-363b-4ed4-97a0-93a6e39786ff"
  ],
  "type": "List"
},
"dateInstalled": {
  "value": "2016-08-22T10:18:16Z",
  "type": "DateTime"
},
"dateFirstUsed": {
  "value": "2016-08-22T10:18:16Z",
```

```
    "type": "DateTime"
  },
  "hardwareVersion": {
    "value": "1.2",
    "type": "Text"
  },
  "firmwareVersion": {
    "value": "2.8.56",
    "type": "Text"
  },
  "softwareVersion": {
    "value": "2.5.11",
    "type": "Text"
  },
  "osVersion": {
    "value": "8.1",
    "type": "Text"
  },
  "supportedProtocol": {
    "value": [
      "HTTP",
      "HTTPS",
      "FTP"
    ],
    "type": "List"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    },
    "type": "geo:json"
  },
  "online": {
    "value": true,
    "type": "Boolean"
  },
  "status": {
    "value": "SC1001",
    "type": "Text"
  },
  "dateLastCalibration": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "batteryLevel": {
    "value": {
      "value": 0.7
    },
    "type": "ExtQuantitativeValue"
  }
}
```

```
  },  
  "value": {  
    "value": {  
      "value": 1  
    },  
    "type": "ExtQuantitativeValue"  
  }  
}
```

### 2.3.14 DeviceModel

This entity contains a harmonised description of a generic device model and is therefore applicable to all IoT segments and related IoT applications. The Device Model includes an optional hierarchical structure that allows device types to be grouped in a flexible way.

#### <DeviceModel><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "DeviceModel".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <DeviceModel><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this DeviceModel.	M	N
doc	URL	Reference to Product Data Sheet or other manufacturer's documentation about this device model including where relevant, details of the	R	Y

		accuracy, trueness, precision and units of measure.		
category	List	A choice from an enumerated list defining the category of this device including:  <b>sensor, actuator, meter, appliance, heater, chiller, lighting, boiler, vessel, airHandlingUnit, consumer, other.</b>	O	Y
description	Text	A description of this DeviceModel .	R	Y
manufacturerName	Text	The name of manufacturer of this DeviceModel.	R	Y
brandName	Text	A description of the brand name of this DeviceModel.	R	Y
root	Boolean	A logical indicator that this DeviceModel is the root of a DeviceModel hierarchy. TRUE indicates it is the root, FALSE indicates that it is not the root.	R	Y
refParentDeviceModel	List of Reference	A List containing a JSON encoded sequence of characters of the unique Ids of the device model groupings this device model is a member of.	O	Y

### 2.3.14.1 DeviceModel JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/c4765078362cfefd61909fc92b27b4ee>

```
{
  "id": "e01f13d1-fea4-4cc4-92c9-0d9fad2c509",
  "type": "DeviceModel",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
```

```
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "name": {
    "value": "Sensor Model 501",
    "type": "Text"
  },
  "doc": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "category": {
    "value": [
      "sensor"
    ],
    "type": "List"
  },
  "description": {
    "value": "Monomatics All Weather Temperature Sensor",
    "type": "Text"
  },
  "manufacturerName": {
    "value": "ACME Manufacturing, Inc.",
    "type": "Text"
  },
  "brandName": {
    "value": "SuperWidgets",
    "type": "Text"
  },
  "root": {
    "value": false,
    "type": "Boolean"
  },
  "refParentDeviceModel": {
    "value": [
      "4146335f-839f-4ff9-a575-6b4e6232b734",
      "c44fc765-51a7-4f71-bf1e-22e874c35180"
    ],
    "type": "List"
  }
}
```

### 2.3.15 DeviceOperation

This entity contains a harmonised description of a generic device operation entity. The device operation entity contains dynamic data reported by a device and is therefore applicable to all IoT segments and related IoT applications.

<DeviceOperation><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>DeviceOperation</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<DeviceOperation><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refDevice	Reference	The unique entity Id of the device to which this device operation relates.	M	N
operationType	List	Choice form an enumerated list including:  <b>event, maintenance, fault, installation, upgrade, other.</b>	R	Y
description	Text	A description of the operation.	R	Y

result	Text	A description of the results of the operation. One of  <b>ok, aborted, failed</b>	R	Y
startDate	DateTime	The planned start timestamp for the operation.	M	N
endDate	DateTime	The planned end timestamp for the operation.  Note that this is advisory and the actual time the operation finishes may be before or after the planned endDate.	M	N
status	Text	A choice from an enumerated list describing the status. One of:  <b>planned, ongoing, finished, scheduled, cancelled.</b>	R	Y
operator	Person	The operator performing this action encoded as a Schema.org person.  <a href="https://schema.org/Person">https://schema.org/Person</a>	O	Y
dateStarted	DateTime	Timestamp when the operation actually started to be performed.	R	Y
dateFinished	DateTime	Timestamp when the operation actually finished.	R	Y
dateReported	DateTime	The timestamp when the device event or fault was reported.	O	Y
dateAddressed	DateTime	The timestamp when the event or fault was addressed or cleared.	O	Y

### 2.3.15.1 DeviceOperation JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/dbaba83f8fab072c6a4765823228cc12>

```
{
  "id": "27577638-bd8a-4732-b418-fc8b949a0b0f",
  "type": "DeviceOperation",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  }
}
```

```
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refDevice": {
    "value": "2033a7c7-d31b-48e7-91c2-014dc426c29e",
    "type": "Reference"
  },
  "operationType": {
    "value": [
      "fault"
    ],
    "type": "List"
  },
  "description": {
    "value": "Backup battery needs replacement",
    "type": "Text"
  },
  "result": {
    "value": "ok",
    "type": "Text"
  },
  "startDate": {
    "value": "2016-08-20T10:18:16Z",
    "type": "DateTime"
  },
  "endDate": {
    "value": "2016-08-18T14:18:16Z",
    "type": "DateTime"
  },
  "status": {
    "value": "ongoing",
    "type": "Text"
  },
  "operator": {
    "value": {
      "givenName": "John Dee"
    },
    "type": "Person"
  },
  "dateStarted": {
    "value": "2016-08-20T10:18:16Z",
    "type": "DateTime"
  },
  },
```

```
"dateFinished": {  
  "value": "2016-08-18T10:18:16Z",  
  "type": "DateTime"  
},  
"dateReported": {  
  "value": "2016-08-18T10:18:16Z",  
  "type": "DateTime"  
}  
}
```

### 2.3.16 EnvironmentObserved

This entity contains a harmonised description of the environmental conditions observed at a particular location and time. This entity is primarily associated with the vertical segment of the environment and agriculture but may also be used in smart home, smart cities, industry and related IoT applications.

#### <EnvironmentObserved><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>EnvironmentObserved</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <EnvironmentObserved><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
location	geo:json	The geo:json encoded map location, of this observation.	M	N

refWeatherObserved	List of Reference	A List containing a JSON encoded sequence of characters that reference the unique ids of the related weather entities.	O	Y
refAirQualityObserved	List of Reference	A List containing a JSON encoded sequence of characters that reference the unique ids of the related AirQualityObserved entities.	O	Y
refWaterQualityObserved	List of Reference	A List containing a JSON encoded sequence of characters that reference the unique ids of the related WaterQuality entities.	O	Y

### 2.3.16.1 EnvironmentObserved JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/63d18a7f5845aa201c9470d84b7912f8>

```
{
  "id": "33f02632-74f4-4c96-9ba1-e26945de9481",
  "type": "EnvironmentObserved",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    }
  },
  "type": "geo:json"
}
```

```

    },
    "refWeatherObserved": {
      "value": [
        "fae29f4c-0691-4bab-bef8-ad1cd165cc28",
        "1c7a2711-ae38-4ea9-8f9f-627067067d53"
      ],
      "type": "List"
    },
    "refAirQualityObserved": {
      "value": [
        "4b8b09c9-ce54-46de-8067-5591e02d8f29",
        "08a14933-b44d-4297-b2d2-2c3f3844012e"
      ],
      "type": "List"
    },
    "refWaterQualityObserved": {
      "value": [
        "68a83e68-61e6-4e3c-975c-5b301c184ca6",
        "b01518e3-2b60-4bbd-9783-3af0d660349e"
      ],
      "type": "List"
    }
  }
}

```

### 2.3.17 Machine

This entity contains a harmonised description of an industrial machine for example for use in CAM (Computer Aided Manufacturing). This entity provides an essentially static description of a generic automation machine. This entity is primarily associated with the industry segment in the automated manufacturing industry, including CNC (Computer Numerical Control) machines, 3D printers and all kinds of industrial robots.

<Machine><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to <b>"Machine"</b> .	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised	R	Y

		entity.		
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Machine><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refMachineModel	Reference	Refers to the machineModel that this machine is an instance of.	M	N
serialNumber	Text	The serial number assigned by the manufacturer.	R	N
status	Text	A manufacturer specific text format machine status code or description. It is an aggregation of dynamic information about the machine.	R	Y
assetIdentifier	Text	An asset identifier (e.g. asset tag number) assigned by the owner.	O	Y
manufacturerCountry	Text	The country where this machine instance was manufactured.	O	Y
factory	Text	The factory name/code manufacturing this machine.	O	Y
dateManufactured	DateTime	The ISO8601 sequence of characters at which date and time the machine was manufactured in UTC.	R	Y
dateInstalled	DateTime	The ISO8601 sequence of characters at which date and time the machine was installed in UTC.	R	Y
dateFirstUsed	DateTime	The ISO8601 sequence of characters at which date and time the machine was first used in UTC.	R	Y

online	Boolean	Identifies the communication status of the machine, online if set to TRUE.	R	Y
installationNotes	Text or URL	Notes relating to this machine installation.	O	Y
location	geo:json	The geo:json encoded location, of this machine.	M	N
refBuilding	Reference	Refers to the building instance into which this machine is installed.	O	Y
owner	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique Ids of the owner(s).  Related to a Schema.org person or organization.  <a href="https://schema.org/Person">https://schema.org/Person</a>  <a href="https://schema.org/Organization">https://schema.org/Organization</a>	O	Y
refSubscriptionService	List of Reference	A List containing a JSON encoded sequence of characters of the unique Ids of any subscription service(s) associated with this machine.	O	Y
description	Text	An optional description of this machine.	R	Y

### 2.3.17.1 Machine JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/7b8303207db9fd5b7cf933ca360a5dd7>

```
{
  "id": "9166c528-9c98-4579-a5d3-8068aea5d6c0",
  "type": "Machine",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
```

```
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refMachineModel": {
    "value": "00b42701-43e1-482d-aa7a-e2956cfd69c3",
    "type": "Reference"
  },
  "serialNumber": {
    "value": "123456789",
    "type": "Text"
  },
  "status": {
    "value": "Ready/Idle : Machine operational",
    "type": "Text"
  },
  "assetIdentifier": {
    "value": "1234567",
    "type": "Text"
  },
  "manufacturerCountry": {
    "value": "UK",
    "type": "Text"
  },
  "factory": {
    "value": "ACME NorthEast Inc.",
    "type": "Text"
  },
  "dateManufactured": {
    "value": "2016-08-21T10:18:16Z",
    "type": "DateTime"
  },
  "dateInstalled": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "dateFirstUsed": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "online": {
    "value": true,
    "type": "Boolean"
  },
  "installationNotes": {
    "value": "http://www.example.com/installationNotel.txt",
    "type": "URL"
  },
  "location": {
    "value": {
      "type": "Point",
```

```
    "coordinates": [
      -104.99404,
      39.75621
    ]
  },
  "type": "geo:json"
},
"refBuilding": {
  "value": "8683b757-649c-49e0-ac89-ad392c9a0d0c",
  "type": "Reference"
},
"owner": {
  "value": [
    "247d402f-3e0b-4e7c-a2c0-335590c27f90",
    "a7995eb7-6bec-4176-b2e8-af545e2bb3b9"
  ],
  "type": "List"
},
"refSubscriptionService": {
  "value": [
    "92158a14-f6c6-4d29-85d1-5d305cc87982",
    "3c6bac7b-9398-4529-8d89-766435b7490b"
  ],
  "type": "List"
},
"description": {
  "value": "Industrial machine to create plastic bottles",
  "type": "Text"
}
}
```

### 2.3.18 MachineModel

This entity contains a harmonised description of a generic machine model. This entity is primarily associated with the industry segment and related IoT applications. The machineModel includes a hierarchical structure that allows machine models to be grouped in a flexible way.

#### <MachineModel><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>MachineModel</b> ".	M	N
dateCreated	Date	Entity creation timestamp.	M	N
dateModified	Date	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <MachineModel><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name given to this machine model.	M	N
description	Text	A description of this machine model.	R	Y

manufacturerName	Text	The name of manufacturer of this machine model.	R	Y
brandName	Text	A description of this machine model brand name.	R	Y
version	Text	The manufacturer defined version number for the machine model.	R	Y
category	List	A List of functional categories which this machineModel supports. Examples include:  <code>robot, cnc, 2dPrinter, 3dPrinter, 3dScanner, lathe, injectionMolding, laserCutter, millingMachine, grindingMachine, stampingMachine, oven, kiln, packaging, mixer, dryer, fan, saw.</code>	O	Y
doc	URL	Reference to Product Data Sheet or other manufacturers documentation about this machine.	R	Y
root	Boolean	A logical indicator that this machineModel is the root of a machineModel hierarchy. <code>true</code> indicates it is the root, <code>false</code> indicates that it is not the root.	R	Y
refParentModel	List of Reference	A List containing a JSON encoded sequence of characters referencing the ids of other machine models which this is related to.	O	Y
processDescription	Text	A description of the industrial process carried out by this machine.	O	Y
standardOperations	List	Lists the standard set of operations supported by this machineModel.	O	Y

### 2.3.18.1 MachineModel JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/d292853b17e78269856715a005b7a733>

```
{
  "id": "e01f13d1-fea4-4cc4-92c9-0d9fadb2c509",
  "type": "MachineModel",
  "dateCreated": {
```

```
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "name": {
    "value": "CA1256b",
    "type": "Text"
  },
  "description": {
    "value": "Machine to screen print t-shirts",
    "type": "Text"
  },
  "manufacturerName": {
    "value": "ScreenOPrint, Inc.",
    "type": "Text"
  },
  "brandName": {
    "value": "QuickT",
    "type": "Text"
  },
  "version": {
    "value": "v1",
    "type": "Text"
  },
  "category": {
    "value": [
      "2dPrinter"
    ],
    "type": "List"
  },
  "doc": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "root": {
    "value": false,
    "type": "Boolean"
  },
  },
```

```
"refParentModel": {
  "value": [
    "4146335f-839f-4ff9-a575-6b4e6232b734",
    "c44fc765-51a7-4f71-bf1e-22e874c35180"
  ],
  "type": "List"
},
"processDescription": {
  "value": "Industrial printer used to mass print t-shirts",
  "type": "Text"
},
"standardOperations": {
  "value": [
    "print"
  ],
  "type": "List"
}
}
```

### 2.3.19 MachineOperation

This entity contains a harmonised description of a generic machine operation. This entity is primarily associated with the industry segment and related IoT applications. Each MachineOperation instance will be related to a specific Machine instance.

#### <MachineOperation><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>MachineOperation</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <MachineOperation><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refMachine	Reference	Refers to the specific machine instance that this machineOperation record relates to.	M	N

operationType	Text	Defines the type of operation conducted/ requested. This will be one of a defined list of operation types specific to the machine/ machineModel.	M	N
description	Text	A description of the operation conducted or applied.	R	Y
result	Text	A description of the results of the operation. One of:  <b>ok, aborted, failed</b>	R	Y
startDate	DateTime	The planned start timestamp for the operation.	R	Y
endDate	DateTime	The planned end timestamp for the operation.  Note that this is advisory and the actual time the operation finishes may be before or after the planned endDate.	R	Y
status	Text	A choice from an enumerated list describing the status. One of:  <b>planned, ongoing, finished, scheduled, cancelled.</b>	R	Y
operator	Person	The operator performing this action encoded as a Schema.org person.  <a href="https://schema.org/Person">https://schema.org/Person</a>	O	Y
dateStarted	DateTime	Timestamp when the operation actually started to be performed.	O	Y
dateFinished	DateTime	Timestamp when the operation actually finished.	O	Y
commandSequence	Text	The command sequence executed/ requested for the machine in a representation format relevant to the machine.	O	Y

### 2.3.19.1 MachineOperation JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/32169966d47e0e128bb37fe08937dfd3>

{

```
"id": "27577638-bd8a-4732-b418-fc8b949a0b0f",
"type": "MachineOperation",
"dateCreated": {
  "value": "2016-08-08T10:18:16Z",
  "type": "DateTime"
},
"dateModified": {
  "value": "2016-08-08T10:18:16Z",
  "type": "DateTime"
},
"source": {
  "value": "http://www.example.com",
  "type": "URL"
},
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"refMachine": {
  "value": "2033a7c7-d31b-48e7-91c2-014dc426c29e",
  "type": "Reference"
},
"operationType": {
  "value": "tShirtPrint",
  "type": "Text"
},
"description": {
  "value": "Printing of 1000 T-shirts",
  "type": "Text"
},
"result": {
  "value": "ok",
  "type": "Text"
},
"startDate": {
  "value": "2016-08-20T10:18:16Z",
  "type": "DateTime"
},
"endDate": {
  "value": "2016-08-18T14:18:16Z",
  "type": "DateTime"
},
"status": {
  "value": "finished",
  "type": "Text"
},
"operator": {
  "value": {
    "name": "Fred Quimby",
```

```

        "jobTitle": "Print Supervisor"
    },
    "type": "Person"
},
"dateStarted": {
    "value": "2016-08-20T10:18:16Z",
    "type": "DateTime"
},
"dateFinished": {
    "value": "2016-08-18T14:18:16Z",
    "type": "DateTime"
},
"commandSequence": {
    "value": "Select inks. Prepare print masks. Print shirts. Clean print
heads and rollers ",
    "type": "Text"
}
}
    
```

### 2.3.20 PointOfInterest

This entity contains a harmonised geographic description of a Point of Interest. This entity is used in applications that use spatial data and is applicable to Automotive, Environment, Industry and Smart City vertical segments and related IoT applications.

<PointOfInterest><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>PointOfInterest</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g.	R	Y

		<a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"		
--	--	--	--	--

<PointOfInterest><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
location	geo:json	The geo:json encoded map location (point or polygon or multi-polygon), of this point of interest.	M	N
category	List	A JSON encoded List of one or more sequence of characters referring to category codes as per the taxonomy definition at <a href="https://github.com/Factual/places/blob/master/categories/factual_taxonomy.json">https://github.com/Factual/places/blob/master/categories/factual_taxonomy.json</a>  The respective locale specific category can be accessed via a lookup of the JSON dictionary.	M	Y
description	Text	An optional description of the entity.	R	Y
place	Place	The schema.org place definition for this Point Of Interest. See <a href="https://schema.org/Place">https://schema.org/Place</a>	R	Y

**2.3.20.1 PointOfInterest JSON**

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/4cd7203d66ccf2caf2123cf4519f5f74>

```
{
  "id": "44e47705-90c3-4dbc-a0ae-7810306de5e9",
  "type": "PointOfInterest",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
```

```
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    },
    "type": "geo:json"
  },
  "category": {
    "value": [
      "36"
    ],
    "type": "List"
  },
  "description": {
    "value": "Learn all about mobile at the GSMA Academy",
    "type": "Text"
  },
  "place": {
    "type": "Place",
    "value": {
      "name": "GSMA Academy",
      "address": {
        "type": "PostalAddress",
        "addressLocality": "London",
        "postalCode": "EC4N 8AF",
        "streetAddress": "25 Walbrook"
      },
      "telephone": "0212345678"
    }
  }
}
```

### 2.3.21 Product

This entity contains a harmonised description of a generic product. This entity is primarily associated with products and supply chains. It is the harmonised description of the <http://gs1.org/voc/Product>:

<Product><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>Product</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Product><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
productType	Reference	Unique id of this product type. Refers to the relevant ProductType record.	R	Y
supplierName	Text	The details of the local retailer of this product.	R	Y

category	List	A choice from an enumerated list. including:  <b>fertiliser, herbicide, pesticide, other</b>	R	Y
gtin	Text	GS1 product code  A Global Trade Item Number (GTIN) is the 14 digit GS1 Identification Key used to identify products. The key comprises a GS1 Company Prefix followed by an Item Reference Number and a Check Digit.  See <a href="http://www.gs1.org/gtin">http://www.gs1.org/gtin</a> for more details.  There are four GTIN formats. A uniform 14-digit format is required for this harmonised model, add leading zeros as required:  00000nnnnnnnn (GTIN-8) 00nnnnnnnnnnnn (GTIN-12) 0nnnnnnnnnnnnnn (GTIN-13)	O	Y
productName	Text	The name of this product.	R	Y
description	Text	A description of this product.	R	Y
manufacturerName	Text	The name of manufacturer of this product.	R	Y
brand	Text	A description of this brand name.	R	Y
inPackageWidth	QuantitativeValue	The width of the product in the package, as measured according to the GS1 Package Measurement Rules. See <a href="http://www.gs1.org/package-measurement-rules-implementation-guide">http://www.gs1.org/package-measurement-rules-implementation-guide</a> for more details.	O	Y
inPackageDepth	QuantitativeValue	The depth of the product in its packaging, as measured according to the GS1 Package Measurement Rules. See <a href="http://www.gs1.org/package-measurement-rules-implementation-guide">http://www.gs1.org/package-measurement-rules-implementation-guide</a> for more details.	O	Y
inPackageHeight	QuantitativeValue	The height of the product in the	O	Y

	eValue	package, as measured according to the GS1 Package Measurement Rules. See <a href="http://www.gs1.org/package-measurement-rules-implementation-guide">http://www.gs1.org/package-measurement-rules-implementation-guide</a> for more details.		
netWeight	QuantitativeValue	Used to identify the net weight of the product. Net Weight excludes all packaging material, including the packaging material of all lower-level GTINs. Example:11.5 kg	O	Y
grossWeight	QuantitativeValue	Used to identify the gross weight of the product. The gross weight includes all packaging materials of the product. At pallet level the productGrossWeight includes the weight of the pallet itself. For example, 200 GRM, value - total pounds, total grams, etc.	O	Y
countryOfOrigin	Text	Country where the product was manufactured, harvested, mined etc.  Code indicating the country of origin of the product.	O	Y
gpcCategoryCode	Text	Product category code  8-digit code (GPC "Brick Value") specifying a product category according to the GS1 Global Product Classification (GPC) standard. For more information see <a href="http://www.gs1.org/gpc">http://www.gs1.org/gpc</a>	O	Y
image	List of URLs	List of URLs of images of the product.  Each URL links to a file containing a visual representation of the product either as catalogue images or as actual images of the specific product.	O	Y
growerURL	URL	URL of a grower of a product (particularly agricultural)	O	Y
manufacturer	Organization	Name of the product manufacturer  The organization that produces the item.	O	Y

### 2.3.21.1 Product JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/0817901a9f8ae3440ab751513acdf88e>

```
{
  "id": "6223903a-d8c5-4e7e-af24-cc90967feb61",
  "type": "Product",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "productType": {
    "type": "Reference",
    "value": "27242396-032d-11e7-83f3-83fdf070a882"
  },
  "supplierName": {
    "type": "Text",
    "value": "Acme Products, Inc."
  },
  "category": {
    "value": [
      "Vegetables"
    ],
    "type": "List"
  },
  "gtin": {
    "type": "Text",
    "value": "01234567890"
  },
  "productName": {
    "type": "Text",
    "value": "Paprika, dried, powdered"
  },
  "description": {
    "type": "Text",
    "value": "Natural paprika grown in Suffolk"
  },
}
```

```
"manufacturerName": {
  "type": "Text",
  "value": "Paprika Company"
},
"brand": {
  "type": "Text",
  "value": "All natural Suffolk spice"
},
"inPackageWidth": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "inch",
    "unitCode": "INH",
    "value": 25
  }
},
"inPackageDepth": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "inch",
    "unitCode": "INH",
    "value": 5
  }
},
"inPackageHeight": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "inch",
    "unitCode": "INH",
    "value": 15
  }
},
"netWeight": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "grammes",
    "unitCode": "GRM",
    "value": 2500
  }
},
"grossWeight": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "grammes",
    "unitCode": "GRM",
    "value": 3000
  }
},
"countryOfOrigin": {
  "type": "Text",
  "value": "GB"
},
"gpcCategoryCode": {
```

```

        "type": "Text",
        "value": "00786613"
    },
    "Image": {
        "type": "URL",
        "value": [
            "http://example.com/productImg1.jpg",
            "http://example.com/productImg2.jpg"
        ]
    },
    "growerURL": {
        "type": "URL",
        "value": "http://www.example.com"
    },
    "manufactuer": {
        "type": "Organization",
        "value": {
            "name": "Paprika Company"
        }
    }
}
    
```

### 2.3.22 ProductRecord

This entity contains a harmonised description of the conditions recorded as a product (generally a physical instance of a product) moves through the supply chain. This entity is primarily associated with the retail supply vertical and related IoT applications.

<ProductRecord><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "ProductRecord".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g.	R	Y

		<a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"		
--	--	--	--	--

<ProductRecord><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refProduct	Reference	Unique id of the Product to which this record relates.	M	N
location	geo:json	The geo:json encoded current location.	M	N
temperature	ExtQuantitativeValue	The observed local air temperature in degrees centigrade encoded as an ExtQuantitativeValue.	O	Y
relativeHumidity	ExtQuantitativeValue	Relative Humidity a number between 0 and 1 representing the range 0% to 100 (%)  $0 \leq \text{relativeHumidity} \leq 1$ encoded as a ExtQuantitativeValue.	O	Y
atmosphericPressure	ExtQuantitativeValue	Atmospheric Pressure in units of hecto Pascals encoded as a ExtQuantitativeValue.	O	Y
description	Text	Description of this ProductRecord.	R	Y
weight	ExtQuantitativeValue	Current (i.e. measured) weight of the product including packaging. This may differ from the original weight due to additional packaging or losses during shipment e.g. evaporation	O	Y
netWeight	QuantitativeValue	Weight of the Agri-Product itself in a package with GS1 code  Used to identify the net weight of the product. Net Weight excludes all packaging material, including the packaging material of all lower-level GTINs. Example:11.5 kg	O	Y

volume	QuantitativeValue	The current volume of the product including packaging.	O	Y
dateObserved	DateTime	The timestamp at which this ProductRecord was generated.	R	Y
O2	QuantitativeValue	The level of gaseous Oxygen (O2) present in the atmosphere as measured around the product. (M1)	O	Y

### 2.3.22.1 ProductRecord JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/4c2fc701cf2bf121b360613cf27ba8d4>

```
{
  "id": "85d05a21-6907-44b3-83d8-85d8a713d003",
  "type": "ProductRecord",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refProduct": {
    "type": "Reference",
    "value": "6223903a-d8c5-4e7e-af24-cc90967feb61"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    },
    "type": "geo:json"
  },
}
```

```
"temperature": {
  "type": "ExtQuantitativeValue",
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "unitCode": "CEL",
    "value": 3.823
  }
},
"relativeHumidity": {
  "type": "ExtQuantitativeValue",
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "unitCode": "C62",
    "value": 0.70
  }
},
"atmosphericPressure": {
  "type": "ExtQuantitativeValue",
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "unitCode": "A97",
    "value": 1006.19
  }
},
"description": {
  "type": "Text",
  "value": "Palm oil consignment arrived at port for shipment"
},
"weight": {
  "type": "ExtQuantitativeValue",
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "unitText": "grammes",
    "unitCode": "GRM",
    "value": 2550
  }
},
"netWeight": {
  "type": "QuantitativeValue",
  "value": {
    "unitText": "grammes",
    "unitCode": "GRM",
    "value": 2500
  }
},
"volume": {
  "type": "QuantitativeValue",
  "value": {
    "unitCode": "MTQ",
    "value": 1.7
  }
},
"dateObserved": {
```

## Official Document CLP.26 - IoT Big Data Harmonised Data Model

```
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "O2": {
    "type": "ExtQuantitativeValue",
    "value": {
      "value": 300,
      "unitCode": "GQ"
    }
  }
}
```

### 2.3.23 ProductType

This entity contains a harmonised description of a generic product type. This entity is primarily associated with the product supply chain verticals and related IoT applications. The ProductType includes a hierarchical structure that allows product types to be grouped in a flexible way.

#### <ProductType><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>ProductType</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <ProductType><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
name	Text	The name of this ProductType.	M	N
description	Text	A description of this ProductType.	M	N

root	Boolean	A logical indicator that this product is the root of a ProductType hierarchy. Logical TRUE indicates it is a root.	M	N
refParentType	List of Reference	A JSON encoded sequence of characters referencing the unique ids of the ProductType groupings this ProductType is a member of.	O	Y

### 2.3.23.1 ProductType JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/1cc0398be95ed4287dec068f8bc6da50>

```
{
  "id": "8bd39518-041d-4a9a-8c0c-0bf15d5f07f1",
  "type": "ProductType",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "name": {
    "type": "Text",
    "value": "Refined Palm Oil"
  },
  "description": {
    "type": "Text",
    "value": "Bulk refined palm oil"
  },
  "root": {
    "type": "Boolean",
    "value": true
  },
  "refParentType": {
    "type": "List",
    "value": [
```

```
        "66edbb59-90ea-4757-aa06-5a5b95675092"  
    ]  
}  
}
```

### 2.3.24 Road

This entity contains a harmonised geographic and contextual description of a Road. Roads are made up of one or more RoadSegment entities. This entity is primarily associated with the Automotive and Smart City vertical segments and related IoT applications.

#### <Road><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "Road".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <Road><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
country	Text	The country in which this road is in	M	N
refRoadSegment	List of Reference	A JSON encode sequence of characters referencing the unique ids of the group of roadSegments that	R	Y

		define this road.		
roadClass	Text	The official classification of this road (relevant to the local country).	R	Y
name	Text	The official designation of this road.	R	Y
alternateName	Text	An alternative name for this road.	O	Y

### 2.3.24.1 Road JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/aa8dc76b8702be6e0f9509563c308861>

```
{
  "id": "19b6f4b7-a9b4-4114-8391-3133bf96aedc",
  "type": "Road",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "country": {
    "value": "United Kingdom",
    "type": "Text"
  },
  "refRoadSegment": {
    "value": [
      "2a982120-4d98-425b-a8db-1de5563db6a8",
      "43e255c7-262e-4d6d-95a1-69a53e37dcc0"
    ],
    "type": "List"
  },
  "roadClass": {
    "value": "Dual Carriageway",
    "type": "Text"
  }
}
```

```
  },  
  "name": {  
    "value": "M1",  
    "type": "Text"  
  },  
  "alternateName": {  
    "value": "M1 Motorway",  
    "type": "Text"  
  }  
}
```

### 2.3.25 RoadSegment

This entity contains a harmonised geographic and contextual description of a RoadSegment. A collection of RoadSegments are used to describe a Road. This entity is primarily associated with the Automotive and Smart City vertical segments and related IoT applications.

#### <RoadSegment><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>RoadSegment</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <RoadSegment><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
startPoint	geo:json	The start point of this RoadSegment.	M	N
endPoint	geo:json	The end point of this RoadSegment.	M	N

roadClass	Text	The official classification of the road that this roadSegment is a part of.	R	Y
name	Text	The official designation of the road that this roadSegment is a part of.	R	Y
location	geo:json	A geo:json line sequence (LineString) containing all the points that make up this RoadSegment.	R	Y
refPointOfInterest	List of Reference	A List containing a JSON encoded sequence of characters referencing the Ids of the points of interest along this road segment.	O	Y

### 2.3.25.1 RoadSegment JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/127ce8f2f2b56e50d9326523fc1a221f>

```
{
  "id": "27109fe0-0c60-4302-a9eb-e7065eca876e",
  "type": "RoadSegment",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "startPoint": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404, 39.75621
      ]
    },
    "type": "geo:json"
  },
}
```

```

"endPoint": {
  "value": {
    "type": "Point",
    "coordinates": [
      -109.99404,
      32.75621
    ]
  },
  "type": "geo:json"
},
"roadClass": {
  "value": "Single Carriageway",
  "type": "Text"
},
"name": {
  "value": "A123",
  "type": "Text"
},
"location": {
  "value": {
    "type": "LineString",
    "coordinates": [
      [-104.99404, 39.75621],
      [-102.98, 32.75],
      [-103.99, 30.75],
      [-103.99, 31.75],
      [-109.99404, 32.75621]
    ]
  },
  "type": "geo:json"
},
"refPointOfInterest": {
  "value": [
    "4d798319-22b1-4714-b847-b81dbba3357b",
    "1909a43d-e5a1-46cb-bbd0-7cc16bc4fa33"
  ],
  "type": "List"
}
}
    
```

### 2.3.26 Subscriber

This entity contains a harmonised description of a subscriber to a service. This entity is primarily associated with the Smart Home vertical segment and related IoT applications.

<Subscriber><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this	M	N

		entity.		
type	Text	Must be equal to " <b>Subscriber</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Subscriber><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
subscriptionId	Reference	A reference to the unique id of the subscription service.	M	N
startDate	DateTime	The start timestamp for this subscription as an ISO8601 sequence of characters in UTC.	R	Y
endDate	DateTime	The end timestamp for this subscription as an ISO8601 sequence of characters in UTC.	R	Y
duration	Number	The duration of the subscription in calendar months.	O	Y
category	List	The category of subscription. A selection from an enumerated list including:  <b>prepay, postpay, utility,</b>	O	Y

		<b>broadband, electric, gas, heat, water, landline, mobile, tv, security, financial, energy management, other.</b>		
averageMonthly Usage	Number or Quantitative Value	Average monthly usage of the subscription service.	O	Y
subscribed	List of Reference	A List containing a JSON encoded sequence of characters referencing the unique ids of those persons or organisations that have subscribed to this service.  Related to a Schema.org person or organization.  <a href="https://schema.org/Person">https://schema.org/Person</a>  <a href="https://schema.org/Organization">https://schema.org/Organization</a>	O	Y

### 2.3.26.1 Subscriber JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/4bdc07091dd7fd8af7abcb58103ba513>

```
{
  "id": "c1716dea-6a4d-4171-a733-916123942f09",
  "type": "Subscriber",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "subscriptionId": {
```

## Official Document CLP.26 - IoT Big Data Harmonised Data Model

```
    "value": "65b1ccb0-ee32-41c1-9746-7ba83fb0f0f1",
    "type": "Reference"
  },
  "startDate": {
    "value": "2016-08-22T10:18:16Z",
    "type": "DateTime"
  },
  "endDate": {
    "value": "2017-08-22T23:59:59Z",
    "type": "DateTime"
  },
  "duration": {
    "value": 12,
    "type": "Number"
  },
  "category": {
    "value": [
      "utility"
    ],
    "type": "List"
  },
  "averageMonthlyUsage": {
    "value": 28,
    "type": "Number"
  },
  "subscribed": {
    "value": [
      "31dd0e29-45b6-476f-9756-a70f8141dcf3"
    ],
    "type": "List"
  }
}
```

### 2.3.27 SubscriptionService

This entity contains a harmonised description of a subscription service. This entity is primarily associated with the Smart Home vertical segment and related IoT applications.

<SubscriptionService><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to "SubscriptionService".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<SubscriptionService><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
description	Text	The description of this service.	M	N
offer	Offer	Encoded as Schema.org offer.  <a href="https://schema.org/Offer">https://schema.org/Offer</a>	R	Y

### 2.3.27.1 SubscriptionService JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/08c9d422617b832bc1c04d164973c172>

```
{
  "id": "a1e76f95-c627-4ec4-86dc-483431d25352",
  "type": "SubscriptionService",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "description": {
    "value": "Broadband supply service",
    "type": "Text"
  },
  "offer": {
    "type": "Offer",
    "value": {
      "priceCurrency": "USD",
      "price": 50,
      "description": "100 mbps fibre broadband service"
    }
  }
}
```

### 2.3.28 Vehicle

This entity contains a harmonised description of a Vehicle. This entity is primarily associated with the Automotive vertical segment but might also be relevant to Industry, Smart City and Agriculture related IoT applications. Where practicable <https://schema.org/Vehicle> naming conventions have been adopted.

<Vehicle><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>Vehicle</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Vehicle><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refVehicleType	Reference	A JSON encoded sequence of characters referencing the Id of the vehicleType entity which describes this vehicle in more detail.	M	N
fuelType	Text	A choice from an enumerated list describing the power source. One of: <b>gasoline, petrol (unleaded), petrol (leaded), petrol, diesel, electric, hydrogen, lpg autogas, cng, biodiesel, ethanol, hybrid electric/petrol, hybrid electric/diesel, other</b>	O	Y

displacement	Number	A number indicating the cylinder capacity of the engine in litres	O	Y
fuelEfficiency	QuantitativeValue	The efficiency of the vehicle expressed as kilometres per litre or miles per gallon following the Schema.org definition at <a href="http://schema.org/fuelEfficiency">http://schema.org/fuelEfficiency</a>	O	Y
vehicleModelDate	DateTime	The ISO8601 sequence of characters indicating the year of release.	O	Y
dateDiscontinued	DateTime	The ISO8601 sequence of characters indicating the year which the vehicle was discontinued.	O	Y
vehicleIdentificationNumber	Text	The VIN (vehicle identification number) of the vehicle.	O	Y
mileageFromOdometer	Number or ExtQuantitativeValue	The total distance the car has travelled according to the on-board odometer in kilometres (unitCode KMT) or miles (unitCode SMI). If Number is used the units are assumed to be kilometres.  references Schema.org Vehicle/mileageFromOdometer.	O	Y

### 2.3.28.1 Vehicle JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/0e22f3200c12c9e725148eafca6b225c>

```
{
  "id": "1fa179a6-b507-4857-ad72-eb5513ef05c6",
  "type": "Vehicle",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  }
}
```

```
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "refVehicleType": {
    "value": "23821045-33d4-46ec-b777-98f461bf4856",
    "type": "Reference"
  },
  "fuelType": {
    "value": "diesel",
    "type": "Text"
  },
  "displacement": {
    "value": 3,
    "type": "Number"
  },
  "fuelEfficiency": {
    "value": {
      "value": 22,
      "unitText": "mpg"
    },
    "type": "QuantitativeValue"
  },
  "vehicleModelDate": {
    "value": "2013-01-01T00:00:00Z",
    "type": "DateTime"
  },
  "dateDiscontinued": {
    "value": "2016-08-23T10:18:16Z",
    "type": "DateTime"
  },
  "vehicleIdentificationNumber": {
    "value": "2T2GK31U08C041124",
    "type": "Text"
  },
  "mileageFromOdometer": {
    "value": {
      "value": 33015,
      "unitCode": "SMI",
      "timestamp": "2016-08-08T10:18:16Z"
    },
    "type": "ExtQuantitativeValue"
  }
}
```

### 2.3.29 VehicleFault

This entity contains a harmonised description of a Vehicle Fault. This entity is primarily associated with the Automotive vertical segment but might also be relevant to Industry, Smart City and Agriculture related IoT applications.

#### <VehicleFault><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>VehicleFault</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <VehicleFault><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refVehicle	List of Reference	A JSON encoded sequence of characters referencing the id of the vehicle in which this fault occurred or multiple ids in the case a common fault can be identified against	M	N

		multiple vehicles.		
dateIdentified	DateTime	An ISO8601 sequence of characters indicating the date and time the fault was detected or identified.	M	N
eventType	Text	The event type descriptor, a choice from an enumerated list including:  <b>collision, emergency, harshAccel, harshDecel, auxBatteryWarn, milWarn.</b>	M	N
location	geo:json	The geo location where the fault was detected.	R	Y
processingType	Text	Indicates how the fault was dealt with, e.g. <i>systemHandled</i> , or not present if the issue has not been resolved.	O	Y
dateProcessed	DateTime	The ISO8601 sequence of characters indicating the data and time at which the issue was solved, or not present if the issue has not been resolved.	O	Y
dtCode	Text	DTC or Diagnostic Trouble Codes are codes generated by the vehicle's computer diagnostic system. These may be manufacturer, equipment or vehicle specific.	R	Y
faultLog	Text	Free text that records information about the initial fault incident, ongoing updates and fault resolution.	O	Y

### 2.3.29.1 VehicleFault JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/9a70cc18bd403c7115d0ffec8ecc2ecf>

```
{
  "id": "4939200a-5ef5-4266-8c91-1f82ad3b543b",
  "type": "VehicleFault",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
}
```

```
"source": {
  "value": "http://www.example.com",
  "type": "URL"
},
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"refVehicle": {
  "value": [
    "e64a2ecb-a8ae-4f51-ab66-2e9729c02d22"
  ],
  "type": "List"
},
"dateIdentified": {
  "value": "2016-08-20T10:18:16Z",
  "type": "DateTime"
},
"eventType": {
  "value": "emergency",
  "type": "Text"
},
"location": {
  "value": {
    "type": "Point",
    "coordinates": [
      -104.99404,
      39.75621
    ]
  },
  "type": "geo:json"
},
"processingType": {
  "value": "systemHandled",
  "type": "Text"
},
"dateProcessed": {
  "value": "2016-08-21T10:18:16Z",
  "type": "DateTime"
},
"dtCode": {
  "value": "EMERG-1234-a",
  "type": "Text"
},
"faultLog": {
  "value": "Emergency stop. Fault with engine",
  "type": "Text"
}
}
```

### 2.3.30 VehicleType

This entity contains a harmonised description of a vehicleType it forms part of the description of a Vehicle. This entity is primarily associated with the Automotive vertical segment but might also be relevant to Industry, Smart City and Agriculture related IoT applications. Where practicable <https://schema.org/Vehicle> naming conventions have been adopted.

#### <VehicleType><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>vehicleType</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

#### <VehicleType><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
model	Text	The vehicle model identifier.	M	N

category	Text	The vehicle category identifier.	M	N
manufacturer	Text	The manufacturer's identifier.	M	N

### 2.3.30.1 VehicleType JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/50133c6710743c065dc5f2f982b698fd>

```
{
  "id": "33253089-9cea-4227-889e-61950965f6f9",
  "type": "VehicleType",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "model": {
    "value": "M Class",
    "type": "Text"
  },
  "category": {
    "value": "SUV",
    "type": "Text"
  },
  "manufacturer": {
    "value": "Mercedes Benz",
    "type": "Text"
  }
}
```

### 2.3.31 WaterQualityObserved

This entity contains a harmonised description of the water quality at a particular location and time. This entity is primarily associated with the vertical segments of agricultural and environment and related IoT applications.

<WaterQualityObserved><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>WaterQualityObserved</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<WaterQualityObserved><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
refDevice	List of Reference	A reference to the unique entity Ids of the devices that originated this observation data.	M	N
location	geo:json	The geo:json encoded map location, that is related to this observation.	M	N
dateObserved	DateTime	The date and time of this observation in ISO8601 UTCformat.	M	N

depth	ExtQuantitativeValue (Number)	Depth where the observation was taken. ( <i>m</i> ) encoded as a ExtQuantitativeValue.	O	Y
pressure	ExtQuantitativeValue (Number)	Hydrostatic pressure where the observation was taken. (115 Hecto Pascals) encoded as a ExtQuantitativeValue.	O	Y
conductivity	ExtQuantitativeValue (Number)	Electrical conductivity. ( <i>S/m</i> ) encoded as a ExtQuantitativeValue.	O	Y
conductance	ExtQuantitativeValue (Number)	Specific conductivity / 25 °C /. ( <i>S/m</i> ) encoded as a ExtQuantitativeValue.	O	Y
temperature	ExtQuantitativeValue (Number)	The temperature expressed in degrees Celsius encoded as a ExtQuantitativeValue.	O	Y
tss	ExtQuantitativeValue (Number)r	Total suspended solids. ( <i>M1</i> ) encoded as a ExtQuantitativeValue	O	Y
tds	ExtQuantitativeValue (Number)	Total dissolved solids. ( <i>M1</i> ) encoded as a ExtQuantitativeValue.	O	Y
turbidity	ExtQuantitativeValue (Number)	Amount of light scattered by particles in the water column. ( <i>FTU</i> ). encoded as a ExtQuantitativeValue.	O	Y
salinity	ExtQuantitativeValue (Number)	Derived from the conductivity measurement. ( <i>parts per thousand, ppt</i> ) encoded as a ExtQuantitativeValue.	O	Y
pH	ExtQuantitativeValue (Number)	pH measurement (typically a number between <i>0 and 14</i> ) encoded as a ExtQuantitativeValue.	O	Y
orp	ExtQuantitativeValue (Number)	Oxidation-Reduction potential ( <i>mV</i> ) encoded as a ExtQuantitativeValue.	O	Y
cdom	ExtQuantitativeValue (Number)	Color dissolved organic matter ( <i>RFU</i> ) encoded as a ExtQuantitativeValue.	O	Y
Chla	ExtQuantitativeValue (Number)	Concentration of chlorophyll A. ( <i>H29</i> )	O	Y

Cl	ExtQuantitativeValue (Number)	Concentration of chlorides. (M1)	O	Y
CO	ExtQuantitativeValue (Number)	The level of free non-compound carbon monoxide present. (M1)	O	Y
CO2	ExtQuantitativeValue (Number)	The level of free non-compound carbon dioxide present. (M1)	O	Y
Hg	ExtQuantitativeValue (Number)	The level of compound mercury present. (M1)	O	Y
NH3	ExtQuantitativeValue (Number)	Concentration -n of ammonia. (M1)	O	Y
NH4	ExtQuantitativeValue (Number)	Concentration of ammonium. (M1)	O	Y
NO3	ExtQuantitativeValue (Number)	Concentration of nitrates. (M1)	O	Y
O2	ExtQuantitativeValue (Number)	The level of free non-compound oxygen present. (M1)	O	Y
PC	ExtQuantitativeValue (Number)	Concentration of pigment phycocyanin which can be measured to estimate cyanobacteria concentrations specifically. (H29)	O	Y
PE	ExtQuantitativeValue (Number)	Concentration of pigment phycoerythrin which can be measured to estimate cyanobacteria concentrations specifically.(H29)	O	Y

### 2.3.31.1 WaterQualityObserved JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/e23befb590592ddefa6fd817d38919f0>

```
{
  "id": "72a30ca8-888e-49a2-8d8d-a5bebc19e98b",
  "type": "WaterQualityObserved",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  }
}
```

```
},
"dateModified": {
  "value": "2016-08-08T10:18:16Z",
  "type": "DateTime"
},
"source": {
  "value": "http://www.example.com",
  "type": "URL"
},
"dataProvider": {
  "value": "OperatorA",
  "type": "Text"
},
"schemaVersion": {
  "value": "1.0",
  "type": "Text"
},
"refDevice": {
  "value": [
    "2033a7c7-d31b-48e7-91c2-014dc426c29e"
  ],
  "type": "List"
},
"location": {
  "value": {
    "type": "Point",
    "coordinates": [
      -104.99404,
      39.75621
    ]
  },
  "type": "geo:json"
},
"dateObserved": {
  "value": "2016-08-16T10:18:16Z",
  "type": "DateTime"
},
"depth": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 4,
    "unitCode": "MTR"
  },
  "type": "ExtQuantitativeValue"
},
"pressure": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 1020.2,
    "unitCode": "A97"
  },
  "type": "ExtQuantitativeValue"
},
},
```

```
"conductivity": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 10,
    "unitCode": "D10"
  },
  "type": "ExtQuantitativeValue"
},
"conductance": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 25,
    "unitCode": "SIE"
  },
  "type": "ExtQuantitativeValue"
},
"temperature": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 15,
    "unitCode": "CEL"
  },
  "type": "ExtQuantitativeValue"
},
"tss": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 200,
    "unitCode": "M1"
  },
  "type": "ExtQuantitativeValue"
},
"tds": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 150,
    "unitCode": "M1"
  },
  "type": "ExtQuantitativeValue"
},
"turbidity": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 343,
    "unitCode": "FTU"
  },
  "type": "ExtQuantitativeValue"
},
"salinity": {
  "value": {
    "timestamp": "2016-08-08T10:18:16Z",
    "value": 220,
    "unitCode": "NX"
  }
}
```

```
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "pH": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 5  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "orp": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 225,  
      "unitCode": "2Z"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "cdom": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 22,  
      "unitCode": "RFU"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "Chla": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 11,  
      "unitCode": "H29"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "CI": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 1000,  
      "unitCode": "M1"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "CO": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",  
      "value": 40,  
      "unitCode": "M1"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "CO2": {  
    "value": {  
      "timestamp": "2016-08-08T10:18:16Z",
```

```
    "value": 1,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"Hg": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 0.2,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"NH3": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 0.03,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"NH4": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 0.02,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"N03": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 1,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"O2": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 50,  
    "unitCode": "M1"  
  },  
  "type": "ExtQuantitativeValue"  
},  
"PC": {  
  "value": {  
    "timestamp": "2016-08-08T10:18:16Z",  
    "value": 52,  
    "unitCode": "H29"  
  },  
  "type": "ExtQuantitativeValue"  
},  
},
```

```

    "PE": {
      "value": {
        "timestamp": "2016-08-08T10:18:16Z",
        "value": 66,
        "unitCode": "H29"
      },
      "type": "ExtQuantitativeValue"
    }
  }
}

```

### 2.3.32 WeatherForecast

This entity contains a harmonised description of a Weather Forecast. This entity is primarily associated with the vertical segments of the environment and agriculture but is applicable to many different applications.

<WeatherForecast><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>WeatherForecast</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<WeatherForecast><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
location	geo:json	The geo:json encoded map location (point or polygon), of this weather forecast.	M	N
dateRetrieved	DateTime	The date and time the forecast was retrieved in ISO8601 UTC format.	M	N
dateIssued	DateTime	The date and time the forecast was issued by the meteorological bureau in ISO8601 UTC format.		
weatherType	Text	The weather type. A choice from an enumerated list. One of:  <code>notAvailable, clearNight, sunnyDay, partlyCloudy, mist, fog, cloudy, overcast, lightRainShower, drizzle, lightRain, heavyRainShower, heavyRain, sleetShower, sleet, hailShower, hail, lightSnowShower, lightSnow, heavySnowShower, heavySnow, thunderShower, thunder.</code>	R	Y
visibility	Number or QuantitativeValue	Defines the forecast visibility nominally in metres or in an alternative measurement according to specified unitCode if QuantitativeValue is used	R	Y
name	Text	The name of the weather forecast location.	M	Y
validFrom	DateTime	The date and time the forecast is valid from expressed as an ISO8601 UTC format sequence of characters.	R	Y
validThrough	DateTime	The date and time the forecast is valid to expressed as an ISO8601 UTC format sequence of characters.	R	Y
dayMinimum	StructuredValue	Defines the minimum forecast values for defined attributes.  Supports the inclusion of the nested attribute values, each of which will be a number. The units of the respective values will match the respective main attributes for temperature/ relative	O	Y

		<p>humidity.</p> <p><b>temperature</b>,  <b>feelsLikeTemperature</b>,  <b>relativeHumidity</b></p> <p><b>temperature</b> -- The forecasted minimum temperature for the period in degrees Celsius.</p> <p><b>feelsLikeTemperature</b> – The forecasted feels like temperature for the period in degrees Celsius.</p> <p><b>relativeHumidity</b> -- The relative humidity expressed a number between <math>0 \leq \text{RelativeHumidity} \leq 1</math> representing the range 0% to 100%</p>		
dayMaximum	StructuredValue	<p>Defines the maximum forecast values for defined attributes.</p> <p>Supports the inclusion of the nested attribute values, each of which will be a number. The units of the respective values will match the respective main attributes for temperature/ relative humidity.</p> <p><b>temperature</b>,  <b>feelsLikeTemperature</b>,  <b>relativeHumidity</b></p> <p><b>temperature</b> -- The forecasted maximum temperature for the period in degrees Celsius.</p> <p><b>feelsLikeTemperature</b> – The forecasted feels like temperature for the period in degrees Celsius.</p> <p><b>relativeHumidity</b> -- The relative humidity expressed a number between <math>0 \leq \text{RelativeHumidity} \leq 1</math> representing the range 0% to 100%</p>	O	Y
address	PostalAddress	<p>The weather forecast location encoded as a Schema.org PostalAddress.</p> <p><a href="https://schema.org/PostalAddress">https://schema.org/PostalAddress</a></p>	R	Y
temperature	Number or ExtQuantita	<p>The temperature expressed in degrees Celsius.</p>	R	Y

	tiveValue			
windDirection	Number or ExtQuantitativeValue	The wind direction expressed in degrees compared to geographic North (measured clockwise).	O	Y
windSpeed	Number or ExtQuantitativeValue	The forecasted wind speed in meters per second.	O	Y
uvIndexMax	Number	The maximum UV index for the period, based on the World Health Organization's UV Index measure.	O	Y
relativeHumidity	Number or ExtQuantitativeValue	The relative humidity expressed a number between  $0 \leq \text{RelativeHumidity} \leq 1$ representing the range 0% to 100%	O	Y
precipitationProbability	Number or ExtQuantitativeValue	The probability of precipitation, expressed as a number between  $0 \leq \text{precipitationProbability} \leq 1$ representing the range 0% to 100%	O	Y
refPointOfInterest	List of Reference	A JSON encode sequence of characters referencing the unique ids of the associated group of pointOfInterests.	O	Y

### 2.3.32.1 WeatherForecast JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/fe74d7f9573c53bc46b5199d2ab9c847>

```
{
  "id": "7453c443-290d-44ef-a60f-d4c087010c88",
  "type": "WeatherForecast",
  "dateCreated": {
    "value": "2016-08-08 T10:18:16Z ",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
```

```
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    },
    "type": "geo:json"
  },
  "dateRetrieved": {
    "value": "2016-08-16T10:18:16Z",
    "type": "DateTime"
  },
  "dateIssued": {
    "value": "2016-08-10T10:18:16Z",
    "type": "DateTime"
  },
  "weatherType": {
    "value": "sunnyDay",
    "type": "Text"
  },
  "visibility": {
    "value": 1500,
    "type": "Number"
  },
  "name": {
    "value": "London City",
    "type": "Text"
  },
  "validFrom": {
    "value": "2016-08-10T10:18:16Z",
    "type": "DateTime"
  },
  "validThrough": {
    "value": "2016-08-29T10:18:16Z",
    "type": "Text"
  },
  "dayMinimum": {
    "value": {
      "temperature" : 30,
      "feelsLikeTemperature" : 32,
      "relativeHumidity" : 0.22
    },
    "type": "StructuredValue"
  },
}
```

```
"dayMaximum ": {
  "value": {
    "temperature" : 33,
    "feelsLikeTemperature" : 38,
    "relativeHumidity" : 0.52
  },
  "type": "StructuredValue"
},
"address": {
  "type": "PostalAddress",
  "value": {
    "addressLocality": "London",
    "postalCode": "EC4N 8AF",
    "streetAddress": "25 Walbrook"
  }
},
"temperature": {
  "value": 30,
  "type": "Number"
},
"windDirection": {
  "value": 122,
  "type": "Number"
},
"windSpeed": {
  "value": 3,
  "type": "Number"
},
"uVIndexMax": {
  "value": 5,
  "type": "Number"
},
"relativeHumidity": {
  "value": 0.10,
  "type": "Number"
},
"precipitationProbability": {
  "value": 0.05,
  "type": "Number"
},
"refPointOfInterest": {
  "value": [
    "d0d88168-780c-11e6-b934-2b9831af3c6f"
  ],
  "type": "List"
}
}
```

### 2.3.33 WeatherObserved

This entity contains a harmonised description of the weather at a particular location and time. This entity is primarily associated with the vertical segments of the environment and agriculture but is applicable to many different applications.

<WeatherObserved><Generic Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
id	Text	Unique id of this instance of this entity.	M	N
type	Text	Must be equal to " <b>WeatherObserved</b> ".	M	N
dateCreated	DateTime	Entity creation timestamp.	M	N
dateModified	DateTime	Timestamp of the last modification of the entity.	O	Y
source	Text	A sequence of characters giving the source of the entity data as a URL.	R	Y
dataProvider	Text	A sequence of characters identifying the originator of the harmonised entity.	R	Y
schemaVersion	Text or URL	Indicates the version number of the data entity via either a URL referring to an external entity version (e.g. <a href="http://schema.org/version/2.0/">http://schema.org/version/2.0/</a> ) or a sequence of text characters of the form "M.N" where M is a sequence of digits representing the major version number and N is a sequence of digits representing a minor version number. If omitted implies a schema version of "1.0"	R	Y

<Weather Observed><Entity Specific Attributes>

Attribute Name	Attribute Type	Description	Mandatory/ Optional/ Recommended	May be Null
location	geo:json	The geo:json encoded map location (point or polygon), of this weather observation.	M	N
refDevice	List of Reference	Reference to the unique ids of the device(s) which captured this weather observation.	O	Y
dateObserved	DateTime	The date and time of this weather observation in ISO8601 UTCformat.	M	N

weatherType	Text	The weather type. A choice from an enumerated list. One of:  <code>notAvailable, clearNight, sunnyDay, partlyCloudy, mist, fog, cloudy, overcast, lightRainShower, drizzle, lightRain, heavyRainShower, heavyRain, sleetShower, sleet, hailShower, hail, lightSnow Shower, lightSnow, heavySnowShower, heavySnow, thunderShower, thunder</code>	R	Y
visibility	Number or QuantitativeValue	Defines the observed visibility nominally in metres or in an alternative measurement according to specified unitCode if QuantitativeValue is used	R	Y
name	Text	The name of the weather observation location.	R	Y
address	PostalAddress	The weather observed location encoded as a Schema.org Postal Address.  <a href="https://schema.org/PostalAddress">https://schema.org/PostalAddress</a>	R	Y
temperature	Number or ExtQuantitativeValue	The recorded temperature expressed in degrees Celsius, encoded as a Number OR a ExtQuantitativeValue.	R	Y
refPointOfInterest	List of Reference	A JSON encode sequence of characters referencing the unique ids of the associated group of pointOfInterests.	O	Y
windDirection	Number or ExtQuantitativeValue	The wind direction expressed in degrees compared to geographic North (measured clockwise), encoded as a Number OR a ExtQuantitativeValue.	R	Y
windSpeed	Number or ExtQuantitativeValue	The observed wind speed in meters per second, encoded as a Number OR a ExtQuantitativeValue.	R	Y
relativeHumidity	Number or ExtQuantitativeValue	The relative humidity expressed a number between  $0 \leq \text{RelativeHumidity} \leq 1$ representing the range 0% to 100%, encoded as a Number OR a ExtQuantitativeValue.	R	Y

dewPoint	Number Or ExtQuantitativeValue	The dew point in degrees Celsius, encoded as a Number OR a ExtQuantitativeValue.	O	Y
atmosphericPressure	Number Or ExtQuantitativeValue	The measured barometric or atmospheric pressure in units of hecto Pascals, encoded as a Number OR a ExtQuantitativeValue.	R	Y
pressureTendency	Text Or ExtQuantitativeValue	Is the pressure is rising or falling? Encoded as Text OR a ExtQuantitativeValue.  A choice from an enumerated list.  One of:  <b>rising, falling, steady.</b>	R	Y

### 2.3.33.1 WeatherObserved JSON

The JSON code can be downloaded from:

<https://gist.github.com/GSMADeveloper/f592f7923c97cd5c6d18bc44a42b7050>

```
{
  "id": "adb144fb-e732-4944-a192-8690bd17de8c",
  "type": "WeatherObserved",
  "dateCreated": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "dateModified": {
    "value": "2016-08-08T10:18:16Z",
    "type": "DateTime"
  },
  "source": {
    "value": "http://www.example.com",
    "type": "URL"
  },
  "dataProvider": {
    "value": "OperatorA",
    "type": "Text"
  },
  "schemaVersion": {
    "value": "1.0",
    "type": "Text"
  },
  "location": {
    "value": {
      "type": "Point",
      "coordinates": [
        -104.99404,
        39.75621
      ]
    }
  }
}
```

```
    ],
  },
  "type": "geo:json"
},
"refDevice": {
  "value": [
    "c3e30a5a-2697-407d-908d-02a627d32730",
    "08d22ce9-ce65-46a6-8e3c-12aa3a5389de"
  ],
  "type": "List"
},
"dateObserved": {
  "value": "2016-08-16T10:18:16Z",
  "type": "DateTime"
},
"weatherType": {
  "value": "sunnyDay",
  "type": "Text"
},
"visibility": {
  "value": 500,
  "type": "Number"
},
"name": {
  "value": "London City",
  "type": "Text"
},
"address": {
  "type": "PostalAddress",
  "value": {
    "addressLocality": "London",
    "postalCode": "EC4N 8AF",
    "streetAddress": "25 Walbrook"
  }
},
"temperature": {
  "value": {
    "value": 15,
    "unitCode": "CEL"
  },
  "type": "ExtQuantitativeValue"
},
"refPointofInterest": {
  "value": [
    "b397c472-1ca8-4605-8d35-2fb27e85c0e8",
    "e7c4d076-7eec-45b2-8982-9cd4c331e491"
  ],
  "type": "List"
},
"windDirection": {
  "value": {
    "value": 122,
    "unitCode": "DD"
  }
}
```

```
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "windSpeed": {  
    "value": {  
      "value": 3,  
      "unitCode": "MTS"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "relativeHumidity": {  
    "value": {  
      "value": 0.20,  
      "unitCode": "C62"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "dewPoint": {  
    "value": {  
      "value": 44,  
      "unitCode": "CEL"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "atmosphericPressure": {  
    "value": {  
      "value": 1013.25,  
      "unitCode": "A97"  
    },  
    "type": "ExtQuantitativeValue"  
  },  
  "pressureTendency": {  
    "value": "rising",  
    "type": "Text"  
  }  
}
```

## Annex A ExtQuantitativeValue and NGSiv2 metadata compatibility (Informative)

The harmonized data models defined by this document make extensive use of the ExtQuantitativeValue structure. An example of the JSON formatted syntax for an attribute of type ExtQuantitativeValue is shown below:

```
"soilTemperature" : {  
  "value": {  
    "value": 27,  
    "unitCode": "CEL",  
    "timestamp": "2016-09-07T07:09:54"  
  },  
  "type" : "ExtQuantitativeValue"  
}
```

The identical example in the equivalent NGSiv2 attribute value plus metadata, format is shown below:

```
"soilTemperature": {  
  "value": 27,  
  "metadata": {  
    "timestamp": {  
      "value": "2016-09-07T07:09:54",  
      "type" : "DateTime",  
    }  
    "unitCode": {  
      "value": "CEL",  
      "type": "Text"  
    }  
  },  
  "type": "Number"  
}
```

Both implementation approaches are equivalent and comply with this harmonised data model.

## Annex B Referenced Schema.org entities (Informative)

Some members of the project group have reported difficulties in accessing <https://schema.org/>. To provide additional clarity we provide a snapshot of the <https://schema.org/> entity definitions below. This information is informative only.

### B.1 Schema.org entity descriptions: Offer

Property	Expected Type	Description
<b>Properties from Offer</b>		
<u>acceptedPaymentMethod</u>	<u>LoanOrCredit</u> or <u>PaymentMethod</u>	The payment method(s) accepted by seller for this offer.
<u>addOn</u>	<u>Offer</u>	An additional offer that can only be obtained in combination with the first base offer (e.g. supplements and extensions that are available for a surcharge).
<u>advanceBookingRequirement</u>	<u>QuantitativeValue</u>	The amount of time that is required between accepting the offer and the actual usage of the resource or service.
<u>aggregateRating</u>	<u>AggregateRating</u>	The overall rating, based on a collection of reviews or ratings, of the item.
<u>areaServed</u>	<u>AdministrativeArea</u> or <u>GeoShape</u> or <u>Place</u> or <u>Text</u>	The geographic area where a service or offered item is provided. Supersedes <u>serviceArea</u> .
<u>availability</u>	<u>ItemAvailability</u>	The availability of this item—for example In stock, Out of stock, Pre-order, etc.
<u>availabilityEnds</u>	<u>DateTime</u>	The end of the availability of the product or service included in the offer.
<u>availabilityStarts</u>	<u>DateTime</u>	The beginning of the availability of the product or service included in the offer.
<u>availableAtOrFrom</u>	<u>Place</u>	The place(s) from which the offer can be obtained (e.g. store locations).
<u>availableDeliveryMethod</u>	<u>DeliveryMethod</u>	The delivery method(s) available for this offer.
<u>businessFunction</u>	<u>BusinessFunction</u>	The business function (e.g. sell, lease, repair, dispose) of the offer or component of a bundle (TypeAndQuantityNode). The default is

Property	Expected Type	Description
		<a href="http://purl.org/goodrelations/v1#Sell">http://purl.org/goodrelations/v1#Sell</a> .
<u>category</u>	<u>Text</u> <u>Thing</u>	or A category for the item. Greater signs or slashes can be used to informally indicate a category hierarchy.
<u>deliveryLeadTime</u>	<u>QuantitativeValue</u>	The typical delay between the receipt of the order and the goods either leaving the warehouse or being prepared for pickup, in case the delivery method is on site pickup.
<u>eligibleCustomerType</u>	<u>BusinessEntityType</u>	The type(s) of customers for which the given offer is valid.
<u>eligibleDuration</u>	<u>QuantitativeValue</u>	The duration for which the given offer is valid.
<u>eligibleQuantity</u>	<u>QuantitativeValue</u>	The interval and unit of measurement of ordering quantities for which the offer or price specification is valid. This allows e.g. specifying that a certain freight charge is valid only for a certain quantity.
<u>eligibleRegion</u>	<u>GeoShape</u> <u>Place</u> <u>Text</u>	or The ISO 3166-1 (ISO 3166-1 alpha-2) or ISO 3166-2 code, the place, or the GeoShape for the geo-political region(s) for which the offer or delivery charge specification is valid. See also <u>ineligibleRegion</u> .
<u>eligibleTransactionVolume</u>	<u>PriceSpecification</u>	The transaction volume, in a monetary unit, for which the offer or price specification is valid, e.g. for indicating a minimal purchasing volume, to express free shipping above a certain order volume, or to limit the acceptance of credit cards to purchases to a certain minimal amount.
<u>gtin12</u>	<u>Text</u>	The <u>GTIN-12</u> code of the product, or the product to which the offer refers. The GTIN-12 is the 12-digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items. See <u>GS1 GTIN Summary</u> for more details.

Property	Expected Type	Description
<u>gtin13</u>	<u>Text</u>	The <u>GTIN-13</u> code of the product, or the product to which the offer refers. This is equivalent to 13-digit ISBN codes and EAN UCC-13. Former 12-digit UPC codes can be converted into a GTIN-13 code by simply adding a preceeding zero. See <u>GS1 GTIN Summary</u> for more details.
<u>gtin14</u>	<u>Text</u>	The <u>GTIN-14</u> code of the product, or the product to which the offer refers. See <u>GS1 GTIN Summary</u> for more details.
<u>gtin8</u>	<u>Text</u>	The <u>GTIN-8</u> code of the product, or the product to which the offer refers. This code is also known as EAN/UCC-8 or 8-digit EAN. See <u>GS1 GTIN Summary</u> for more details.
<u>includesObject</u>	<u>TypeAndQuantityNode</u>	This links to a node or nodes indicating the exact quantity of the products included in the offer.
<u>ineligibleRegion</u>	<u>GeoShape</u> <u>Place</u> <u>Text</u>	or or The ISO 3166-1 (ISO 3166-1 alpha-2) or ISO 3166-2 code, the place, or the GeoShape for the geo-political region(s) for which the offer or delivery charge specification is not valid, e.g. a region where the transaction is not allowed. See also <u>eligibleRegion</u> .
<u>inventoryLevel</u>	<u>QuantitativeValue</u>	The current approximate inventory level for the item or items.
<u>itemCondition</u>	<u>OfferItemCondition</u>	A predefined value from OfferItemCondition or a textual description of the condition of the product or service, or the products or services included in the offer.
<u>itemOffered</u>	<u>Product</u> <u>Service</u>	or The item being offered.
<u>mpn</u>	<u>Text</u>	The Manufacturer Part Number (MPN) of the product, or the product to which the offer refers.
<u>offeredBy</u>	<u>Organization</u> <u>Person</u>	or A pointer to the organization or person making the offer.

Property	Expected Type	Description
<u>price</u>	<u>Number</u> <u>Text</u> or	Inverse property: <u>makesOffer</u> . The offer price of a product, or of a price component when attached to <u>PriceSpecification</u> and its subtypes. Usage guidelines: <ul style="list-style-type: none"> <li>• Use the <u>priceCurrency</u> property (with <u>ISO 4217 codes</u> e.g. "USD") instead of including <u>ambiguous symbols</u> such as '\$' in the value.</li> <li>• Use '.' (Unicode 'FULL STOP' (U+002E)) rather than ',' to indicate a decimal point. Avoid using these symbols as a readability separator.</li> <li>• Note that both <u>RDFa</u> and Microdata syntax allow the use of a "content=" attribute for publishing simple machine-readable values alongside more human-friendly formatting.</li> <li>• Use values from 0123456789 (Unicode 'DIGIT ZERO' (U+0030) to 'DIGIT NINE' (U+0039)) rather than superficially similar Unicode symbols.</li> </ul>
<u>priceCurrency</u>	<u>Text</u>	The currency (in 3-letter ISO 4217 format) of the price or a price component, when attached to <u>PriceSpecification</u> and its subtypes.
<u>priceSpecification</u>	<u>PriceSpecification</u>	One or more detailed price specifications, indicating the unit price and delivery or payment charges.
<u>priceValidUntil</u>	<u>Date</u>	The date after which the price is no longer available.
<u>review</u>	<u>Review</u>	A review of the item. Supersedes <u>reviews</u> .
<u>seller</u>	<u>Organization</u> <u>Person</u> or	An entity which offers (sells / leases / lends / loans) the services / goods. A seller may also be a provider. Supersedes <u>merchant</u> , <u>vendor</u> .
<u>serialNumber</u>	<u>Text</u>	The serial number or any alphanumeric identifier of a particular product. When

Property	Expected Type	Description
		attached to an offer, it is a shortcut for the serial number of the product included in the offer.
<u>sku</u>	<u>Text</u>	The Stock Keeping Unit (SKU), i.e. a merchant-specific identifier for a product or service, or the product to which the offer refers.
<u>validFrom</u>	<u>DateTime</u>	The date when the item becomes valid.
<u>validThrough</u>	<u>DateTime</u>	The date after when the item is not valid. For example the end of an offer, salary period, or a period of opening hours.
<u>warranty</u>	<u>WarrantyPromise</u>	The warranty promise(s) included in the offer. Supersedes <u>warrantyPromise</u> .

## B.2 Schema.org entity descriptions: Organisation

Property	Expected Type	Description
<b>Properties from <u>Organization</u></b>		
<u>address</u>	<u>PostalAddress</u> Text or	Physical address of the item.
<u>aggregateRating</u>	<u>AggregateRating</u>	The overall rating, based on a collection of reviews or ratings, of the item.
<u>alumni</u>	<u>Person</u>	Alumni of an organization. Inverse property: <u>alumniOf</u> .
<u>areaServed</u>	<u>AdministrativeArea</u> <u>GeoShape</u> <u>Place</u> Text or	The geographic area where a service or offered item is provided. Supersedes <u>serviceArea</u> .
<u>award</u>	Text	An award won by or for this item. Supersedes <u>awards</u> .
<u>brand</u>	<u>Brand</u> <u>Organization</u> or	The brand(s) associated with a product or service, or the brand(s) maintained by an organization or business person.
<u>contactPoint</u>	<u>ContactPoint</u>	A contact point for a person or organization. Supersedes <u>contactPoints</u> .
<u>department</u>	<u>Organization</u>	A relationship between an organization and a department of that organization, also described as an organization (allowing different urls, logos, opening hours). For example: a store with a pharmacy, or a bakery with a cafe.
<u>dissolutionDate</u>	Date	The date that this organization was dissolved.
<u>duns</u>	Text	The Dun & Bradstreet DUNS number for identifying an organization or business person.
<u>email</u>	Text	Email address.
<u>employee</u>	<u>Person</u>	Someone working for this organization. Supersedes <u>employees</u> .
<u>event</u>	<u>Event</u>	Upcoming or past event associated with this place, organization, or action. Supersedes <u>events</u> .
<u>faxNumber</u>	Text	The fax number.
<u>founder</u>	<u>Person</u>	A person who founded this organization.

Property	Expected Type	Description
		Supersedes <u>founders</u> .
<u>foundingDate</u>	<u>Date</u>	The date that this organization was founded.
<u>foundingLocation</u>	<u>Place</u>	The place where the Organization was founded.
<u>funder</u>	<u>Organization</u> <u>Person</u>	or A person or organization that supports (sponsors) something through some kind of financial contribution.
<u>globalLocationNumber</u>	<u>Text</u>	The <u>Global Location Number</u> (GLN, sometimes also referred to as International Location Number or ILN) of the respective organization, person, or place. The GLN is a 13-digit number used to identify parties and physical locations.
<u>hasOfferCatalog</u>	<u>OfferCatalog</u>	Indicates an OfferCatalog listing for this Organization, Person, or Service.
<u>hasPOS</u>	<u>Place</u>	Points-of-Sales operated by the organization or person.
<u>isicV4</u>	<u>Text</u>	The International Standard of Industrial Classification of All Economic Activities (ISIC), Revision 4 code for a particular organization, business person, or place.
<u>legalName</u>	<u>Text</u>	The official name of the organization, e.g. the registered company name.
<u>leiCode</u>	<u>Text</u>	An organization identifier that uniquely identifies a legal entity as defined in ISO 17442.
<u>location</u>	<u>Place</u> <u>PostalAddress</u> <u>Text</u>	or The location of for example where the event is happening, an organization is located, or where an action takes place.
<u>logo</u>	<u>ImageObject</u> <u>URL</u>	or An associated logo.
<u>makesOffer</u>	<u>Offer</u>	A pointer to products or services offered by the organization or person. Inverse property: <u>offeredBy</u> .
<u>member</u>	<u>Organization</u> <u>Person</u>	or A member of an Organization or a ProgramMembership. Organizations can be members of organizations; ProgramMembership is typically for individuals. Supersedes <u>members</u> , <u>musicGroupMember</u> . Inverse property: <u>memberOf</u> .

Property	Expected Type	Description
<u>memberOf</u>	<u>Organization</u> or <u>ProgramMembership</u>	An Organization (or ProgramMembership) to which this Person or Organization belongs. Inverse property: <u>member</u> .
<u>naics</u>	Text	The North American Industry Classification System (NAICS) code for a particular organization or business person.
<u>numberOfEmployees</u>	QuantitativeValue	The number of employees in an organization e.g. business.
<u>owns</u>	<u>OwnershipInfo</u> or <u>Product</u>	Products owned by the organization or person.
<u>parentOrganization</u>	<u>Organization</u>	The larger organization that this local business is a branch of, if any. Supersedes <u>branchOf</u> . Inverse property: <u>subOrganization</u> .
<u>review</u>	Review	A review of the item. Supersedes <u>reviews</u> .
<u>seeks</u>	Demand	A pointer to products or services sought by the organization or person (demand).
<u>sponsor</u>	<u>Organization</u> or <u>Person</u>	A person or organization that supports a thing through a pledge, promise, or financial contribution. e.g. a sponsor of a Medical Study or a corporate sponsor of an event.
<u>subOrganization</u>	<u>Organization</u>	A relationship between two organizations where the first includes the second, e.g., as a subsidiary. See also: the more specific 'department' property. Inverse property: <u>parentOrganization</u> .
<u>taxID</u>	Text	The Tax / Fiscal ID of the organization or person, e.g. the TIN in the US or the CIF/NIF in Spain.
<u>telephone</u>	Text	The telephone number.
<u>vatID</u>	Text	The Value-added Tax ID of the organization or person.

### B.3 Schema.org entity descriptions: Person

Property	Expected Type	Description
<b>Properties from Person</b>		
<u>additionalName</u>	<u>Text</u>	An additional name for a Person, can be used for a middle name.
<u>address</u>	<u>PostalAddress</u> <u>Text</u>	or Physical address of the item.
<u>affiliation</u>	<u>Organization</u>	An organization that this person is affiliated with. For example, a school/university, a club, or a team.
<u>alumniOf</u>	<u>EducationalOrganization</u> or <u>Organization</u>	An organization that the person is an alumni of. Inverse property: <u>alumni</u> .
<u>award</u>	<u>Text</u>	An award won by or for this item. Supersedes <u>awards</u> .
<u>birthDate</u>	<u>Date</u>	Date of birth.
<u>birthPlace</u>	<u>Place</u>	The place where the person was born.
<u>brand</u>	<u>Brand</u> <u>Organization</u>	or The brand(s) associated with a product or service, or the brand(s) maintained by an organization or business person.
<u>children</u>	<u>Person</u>	A child of the person.
<u>colleague</u>	<u>Person</u> <u>URL</u>	or A colleague of the person. Supersedes <u>colleagues</u> .
<u>contactPoint</u>	<u>ContactPoint</u>	A contact point for a person or organization. Supersedes <u>contactPoints</u> .
<u>deathDate</u>	<u>Date</u>	Date of death.
<u>deathPlace</u>	<u>Place</u>	The place where the person died.
<u>duns</u>	<u>Text</u>	The Dun & Bradstreet DUNS number for identifying an organization or business person.
<u>email</u>	<u>Text</u>	Email address.
<u>familyName</u>	<u>Text</u>	Family name. In the U.S., the last name of a Person. This can be used along with givenName instead of the name property.

Property	Expected Type	Description
<u>faxNumber</u>	<u>Text</u>	The fax number.
<u>follows</u>	<u>Person</u>	The most generic uni-directional social relation.
<u>funder</u>	<u>Organization</u> <u>Person</u>	or A person or organization that supports (sponsors) something through some kind of financial contribution.
<u>gender</u>	<u>GenderType</u> <u>Text</u>	or Gender of the person. While <a href="http://schema.org/Male">http://schema.org/Male</a> and <a href="http://schema.org/Female">http://schema.org/Female</a> may be used, text strings are also acceptable for people who do not identify as a binary gender.
<u>givenName</u>	<u>Text</u>	Given name. In the U.S., the first name of a Person. This can be used along with <u>familyName</u> instead of the <u>name</u> property.
<u>globalLocationNumber</u>	<u>Text</u>	The <u>Global Location Number</u> (GLN, sometimes also referred to as International Location Number or ILN) of the respective organization, person, or place. The GLN is a 13-digit number used to identify parties and physical locations.
<u>hasOfferCatalog</u>	<u>OfferCatalog</u>	Indicates an OfferCatalog listing for this Organization, Person, or Service.
<u>hasPOS</u>	<u>Place</u>	Points-of-Sales operated by the organization or person.
<u>height</u>	<u>Distance</u> <u>QuantitativeValue</u>	or The height of the item.
<u>homeLocation</u>	<u>ContactPoint</u> <u>Place</u>	or A contact location for a person's residence.
<u>honorificPrefix</u>	<u>Text</u>	An honorific prefix preceding a Person's name such as Dr/Mrs/Mr.
<u>honorificSuffix</u>	<u>Text</u>	An honorific suffix preceding a Person's name such as M.D. /PhD/MSCSW.
<u>isicV4</u>	<u>Text</u>	The International Standard of Industrial Classification of All Economic Activities (ISIC), Revision 4 code for a particular organization, business person, or place.

Property	Expected Type	Description
<u>jobTitle</u>	<u>Text</u>	The job title of the person (for example, Financial Manager).
<u>knows</u>	<u>Person</u>	The most generic bi-directional social/work relation.
<u>makesOffer</u>	<u>Offer</u>	A pointer to products or services offered by the organization or person. Inverse property: <u>offeredBy</u> .
<u>memberOf</u>	<u>Organization</u> <u>ProgramMembership</u>	or An Organization (or ProgramMembership) to which this Person or Organization belongs. Inverse property: <u>member</u> .
<u>naics</u>	<u>Text</u>	The North American Industry Classification System (NAICS) code for a particular organization or business person.
<u>nationality</u>	<u>Country</u>	Nationality of the person.
<u>netWorth</u>	<u>MonetaryAmount</u> <u>PriceSpecification</u>	or The total financial value of the person as calculated by subtracting assets from liabilities.
<u>owns</u>	<u>OwnershipInfo</u> <u>Product</u>	or Products owned by the organization or person.
<u>parent</u>	<u>Person</u>	A parent of this person. Supersedes <u>parents</u> .
<u>performerIn</u>	<u>Event</u>	Event that this person is a performer or participant in.
<u>relatedTo</u>	<u>Person</u>	The most generic familial relation.
<u>seeks</u>	<u>Demand</u>	A pointer to products or services sought by the organization or person (demand).
<u>sibling</u>	<u>Person</u>	A sibling of the person. Supersedes <u>siblings</u> .
<u>sponsor</u>	<u>Organization</u> <u>Person</u>	or A person or organization that supports a thing through a pledge, promise, or financial contribution. e.g. a sponsor of a Medical Study or a corporate sponsor of an event.
<u>spouse</u>	<u>Person</u>	The person's spouse.

Property	Expected Type	Description
<u>taxID</u>	<u>Text</u>	The Tax / Fiscal ID of the organization or person, e.g. the TIN in the US or the CIF/NIF in Spain.
<u>telephone</u>	<u>Text</u>	The telephone number.
<u>vatID</u>	<u>Text</u>	The Value-added Tax ID of the organization or person.
<u>weight</u>	<u>QuantitativeValue</u>	The weight of the product or person.
<u>workLocation</u>	<u>ContactPoint</u> <u>Place</u>	or A contact location for a person's place of work.
<u>worksFor</u>	<u>Organization</u>	Organizations that the person works for.

## B.4 Schema.org entity descriptions: PostalAddress

Property	Expected Type	Description
<b>Properties from <u>PostalAddress</u></b>		
<u>addressCountry</u>	<u>Country</u> or <u>Text</u>	The country. For example, USA. You can also provide the two-letter <u>ISO 3166-1 alpha-2 country code</u> .
<u>addressLocality</u>	<u>Text</u>	The locality. For example, Mountain View.
<u>addressRegion</u>	<u>Text</u>	The region. For example, CA.
<u>postOfficeBoxNumber</u>	<u>Text</u>	The post office box number for PO box addresses.
<u>postalCode</u>	<u>Text</u>	The postal code. For example, 94043.
<u>streetAddress</u>	<u>Text</u>	The street address. For example, 1600 Amphitheatre Pkwy.

## B.5 Schema.org entity descriptions: Product

Property	Expected Type	Description
<b>Properties from <u>Product</u></b>		
<u>additionalProperty</u>	<u>PropertyValue</u>	<p>A property–value pair representing an additional characteristics of the entity, e.g. a product feature or another characteristic for which there is no matching property in schema.org.</p> <p>Note: Publishers should be aware that applications designed to use specific schema.org properties (e.g. <a href="http://schema.org/width">http://schema.org/width</a>, <a href="http://schema.org/color">http://schema.org/color</a>, <a href="http://schema.org/gtin13">http://schema.org/gtin13</a>, ...) will typically expect such data to be provided using those properties, rather than using the generic property/value mechanism.</p>
<u>aggregateRating</u>	<u>AggregateRating</u>	The overall rating, based on a collection of reviews or ratings, of the item.
<u>audience</u>	<u>Audience</u>	An intended audience, i.e. a group for whom something was created. Supersedes <u>serviceAudience</u> .
<u>award</u>	<u>Text</u>	An award won by or for this item. Supersedes <u>awards</u> .
<u>brand</u>	<u>Brand</u> or <u>Organization</u>	The brand(s) associated with a product or service, or the brand(s) maintained by an organization or business person.
<u>category</u>	<u>Text</u> or <u>Thing</u>	A category for the item. Greater signs or slashes can be used to informally indicate a category hierarchy.
<u>color</u>	<u>Text</u>	The color of the product.
<u>depth</u>	<u>Distance</u> or <u>QuantitativeValue</u>	The depth of the item.
<u>gtin12</u>	<u>Text</u>	The <u>GTIN–12</u> code of the product, or the product to which the offer refers. The GTIN–12 is the 12–digit GS1 Identification Key composed of a U.P.C. Company Prefix, Item Reference, and Check Digit used to identify trade items. See <u>GS1 GTIN Summary</u> for more

Property	Expected Type	Description
		details.
<u>gtin13</u>	<u>Text</u>	The <u>GTIN-13</u> code of the product, or the product to which the offer refers. This is equivalent to 13-digit ISBN codes and EAN UCC-13. Former 12-digit UPC codes can be converted into a GTIN-13 code by simply adding a preceding zero. See <u>GS1 GTIN Summary</u> for more details.
<u>gtin14</u>	<u>Text</u>	The <u>GTIN-14</u> code of the product, or the product to which the offer refers. See <u>GS1 GTIN Summary</u> for more details.
<u>gtin8</u>	<u>Text</u>	The <u>GTIN-8</u> code of the product, or the product to which the offer refers. This code is also known as EAN/UCC-8 or 8-digit EAN. See <u>GS1 GTIN Summary</u> for more details.
<u>height</u>	<u>Distance</u> or <u>QuantitativeValue</u>	The height of the item.
<u>isAccessoryOrSparePartFor</u>	<u>Product</u>	A pointer to another product (or multiple products) for which this product is an accessory or spare part.
<u>isConsumableFor</u>	<u>Product</u>	A pointer to another product (or multiple products) for which this product is a consumable.
<u>isRelatedTo</u>	<u>Product</u> or <u>Service</u>	A pointer to another, somehow related product (or multiple products).
<u>isSimilarTo</u>	<u>Product</u> or <u>Service</u>	A pointer to another, functionally similar product (or multiple products).
<u>itemCondition</u>	<u>OfferItemCondition</u>	A predefined value from OfferItemCondition or a textual description of the condition of the product or service, or the products or services included in the offer.
<u>logo</u>	<u>ImageObject</u> or <u>URL</u>	An associated logo.
<u>manufacturer</u>	<u>Organization</u>	The manufacturer of the product.
<u>model</u>	<u>ProductModel</u> or <u>Text</u>	The model of the product. Use with the URL of a ProductModel or a textual representation of the model identifier. The

Property	Expected Type	Description
		URL of the ProductModel can be from an external source. It is recommended to additionally provide strong product identifiers via the gtin8/gtin13/gtin14 and mpn properties.
<u>mpn</u>	<u>Text</u>	The Manufacturer Part Number (MPN) of the product, or the product to which the offer refers.
<u>offers</u>	<u>Offer</u>	An offer to provide this item—for example, an offer to sell a product, rent the DVD of a movie, perform a service, or give away tickets to an event.
<u>productID</u>	<u>Text</u>	The product identifier, such as ISBN. For example: meta itemprop="productID" content="isbn:123-456-789".
<u>productionDate</u>	<u>Date</u>	The date of production of the item, e.g. vehicle.
<u>purchaseDate</u>	<u>Date</u>	The date the item e.g. vehicle was purchased by the current owner.
<u>releaseDate</u>	<u>Date</u>	The release date of a product or product model. This can be used to distinguish the exact variant of a product.
<u>review</u>	<u>Review</u>	A review of the item. Supersedes <u>reviews</u> .
<u>sku</u>	<u>Text</u>	The Stock Keeping Unit (SKU), i.e. a merchant-specific identifier for a product or service, or the product to which the offer refers.
<u>weight</u>	<u>QuantitativeValue</u>	The weight of the product or person.
<u>width</u>	<u>Distance</u> or <u>QuantitativeValue</u>	The width of the item.

## B.6 Schema.org entity descriptions: QuantitativeValue

Property	Expected Type	Description
<b>Properties from <u>QuantitativeValue</u></b>		
<u>additionalProperty</u>	<u>PropertyValue</u>	<p>A property–value pair representing an additional characteristics of the entity, e.g. a product feature or another characteristic for which there is no matching property in schema.org.</p> <p>Note: Publishers should be aware that applications designed to use specific schema.org properties (e.g. <a href="http://schema.org/width">http://schema.org/width</a>, <a href="http://schema.org/color">http://schema.org/color</a>, <a href="http://schema.org/gtin13">http://schema.org/gtin13</a>, ...) will typically expect such data to be provided using those properties, rather than using the generic property/value mechanism.</p>
<u>maxValue</u>	<u>Number</u>	The upper value of some characteristic or property.
<u>minValue</u>	<u>Number</u>	The lower value of some characteristic or property.
<u>unitCode</u>	<u>Text</u> <u>URL</u>	or The unit of measurement given using the UN/CEFACT Common Code (3 characters) or a URL. Other codes than the UN/CEFACT Common Code may be used with a prefix followed by a colon.
<u>unitText</u>	<u>Text</u>	A string or text indicating the unit of measurement. Useful if you cannot provide a standard unit code for <u>unitCode</u> .
<u>value</u>	<u>Boolean</u> <u>Number</u> <u>StructuredValue</u> <u>Text</u>	<p>or or or</p> <p>The value of the quantitative value or property value node.</p> <ul style="list-style-type: none"> <li>For <u>QuantitativeValue</u> and <u>MonetaryAmount</u>, the recommended type for values is 'Number'.</li> <li>For <u>PropertyValue</u>, it can be 'Text;', 'Number', 'Boolean', or 'StructuredValue'.</li> </ul>
<u>valueReference</u>	<u>Enumeration</u> <u>PropertyValue</u> <u>QualitativeValue</u> <u>QuantitativeValue</u> <u>StructuredValue</u>	<p>or or or or</p> <p>A pointer to a secondary value that provides additional information on the original value, e.g. a reference temperature.</p>

## B.7 Schema.org entity descriptions: Vehicle

Property	Expected Type	Description
<b>Properties from <u>Vehicle</u></b>		
<u><a href="#">cargoVolume</a></u>	<u>QuantitativeValue</u>	<p>The available volume for cargo or luggage. For automobiles, this is usually the trunk volume.</p> <p>Typical unit code(s): LTR for liters, FTQ for cubic foot/feet</p> <p>Note: You can use <u>minValue</u> and <u>maxValue</u> to indicate ranges.</p>
<u><a href="#">dateVehicleFirstRegistered</a></u>	<u>Date</u>	<p>The date of the first registration of the vehicle with the respective public authorities.</p>
<u><a href="#">driveWheelConfiguration</a></u>	<u>DriveWheelConfigurationValue</u> or <u>Text</u>	<p>The drive wheel configuration, i.e. which roadwheels will receive torque from the vehicle's engine via the drivetrain.</p>
<u><a href="#">fuelConsumption</a></u>	<u>QuantitativeValue</u>	<p>The amount of fuel consumed for traveling a particular distance or temporal duration with the given vehicle (e.g. litres per 100 km).</p> <ul style="list-style-type: none"> <li>Note 1: There are unfortunately no standard unit codes for liters per 100 km. Use <u>unitText</u> to indicate the unit of measurement, e.g. L/100 km.</li> <li>Note 2: There are two ways of indicating the fuel consumption, <u>fuelConsumption</u> (e.g. 8 liters per 100 km) and <u>fuelEfficiency</u> (e.g. 30 miles per gallon). They are reciprocal.</li> <li>Note 3: Often, the absolute value is useful only when related to driving speed ("at 80 km/h") or usage pattern ("city traffic"). You can use <u>valueReference</u> to link the value for the fuel consumption to another value.</li> </ul>

Property	Expected Type	Description
<u><a href="#">fuelEfficiency</a></u>	<u><a href="#">QuantitativeValue</a></u>	<p>The distance traveled per unit of fuel used; most commonly miles per gallon (mpg) or kilometers per liter (km/L).</p> <ul style="list-style-type: none"> <li>Note 1: There are unfortunately no standard unit codes for miles per gallon or kilometers per liter. Use <u><a href="#">unitText</a></u> to indicate the unit of measurement, e.g. mpg or km/L.</li> <li>Note 2: There are two ways of indicating the fuel consumption, <u><a href="#">fuelConsumption</a></u>(e.g. 8 liters per 100 km) and <u><a href="#">fuelEfficiency</a></u> (e.g. 30 miles per gallon). They are reciprocal.</li> <li>Note 3: Often, the absolute value is useful only when related to driving speed ("at 80 km/h") or usage pattern ("city traffic"). You can use <u><a href="#">valueReference</a></u> to link the value for the fuel economy to another value.</li> </ul>
<u><a href="#">fuelType</a></u>	<u><a href="#">QualitativeValue</a></u> <u><a href="#">Text</a></u> <u><a href="#">URL</a></u>	<p>or or</p> <p>The type of fuel suitable for the engine or engines of the vehicle. If the vehicle has only one engine, this property can be attached directly to the vehicle.</p>
<u><a href="#">knownVehicleDamages</a></u>	<u><a href="#">Text</a></u>	<p>A textual description of known damages, both repaired and unrepaired.</p>
<u><a href="#">mileageFromOdometer</a></u>	<u><a href="#">QuantitativeValue</a></u>	<p>The total distance travelled by the particular vehicle since its initial production, as read from its odometer. Typical unit code(s): KMT for kilometers, SMI for statute miles</p>
<u><a href="#">numberOfAirbags</a></u>	<u><a href="#">Number</a></u> <u><a href="#">Text</a></u>	<p>or</p> <p>The number or type of airbags in the vehicle.</p>
<u><a href="#">numberOfAxles</a></u>	<u><a href="#">Number</a></u> <u><a href="#">QuantitativeValue</a></u>	<p>or</p> <p>The number of axles. Typical unit code(s): C62</p>
<u><a href="#">numberOfDoors</a></u>	<u><a href="#">Number</a></u> <u><a href="#">QuantitativeValue</a></u>	<p>or</p> <p>The number of doors. Typical unit code(s): C62</p>
<u><a href="#">numberOfForwardGears</a></u>	<u><a href="#">Number</a></u> <u><a href="#">QuantitativeValue</a></u>	<p>or</p> <p>The total number of forward gears available for the transmission system of the vehicle.</p>

Property	Expected Type	Description
		Typical unit code(s): C62
<u>numberOfPreviousOwners</u>	<u>Number</u> or <u>QuantitativeValue</u>	The number of owners of the vehicle, including the current one. Typical unit code(s): C62
<u>productionDate</u>	<u>Date</u>	The date of production of the item, e.g. vehicle.
<u>purchaseDate</u>	<u>Date</u>	The date the item e.g. vehicle was purchased by the current owner.
<u>steeringPosition</u>	<u>SteeringPositionValue</u>	The position of the steering wheel or similar device (mostly for cars).
<u>vehicleConfiguration</u>	<u>Text</u>	A short text indicating the configuration of the vehicle, e.g. '5dr hatchback ST 2.5 MT 225 hp' or 'limited edition'.
<u>vehicleEngine</u>	<u>EngineSpecification</u>	Information about the engine or engines of the vehicle.
<u>vehicleIdentificationNumber</u>	<u>Text</u>	The Vehicle Identification Number (VIN) is a unique serial number used by the automotive industry to identify individual motor vehicles.
<u>vehicleInteriorColor</u>	<u>Text</u>	The color or color combination of the interior of the vehicle.
<u>vehicleInteriorType</u>	<u>Text</u>	The type or material of the interior of the vehicle (e.g. synthetic fabric, leather, wood, etc.). While most interior types are characterized by the material used, an interior type can also be based on vehicle usage or target audience.
<u>vehicleModelDate</u>	<u>Date</u>	The release date of a vehicle model (often used to differentiate versions of the same make and model).
<u>vehicleSeatingCapacity</u>	<u>Number</u> or <u>QuantitativeValue</u>	The number of passengers that can be seated in the vehicle, both in terms of the physical space available, and in terms of limitations set by law. Typical unit code(s): C62 for persons.

Property	Expected Type	Description
<b><u>vehicleSpecialUsage</u></b>	<u>Text</u>	Indicates whether the vehicle has been used for special purposes, like commercial rental, driving school, or as a taxi. The legislation in many countries requires this information to be revealed when offering a car for sale.
<b><u>vehicleTransmission</u></b>	<u>QualitativeValue</u> <u>Text</u> <u>URL</u>	or or The type of component used for transmitting the power from a rotating power source to the wheels or other relevant component(s) ("gearbox" for cars).

## Annex C Document Management

### C.1 Document History

Version	Date	Brief Description of Change	Approval Authority	Editor / Company
0.10	8 Sept 2016	New PRD - first draft	PSMC	Allan Bartlett / GSMA
1.0	11 Oct 2016	Approved first version	PSMC	Allan Bartlett / GSMA
2.0	21 June 2017	<p>Updated PRD with the following improved definitions:</p> <ol style="list-style-type: none"> <li>1. Mandatory Null Values removed (Generic issue) changed to three possible combinations (section 2.3):                             <ol style="list-style-type: none"> <li>I. "Mandatory / May not be Null" – attribute must always be specified and with a non Null value;</li> <li>II. "Recommended / May be Null" – attribute should always be specified but may have a Null value or may default to a defined value if omitted;</li> <li>III. "Optional / May be Null" – attribute may be specified but may have a Null value or may default to a defined value if omitted.</li> </ol> </li> <li>2. 'EnvironmentObserved' entity 2.3.16 has 'Measurand' attribute removed due to ambiguous usage.</li> <li>3. 'Machine' entity 2.3.17 has 'factory' attribute added.</li> <li>4. 'Product' entity 2.3.21 allowed only one supplierName to be listed (Specific to 'Product' entity) so changed to supplier or the URL to the supplier of the product or to a list of suppliers for the product. The URL can point to either a web page for one or more suppliers or a JSON based list of suppliers structured using the Schema.org defined 'Organisation'URL</li> <li>5. 'ProductRecord' entity 2.3.22 (Specific issue to 'ProductRecord') enhanced e.g. O2 attribute</li> <li>6. 'Vehicle' entity 2.3.28 references multiple 'VehicleType's (Specific to 'Vehicle' entity) so changed the definition of the 'refVehicleType' attribute to a single value rather than a list of values.</li> <li>7. 'Vehicle' entity 2.3.28 updated with 'fuelEconomy' attribute adopted to use the Schema.org definition of 'fuelEfficiency' which is based on 'QuantitativeValue'.</li> <li>8. 'WaterQualityObserved' 2.3.31 - removed 'measurand' (Generic issue with 'measurand'). <b>Measurand removed</b> from this and all other entity definitions.</li> <li>9. 'WeatherForecast' 2.3.32 attribute</li> </ol>	Project Approval	Allan Bartlett / GSMA

		<p>'visibility' lacked agreement on definition (Specific issue to 'WeatherForecast') so revised to type 'ExtQuantitativeValue' and normally recorded in metres (though with the option to use 'statute miles' provided the relevant unitCode is used within 'ExtQuantitativeValue')</p> <p>10. 'WeatherForecast' 2.3.32 validity period was not queryable using NGSiv2 (Generic issue for validity periods) so revised the 'validity' attribute to separate 'validFrom' and 'validTo' attributes.</p> <p>11. 'WeatherForecast' 2.3.32 'dayMinimum' &amp; 'dayMaximum' attributes was not queryable using NGSiv2 (Generic issue relating to 'Array of text') so have been revised.</p> <p>GSMA logo updated on page 1                  Typo on page 11 of Whcere corrected to Where</p>		

## C.2 Other Information

Type	Description
Document Owner	Connected Living – IoT Big Data Project
Editor / Company	GSMA

It is our intention to provide a quality product for your use. If you find any errors or omissions, please contact us with your comments. You may notify us at [prd@gsma.com](mailto:prd@gsma.com)

Your comments or suggestions & questions are always welcome.