



## RSP Test Certificates Definition

Version 1.1

10 October 2017

*This is a Non-binding Permanent Reference Document of the GSMA*

---

### **Security Classification: Non-confidential**

Access to and distribution of this document is restricted to the persons permitted by the security classification. This document is confidential to the Association and is subject to copyright protection. This document is to be used only for the purposes for which it has been supplied and information contained in it must not be disclosed or in any other way made available, in whole or in part, to persons other than those permitted under the security classification without the prior written approval of the Association.

### **Copyright Notice**

Copyright © 2017 GSM Association

### **Disclaimer**

The GSM Association ("Association") makes no representation, warranty or undertaking (express or implied) with respect to and does not accept any responsibility for, and hereby disclaims liability for the accuracy or completeness or timeliness of the information contained in this document. The information contained in this document may be subject to change without prior notice.

### **Antitrust Notice**

The information contain herein is in full compliance with the GSM Association's antitrust compliance policy.

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>4</b>
1.1	Scope	4
1.2	References	4
<b>2</b>	<b>Tool chain for generation of the keys and certificates</b>	<b>4</b>
2.1	OpenSSL	4
2.2	Keys generation	5
2.3	CI Certificate Generation	5
2.4	Non-Root Certificate generation	6
2.5	Certificate display	7
<b>3</b>	<b>Test Certificates and keys – Valid test cases</b>	<b>8</b>
3.1	Certificate Issuer	8
3.1.1	CI Certificate: definition of data to be signed	8
3.1.2	CI Keys and Certificate	9
3.1.3	Input data for generation	9
3.2	eUICC	9
3.2.1	eUICC Certificate: definition of data to be signed	9
3.2.2	eUICC Keys and Certificate	10
3.2.3	Input data for generation	11
3.3	EUM	11
3.3.1	EUM Certificate: definition of data to be signed	11
3.3.2	EUM Keys and Certificate	12
3.3.3	Input data for generation	13
3.4	SM-DP+	13
3.4.1	DPauth	13
3.4.1.1	SM-DP+ n°1 Certificate for Authentication: definition of data to be signed	13
3.4.1.2	SM-DP+ n°1 Keys and Certificate	14
3.4.1.3	SM-DP+ n°1: Input data for generation	14
3.4.1.4	SM-DP+ n°2 Certificate for Authentication: definition of data to be signed	15
3.4.1.5	SM-DP+ n°2 Keys and Certificate	16
3.4.1.6	SM-DP+ n°2: Input data for generation	16
3.4.2	DPpb	17
3.4.2.1	SM-DP+ n°1 Certificate for Profile Binding: definition of data to be signed	17
3.4.2.2	SM-DP+ n°1 Keys and Certificate	17
3.4.2.3	SM-DP+ n°1: Input data for generation	18
3.4.2.4	SM-DP+ n°2 Certificate for Profile Binding: definition of data to be signed	18
3.4.2.5	SM-DP+ n°2 Keys and Certificate	19
3.4.2.6	SM-DP+ n°2: Input data for generation	20
3.4.3	TLS	20
3.4.3.1	SM-DP+ n°1 TLS Certificate: definition of data to be signed	20

3.4.3.2	SM-DP+ n°1 TLS Keys and Certificate	21
3.4.3.3	Input data for generation	21
3.4.3.4	SM-DP+ n°2 TLS Certificate: definition of data to be signed	22
3.4.3.5	SM-DP+ n°2 TLS Keys and Certificate	23
3.4.3.6	Input data for generation	23
3.5	SM-DS	23
3.5.1	DSauth	23
3.5.1.1	SM-DS Certificate for Authentication: definition of data to be signed	23
3.5.1.2	SM-DS Keys and Certificate	24
3.5.1.3	Input data for generation	25
3.5.2	TLS	25
3.5.2.1	SM-DS n°1 TLS Certificate: definition of data to be signed	25
3.5.2.2	SM-DS n°1 TLS Keys and Certificate	26
3.5.2.3	Input data for generation	26
3.5.2.4	SM-DS n°2 TLS Certificate: definition of data to be signed	27
3.5.2.5	SM-DS n°2 TLS Keys and Certificate	27
3.5.2.6	Input data for generation	28
<b>4</b>	<b>Test Certificates and keys – Invalid test cases</b>	<b>28</b>
4.1	eUICC	28
4.2	SM-DP+	28
4.2.1	DPauth	28
4.2.1.1	DPAuth – Invalid Signature	28
4.2.2	DPpb	30
4.2.2.1	DPpb – Invalid Signature	30
4.2.2.2	DPpb – Invalid Curve	31
4.2.3	TLS	32
4.3	SM-DS: Invalid signature	42
4.3.1	DSauth	42
4.3.1.1	DSauth – Invalid Signature	42
4.3.2	TLS	44
<b>Annex A</b>	<b>RSP Certificates and Keys Files (Normative)</b>	<b>55</b>
<b>Annex B</b>	<b>Document Management</b>	<b>56</b>
B.1	Document History	56

## 1 Introduction

### 1.1 Scope

This document's scope is to define the Test Certificates that will be used in the tests specified in SGP.23 [1] based on SGP.22 [2].

These Test Certificates are based on NIST P-256 and/or BrainpoolP256r1 curves.

The certificates to be created for nominal test cases, along with the relevant key pairs, are the following:

- One GSMA CI Certificate (CERT.CI.ECDSA) per curve
- One EUM Certificate (CERT.EUM.ECDSA) per curve
- For each SM-DP+, two Certificates (CERT.DPauth.ECDSA and CERT.DPpb.ECDSA) per curve
- Two SM-DP+ TLS Certificate (CERT.DP.TLS) per curve
- One eUICC Certificate (CERT.EUICC.ECDSA) per curve
- One SM-DS Certificate (CERT.DSauth.ECDSA) per curve
- Two SM-DS TLS Certificate (CERT.DS.TLS) per curve

The certificates to be created for error cases are the following:

- Two SM-DP+ Certificates (CERT.DPauth.ECDSA and CERT.DPpb.ECDSA) per curve with invalid signature
- One SM-DS Certificate (CERT.DSauth.ECDSA) per curve with invalid signature
- Two SM-DP+ Certificates (CERT.DPauth.ECDSA and CERT.DPpb.ECDSA) with invalid curve
- One SM-DS Certificate (CERT.DSauth.ECDSA) with invalid curve

### 1.2 References

Ref	Document Number	Title
[1]	SGP.22	GSMA "RSP Technical specification" V2.1
[2]	SGP.23	GSMA "RSP Test Specification" v1.0
[3]	RFC5280	Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile

## 2 Tool chain for generation of the keys and certificates

This section describes the tools and the environment that have been used to generate the keys and the certificates described in this document.

### 2.1 OpenSSL

OpenSSL is an open source project that also provides a general-purpose cryptography library.

Information and documentation can be found here: <https://www.openssl.org/>.

Binaries can be downloaded here: <https://wiki.openssl.org/index.php/Binaries>.

The next section assumes that the tool has been installed and correctly configured in your environment.

The OpenSSL version used to generate the certificates in this document is 1.1.0e

## 2.2 Keys generation

The following command lines generate (randomly) a private key

- For NIST P-256 curve:

```
openssl ecparam -name prime256v1 -genkey -out <sk_file_name>
```

- For brainpoolP256r1 curve:

```
openssl ecparam -name brainpoolP256r1 -genkey -out <sk_file_name>
```

<sk\_file\_name> specifies the file name that will contain the generated private key (not encrypted) in the PEM form.

Note: The PEM form is the default format: it consists of the ASN.1 DER format base64 encoded with additional header and footer lines.

The complete description of the `openssl ecparam` command can be found here: <https://www.openssl.org/docs/man1.1.0/apps/ecparam.html>

The following command line generates the related public key.

```
openssl ec -in <sk_file_name> -pubout -out <pk_file_name>
```

<sk\_file\_name> specifies the file name that contains the private key generated with the previous command line.

<pk\_file\_name> specifies the file name that will contain the generated public key in the PEM form.

The complete description of the `openssl ec` command can be found here: <https://www.openssl.org/docs/man1.1.0/apps/ec.html>

## 2.3 CI Certificate Generation

The following command lines generate a root certificate like for the GSMA CI. The first command line generates the certificate in PEM format (Base64 encoded) and the second

command line converts the same certificate from PEM format into DER (i.e. binary DER) encoded format.

```
openssl req -config <ca_configuration_file> -key <ca_sk_file_name> -new -x509 -days  
<days> -sha256 -set_serial <serial> -extensions extend -out <cert_pem_file_name>  
  
openssl x509 -in <cert_pem_file_name> -outform DER -out <cert_der_file_name>
```

<ca\_configuration\_file> is the configuration file that contains the attributes and extensions values of the CA certificate.

<ca\_sk\_file\_name> specifies the file name that contains the CA private key in PEM format.

<serial> specifies the serial number to set in the certificate.

<days> specifies the number of days of validity to set in the certificate.

<cert\_pem\_file\_name> specifies the file name that will contain the certificate in PEM format.

<cert\_der\_file\_name> specifies the file name that will contain the certificate in DER format

The complete description of the `openssl req` command can be found here:

<https://www.openssl.org/docs/man1.1.0/apps/req.html>

The complete description of the input data file format for <ca\_configuration\_file> specifying certificate extension can be found here:

[https://www.openssl.org/docs/man1.1.0/apps/x509v3\\_config.html](https://www.openssl.org/docs/man1.1.0/apps/x509v3_config.html)

## 2.4 Non-Root Certificate generation

The generation of a certificate starts with the generation of a Certificate Signing Request (CSR). The following command line generates this CSR.

```
openssl req -new -nodes -sha256 -config <input_csr_file_name> -key <sk_file_name> -  
out <csr_file_name>
```

<input\_csr\_file\_name> specifies the file name that contains the input data for CSR.

<sk\_file\_name> specifies the file name that contains the private key generated with the command described in section 2.2.

<csr\_file\_name> specifies the file name that will contain the generated CSR.

The complete description of the `openssl req` command can be found here:

<https://www.openssl.org/docs/man1.1.0/apps/req.html>

The complete description of the input data file format for CSR can be found here:

[https://www.openssl.org/docs/man1.1.0/apps/x509v3\\_config.html](https://www.openssl.org/docs/man1.1.0/apps/x509v3_config.html)

The following command lines generate the certificate corresponding to a CSR. The first command line generates the certificate in PEM format (Base64 encoded) and the second

command line converts the same certificate from PEM format into DER (i.e. binary DER) encoded format.

```
openssl x509 -req -in <csr_file_name> -CA <ca_cert_file_name> -CAkey  
<ca_sk_file_name> -set_serial <serial> -days <days> -extfile <cert_ext_file_name> -  
out <cert_pem_file_name>  
  
openssl x509 -in <cert_pem_file_name> -outform DER -out <cert_der_file_name>
```

<csr\_file\_name> specifies the file name that contains the CSR generated with the previous command line.

<ca\_cert\_file\_name> specifies the file name that contains the CA Certificate in PEM format.

<ca\_sk\_file\_name> specifies the file name that contains the CA private key in PEM format related to the certificate indicated by <ca\_cert\_file\_name>.

<serial> specifies the serial number to set in the certificate.

<days> specifies the number of days of validity to set in the certificate.

<cert\_ext\_file\_name> specifies the file name that contains certificate extensions to set in the certificate.

<cert\_pem\_file\_name> specifies the file name that will contain the certificate in PEM format.

<cert\_der\_file\_name> specifies the file name that will contain the certificate in DER format

**NOTE:** As defined, the input CA certificate to generate the Non-Root Certificates SHALL be in PEM format, the following command will be used to convert from DER format to PEM format (whether the PEM format is not provided)

```
openssl x509 -inform der -in <cert_der_file_name> -out <cert_pem_file_name>
```

The complete description of the `openssl x509` command can be found here:

<https://www.openssl.org/docs/man1.1.0/apps/x509.html>

The complete description of the file format for specifying certificate extension can be found here: [https://www.openssl.org/docs/man1.1.0/apps/x509v3\\_config.html](https://www.openssl.org/docs/man1.1.0/apps/x509v3_config.html)

## 2.5 Certificate display

A certificate can be displayed with the following command lines.

```
openssl x509 -in <cert_pem_file_name> -text -noout  
openssl x509 -in <cert_der_file_name> -inform der -text -noout
```

<cert\_pem\_file\_name> specifies the file name that contains the certificate in PEM format.

<cert\_der\_file\_name> specifies the file name that contains the certificate in DER format.

### 3 Test Certificates and keys – Valid test cases

Please note that currently no CRLs are provided. It needs to be confirmed that the value contained in extension `crldistributionPoint` will not lead to a problem with LPA/SM-DP+/SM-DS implementations.

#### 3.1 Certificate Issuer

##### 3.1.1 CI Certificate: definition of data to be signed

Field	Value
version	2
serialNumber	'00 B8 74 F3 AB FA 6C 44 D3'
signature	sha256ECDSA
Issuer	See 'subject'
Validity	12783 days (35 years)
Subject	cn = GSMA Test CI ou = TESTCERT o = RSPTEST c = IT
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey=[CI public key value]
Extension	(Sequence)
subjectKeyIdentifier extension	NIST: 'F5 41 72 BD F9 8A 95 D6 5C BE B8 8A 38 A1 C1 1D 80 0A 85 C3' Brainpool: 'C0 BC 70 BA 36 92 9D 43 B4 67 FF 57 57 05 30 E5 7A B8 FC D8'
keyUsage Extension	Certificate Signing, Off-line CRL Signing, CRL Signing (06)
certificatePolicies Extension	'2.23.146.1.2.1.0' (id-rspRole-ci)
basicConstraints Extension	CA = true
subjectAltName Extension	'2.999.1'



crLDistributionPoints Extension	[1]CRL Distribution Point Distribution Point Name: Full Name: URL=http://ci.test.gsma.com/CRL-A.crl
	[2]CRL Distribution Point Distribution Point Name: Full Name: URL=http://ci.test.gsma.com/CRL-B.crl

**Table 1: CERT.CI.ECDSA**

### 3.1.2 CI Keys and Certificate

Hereafter the generated CI keys and certificates as defined in Annex A.

File name	Description
SK_CI_ECDSA_NIST.pem	NIST P-256 Private Key of the CI
CERT_CI_ECDSA_NIST.der CERT_CI_ECDSA_NIST.pem	Certificate of the CI for its NIST P-256 Public Key in DER and PEM formats
SK_CI_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the CI
CERT_CI_ECDSA_BRP.der CERT_CI_ECDSA_BRP.pem	Certificate of the CI for its Brainpool P256r1 Public Key in DER and PEM formats

**Table 2: CI Keys and Certificates**

### 3.1.3 Input data for generation

The SK.CI.ECDSA and PK.CI.ECDSA are generated using the command lines as described in section 2.2.

The CERT.CI.ECDSA is generated using the command lines described in section 2.3 with the following input data:

<ca\_configuration\_file>: CI-csr.cnf as defined in Annex A.

<serial> set with value defined in section 3.1.1 for serialNumber data field.

<days> set with value defined in section 3.1.1 for validity data field.

## 3.2 eUICC

### 3.2.1 eUICC Certificate: definition of data to be signed

Field	Value
Version	2
serialNumber	'02 00 00 00 00 00 00 00 01'
signature	sha256ECDSA

Issuer	cn = EUM Test o = RSP Test EUM c = DE
Validity	2000000 days
Subject	cn = Test eUICC serialNumber = '89049032123451234512345678901235' (EID) o = RSP Test EUM c = DE
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey=[EUICC public key value] (see section 3.2.2)
<b>Extension (Sequence)</b>	
authorityKeyIdentifier Extension	<Value of CERT.EUM.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1
subjectKeyIdentifier Extension	NIST: A5 24 76 AF 5D 50 AA 37 64 37 CC B1 DA 21 72 EF 45 F4 84 F0Brainpool: C8 A6 4F 34 3B 85 B7 B0 57 8D C5 7F 8F 13 58 6D C8 04 ED 84
keyUsage Extension	Critical digitalSignature ('80')
certificatePolicies Extension	Critical '2.23.146.1.2.1.1' (id-rspRole-euicc)

**Table 3: CERT.EUICC.ECDSA**

NOTE: OpenSSL tool does not allow the generation of Infinite duration certificates. For this reason, the eUICC certificate generated herein, only intended for test purposes, is not aligned with the SGP.14 specification. An eUICC certificate generated with another tool supporting this capability SHALL have the duration set to Infinite.

### 3.2.2 eUICC Keys and Certificate

Here are the generated eUICC keys and certificates as defined in Annex A.

File name	Description
SK_EUICC_ECDSA_NIST.pem	NIST P-256 Private key of the eUICC for creating signatures
PK_EUICC_ECDSA_NIST.pem	NIST P-256 Public Key of the eUICC (part of the CERT_EUICC_ECDSA_NIST.der)
CERT_EUICC_ECDSA_NIST.der	Certificate of the eUICC for its NIST P-256 Public key
SK_EUICC_ECDSA_BRP.pem	Brainpool P256r1 Private key of the eUICC for creating signatures

PK_EUICC_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the eUICC (part of the CERT_EUICC_ECDSA_BRP.der)
CERT_EUICC_ECDSA_BRP.der	Certificate of the eUICC for its Brainpool P256r1 Public key

**Table 4: eUICC Keys and Certificates**

### 3.2.3 Input data for generation

The SK.EUICC.ECDSA and PK.EUICC.ECDSA are generated using the command lines as described in section 2.2.

The CERT.EUICC.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: eUICC-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.3.2 (file containing the CERT.EUM.ECDSA and SK.EUM.ECDSA respectively).

<serial> set with value defined in section 3.2.1 for serialNumber data field.

<days> set with value defined in section 3.2.1 for validity data field.

<cert\_ext\_file\_name>: eUICC-ext.cnf as defined in Annex A.

## 3.3 EUM

### 3.3.1 EUM Certificate: definition of data to be signed

Field	Value
version	2
serialNumber	'12 34 56 78'
signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
validity	12410 days (34 years)
subject	cn = EUM Test o = RSP Test EUM c = DE
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey=[EUM public key value] (see section 3.3.2)
authorityKeyIdentifier Extension	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1

subjectKeyIdentifier Extension	NIST (prime256v1): DD:3D:A2:4D:35:0C:1C:C5:D0:AF:09:65:F4:0E:C3:4C:5E:E4:09:F1 Brainpool (brainpoolP256r1): 6F A1 E5 21 73 63 A8 22 BD ED 98 8A 1A 0D 0F F5 D7 62 0D B7
keyUsage Extension	Critical Certificate Sign ('04')
Certificate Policies	Critical '2.23.146.1.2.1.2' (id-rspRole-eum)
subjectAltName Extension	'2.999.5'
basicConstraints	Critical CA = true pathLenConstraint = 0
crlDistributionPoints Extension	[1]CRL Distribution Point Distribution Point Name: Full Name: URL=http://ci.test.gsma.com/CRL-B.crl
nameConstraints	Critical permittedSubtrees: id-at-organizationName: '2.5.4.10' organization name: "RSP Test EUM"      UTF8String id-at-serialNumber: '2.5.4.5' iin: "89049032"                              PrintableString

**Table 5: CERT.EUM.ECDSA**

### 3.3.2 EUM Keys and Certificate

Hereafter the generated EUM keys and certificates as defined in Annex A.

File name	Description
SK_EUM_ECDSA_NIST.pem	NIST P-256 Private key of the EUM for creating signatures
PK_EUM_ECDSA_NIST.pem	NIST P-256 Public Key of the EUM (part of the CERT_EUM_ECDSA_NIST.der)
CERT_EUM_ECDSA_NIST.der	Certificate of the EUM for its Public NIST P-256 key
SK_EUM_ECDSA_BRP.pem	Brainpool P256r1 Private key of the EUM for creating signatures
PK_EUM_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the EUM (part of the CERT_EUM_ECDSA_BRP.der)
CERT_EUM_ECDSA_BRP.der	Certificate of the EUM for its Public Brainpool P256r1 key

**Table 6: EUM Keys and Certificates**

### 3.3.3 Input data for generation

The SK.EUM.ECDSA and PK.EUM.ECDSA are generated using the command lines as described in section 2.2.

The CERT.EUM.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: EUM-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.3.2 for serialNumber data field.

<days> set with value defined in section 3.3.2 for validity data field.

<cert\_ext\_file\_name>: EUM-ext.cnf as defined in Annex A.

## 3.4 SM-DP+

### 3.4.1 DPauth

#### 3.4.1.1 SM-DP+ n°1 Certificate for Authentication: definition of data to be signed

Field	Value
Version	'2'
serialNumber	'100'
signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3 years)
Subject	o = 'ACME' cn = 'TEST SM-DP+'
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey= corresponding <PK.DPauth.ECDSA value> (see 3.4.1.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1

Extension for subjectKeyIdentifier	NIST: 'BD 5A 82 CC 1A 96 60 21 18 BA 75 60 A1 FF 83 A7 8B 21 0B E5' Brainpool: '79 A4 BD 4D 78 FF 47 34 BC 60 45 CF 91 96 24 4A 1F B8 4B EB'
Extension for keyUsage	Digital Signature ('80')
Extension for certificatePolicies	'2.23.146.1.2.1.4' (id-rspRole-dp-auth)
Extension for subjectAltName	'2.999.10'
Extension for crlDistributionPoints	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 7: CERT.DPauth.ECDSA of SM-DP+ n°1**

### 3.4.1.2 SM-DP+ n°1 Keys and Certificate

Hereafter the generated keys and certificates of SM-DP+ n°1 for Authentication as defined in Annex A.

File name	Description
SK_S_SM_DPauth_ECDSA_NIST.pem	NIST P-256 Private Key of the SM-DP+ n°1 for creating signatures for SM-DP+ authentication
PK_S_SM_DPauth_ECDSA_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DPauth_ECDSA_NIST.der)
CERT_S_SM_DPauth_ECDSA_NIST.der	Certificate of the SM-DP+ n°1 for its Public NIST P-256 key used for SM-DP+ authentication
SK_S_SM_DPauth_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the SM-DP+ n°1 for creating signatures for SM-DP+ authentication
PK_S_SM_DPauth_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DPauth_ECDSA_BRP.der)
CERT_S_SM_DPauth_ECDSA_BRP.der	Certificate of the SM-DP+ n°1 for its Public Brainpool P256r1 key used for SM-DP+ authentication

**Table 8: DPAuth Keys and Certificates of SM-DP+ n°1**

### 3.4.1.3 SM-DP+ n°1: Input data for generation

The SK.DPauth.ECDSA and PK.DPauth.ECDSA of the SM-DP+ n°1 are generated using the command lines as described in section 2.2.

The related CERT.DPauth.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.1.1 for serialNumber data field.

<days> set with value defined in section 3.4.1.1 for validity data field.

<cert\_ext\_file\_name>: DPauth-ext.cnf as defined in Annex A.

### 3.4.1.4 SM-DP+ n°2 Certificate for Authentication: definition of data to be signed

Field	Value
Version	Same as in section 3.4.1.1
serialNumber	'200'
signature	Same as in section 3.4.1.1
Issuer	Same as in section 3.4.1.1
Validity	Same as in section 3.4.1.1
Subject	o = 'ACME' cn = 'TEST SM-DP+2'
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey= corresponding <PK.DPauth.ECDSA value> (see 3.4.1.5)
Extensions	Same as in section 3.4.1.1
Extension for authorityKeyIdentifier	Same as in section 3.4.1.1
Extension for subjectKeyIdentifier	NIST: '95 9E F7 E6 50 C1 BE 21 6A 39 19 74 27 6D 26 B8 A9 35 61 71' Brainpool: 'D7 0E FD 05 7B AC 1F 7C 55 EA 5D 8C 26 BE 16 02 92 84 5B AF'
Extension for keyUsage	Same as in section 3.4.1.1
Extension for certificatePolicies	Same as in section 3.4.1.1
Extension for subjectAltName	'2.999.12'
Extension for crlDistributionPoints	Same as in section 3.4.1.1

**Table 9: CERT.DPauth.ECDSA of SM-DP+ n°2**

### 3.4.1.5 SM-DP+ n°2 Keys and Certificate

Hereafter the generated keys and certificates of SM-DP+ n°2 for Authentication as defined in Annex A.

File name	Description
SK_S_SM_DP2auth_ECDSA_NIST.pem	NIST P-256 Private Key of the SM-DP+ n°2 for creating signatures for SM-DP+ authentication
PK_S_SM_DP2auth_ECDSA_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°2 (part of the CERT_S_SM_DP2auth_ECDSA_NIST.der)
CERT_S_SM_DP2auth_ECDSA_NIST.der	Certificate of the SM-DP+ n°2 for its Public NIST P-256 key used for SM-DP+ authentication
SK_S_SM_DP2auth_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the SM-DP+ n°2 for creating signatures for SM-DP+ authentication
PK_S_SM_DP2auth_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the SM-DP+ n°2 (part of the CERT_S_SM_DP2auth_ECDSA_BRP.der)
CERT_S_SM_DP2auth_ECDSA_BRP.der	Certificate of the SM-DP+ n°2 for its Public Brainpool P256r1 key used for SM-DP+ authentication

**Table 10: DPAuth Keys and Certificates of SM-DP+ n°2**

### 3.4.1.6 SM-DP+ n°2: Input data for generation

The SK.DPauth.ECDSA and PK.DPauth.ECDSA of the SM-DP+ n°2 are generated using the command lines as described in section 2.2.

The related CERT.DPauth.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP2-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.1.4 for serialNumber data field.

<days> set with value defined in section 3.4.1.4 for validity data field.

<cert\_ext\_file\_name>: DPauth2-ext.cnf as defined in Annex A.



### 3.4.2 DPpb

#### 3.4.2.1 SM-DP+ n°1 Certificate for Profile Binding: definition of data to be signed

Field	Value
Version	'2'
serialNumber	'101'
Signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3 years)
Subject	o = 'ACME' cn = 'TEST SM-DP+'
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey= corresponding <PK.DPpb.ECDSA value> (see 3.4.2.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	< Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1
Extension for subjectKeyIdentifier	NIST (prime256v1): 'E6 EA F7 1E E0 FB 94 30 EC CD 1E BB 42 1F 88 14 37 C1 32 63' Brainpool (brainpoolP256r1): 'A8 C6 8D F4 49 EB 71 EC 72 3E AC 13 2E 40 E4 B6 F5 46 44 FE'
Extension for keyUsage	Digital Signature ('80')
Extension for certificatePolicies	'2.23.146.1.2.1.5' (id-rspRole-dp-pb)
Extension for subjectAltName	'2.999.10'
Extension for crlDistributionPoints	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 11: CERT.DPpb.ECDSA of SM-DP+ n°1**

#### 3.4.2.2 SM-DP+ n°1 Keys and Certificate

Hereafter the generated keys and certificates of the SM-DP+ n°1 for Profile Package Binding as defined in Annex A.

File name	Description
SK_S_SM_DPpb_ECDSA_NIST.pem	NIST P-256 Private Key of the SM-DP+ n°1 for creating signatures for Profile Package Binding
PK_S_SM_DPpb_ECDSA_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DPpb_ECDSA_NIST.der)
CERT_S_SM_DPpb_ECDSA_NIST.der	Certificate of the SM-DP+ n°1 for its Public NIST P-256 key used for Profile Package Binding
SK_S_SM_DPpb_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the SM-DP+ n°1 for creating signatures for Profile Package Binding
PK_S_SM_DPpb_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DPpb_ECDSA_BRP.der)
CERT_S_SM_DPpb_ECDSA_BRP.der	Certificate of the SM-DP+ n°1 for its Public Brainpool P256r1 key used for Profile Package Binding

**Table 12: DPpb Keys and Certificates of SM-DP+ n°1**

### 3.4.2.3 SM-DP+ n°1: Input data for generation

The SK.DPpb.ECDSA and PK.DPpb.ECDSA of the SM-DP+ n°1 are generated using the command lines as described in section 2.2.

The related CERT.DPpb.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.2.1 for serialNumber data field.

<days> set with value defined in section 3.4.2.1 for validity data field.

<cert\_ext\_file\_name>: DPpb-ext.cnf as defined in Annex A.

### 3.4.2.4 SM-DP+ n°2 Certificate for Profile Binding: definition of data to be signed

Field	Value
Version	Same as in section 3.4.2.1
serialNumber	'201'
Signature	Same as in section 3.4.2.1
Issuer	Same as in section 3.4.2.1
Validity	Same as in section 3.4.2.1
Subject	o = 'ACME' cn = 'TEST SM-DP+2'

subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey= corresponding <PK.DPpb.ECDSA value> (see 3.4.2.5)
Extensions	Same as in section 3.4.2.1
Extension for authorityKeyIdentifier	Same as in section 3.4.2.1
Extension for subjectKeyIdentifier	NIST (prime256v1): '20 A3 A8 30 E9 2E E7 A4 68 C5 EB 27 BA 8D F1 84 59 AD FD D7' Brainpool (brainpoolP256r1): '31 03 8A 55 B6 BE CF 6C EA 59 DE 2F DA 14 F4 32 7F B8 B6 A9'
Extension for keyUsage	Same as in section 3.4.2.1
Extension for certificatePolicies	Same as in section 3.4.2.1
Extension for subjectAltName	'2.999.12'
Extension for crlDistributionPoints	Same as in section 3.4.2.1

**Table 13: CERT.DPpb.ECDSA of SM-DP+ n°2**

### 3.4.2.5 SM-DP+ n°2 Keys and Certificate

Hereafter the generated keys and certificates of the SM-DP+ n°2 for Profile Package Binding as defined in Annex A.

File name	Description
SK_S_SM_DP2pb_ECDSA_NIST.pem	NIST P-256 Private Key of the SM-DP+ n°2 for creating signatures for Profile Package Binding
PK_S_SM_DP2pb_ECDSA_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°2 (part of the CERT_S_SM_DP2pb_ECDSA_NIST.der)
CERT_S_SM_DP2pb_ECDSA_NIST.der	Certificate of the SM-DP+ n°2 for its Public NIST P-256 key used for Profile Package Binding
SK_S_SM_DP2pb_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the SM-DP+ n°2 for creating signatures for Profile Package Binding
PK_S_SM_DP2pb_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the SM-DP+ n°2 (part of the CERT_S_SM_DP2pb_ECDSA_BRP.der)
CERT_S_SM_DP2pb_ECDSA_BRP.der	Certificate of the SM-DP+ n°2 for its Public Brainpool P256r1 key used for Profile Package Binding

**Table 14: DPpb Keys and Certificates of SM-DP+ n°2**

### 3.4.2.6 SM-DP+ n°2: Input data for generation

The SK.DPpb.ECDSA and PK.DPpb.ECDSA of the SM-DP+ n°2 are generated using the command lines as described in section 2.2.

The related CERT.DPpb.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP2-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.2.4 for serialNumber data field.

<days> set with value defined in section 3.4.2.4 for validity data field.

<cert\_ext\_file\_name>: DPpb2-ext.cnf as defined in Annex A.

### 3.4.3 TLS

#### 3.4.3.1 SM-DP+ n°1 TLS Certificate: definition of data to be signed

Field	Value
Version	2
serialNumber	'9'
signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
validity	1095 days (3years)
subject	o = 'ACME' cn = 'testsmppplus1.gsma.com'
subjectPublicKeyInfo	algorithm.algorithm= '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (Prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey = < PK.DP.TLS value> (see 3.4.3.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1
Extension for subjectKeyIdentifier	NIST (prime256v1): '27 FE F1 F2 29 18 7E C7 83 ED F6 E0 29 64 A4 51 8D 57 D4 A9' Brainpool (brainpoolP256r1):

		'3D 33 09 83 F3 9F CC 5B D2 E4 AD 68 A6 19 A7 47 48 AE 8B 9D'
Extension for keyUsage		Critical digitalSignature ('80')
Extension for certificatePolicies	for	'2.23.146.1.2.1.3' (id-rspRole-dp-tls)
Extension for extendedKeyUsage		Critical TLS Web Server Authentication TLS Client Authentication
Extension for subjectAltName	for	DNS= testsmppplus1.gsma.com SM-DP+OID = '2.999.10'
Extension for crlDistributionPoints		<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 15: CERT.DP.TLS for SM-DP+ n°1**

### 3.4.3.2 SM-DP+ n°1 TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ n°1 for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DP_TLS_NIST.der)
CERT_S_SM_DP_TLS_NIST.der	Certificate of the SM-DP+ n°1 based on NIST P-256 for securing TLS
SK_S_SM_DP_TLS_BRP.pem	Brainpool P256r1 Private key of the SM-DP+ n°1 for securing TLS connection
PK_S_SM_DP_TLS_BRP.pem	Brainpool P256r1 Public Key of the SM-DP+ n°1 (part of the CERT_S_SM_DP_TLS_BRP.der)
CERT_S_SM_DP_TLS_BRP.der	Certificate of the SM-DP+ n°1 based on Brainpool P256r1 for securing TLS

**Table 16: DP\_TLS Keys and Certificates of SM-DP+ n°1**

### 3.4.3.3 Input data for generation

The SK.DP.TLS and PK.DP.TLS are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_SM\_DP\_TLS.ext.cnf as defined in Annex A.

### 3.4.3.4 SM-DP+ n°2 TLS Certificate: definition of data to be signed

Field	Value
Version	2
serialNumber	'99'
Signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3years)
Subject	o = 'ACME' cn = 'testsmdpplus2.gsma.com'
subjectPublicKeyInfo	algorithm.algorithm= '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (Prime256v1) subjectPublicKey = < PK.DP.TLS value> (see Section 3.4.3.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1
Extension for subjectKeyIdentifier	NIST (prime256v1): '9f 5f 6b 0c e7 00 32 25 2d ce 10 d3 49 a6 55 18 1b 85 3e ce'
Extension for keyUsage	Critical digitalSignature ('80')
Extension certificatePolicies for	'2.23.146.1.2.1.3' (id-rspRole-dp-tls)
Extension for extendedKeyUsage	Critical TLS Web Server Authentication TLS Client Authentication
Extension subjectAltName for	DNS= testsmdpplus2.gsma.com SM-DP+OID = '2.999.12'
Extension for crlDistributionPoints	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 17: CERT.DP2.TLS**

### 3.4.3.5 SM-DP+ n°2 TLS Keys and Certificate

Hereafter the generated SM-DP+ n°2 keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP2_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ n°2 for securing TLS connection
PK_S_SM_DP2_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ n°2 (part of the CERT_S_SM_DP2_TLS_NIST.der)
CERT_S_SM_DP2_TLS_INV_CERT_PO L.der	CERT.DP.TLS certificate of the S_SM-DP+ n°2, based on NIST P-256

**Table 18: DP\_TLS Keys and Certificates of SM-DP+ n°2**

### 3.4.3.6 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP2\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP2\_TLS.ext.cnf as defined in Annex A.

## 3.5 SM-DS

### 3.5.1 DSauth

#### 3.5.1.1 SM-DS Certificate for Authentication: definition of data to be signed

Field	Value
Version	2
serialNumber	'7495'
Signature	algorithm = '1.2.840.10045.4.3.2' (sha256ECDSA)
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3 years)

Subject	o = 'ACME' cn = 'TEST SM-DS'
subjectPublicKeyInfo	algorithm.algorithm= '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (Prime256v1) or '1.3.36.3.3.2.8.1.1.7' (brainpoolP256r1) subjectPublicKey = < PK.Dsauth.ECDSA value> (see 3.5.1.2)
Extensions	(Sequence)
Extension for Authority Key Identifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for prime256v1 or brainpoolP256r1
Extension for subjectKeyIdentifier	NIST (prime256v1): 'C1 F4 06 4B 3B 25 8A FB 61 38 8B 3F F2 EE 6A 61 E2 C4 4D 72' Brainpool (brainpoolP256r1): 'F0 5F 0B 54 AE E8 AE 01 08 F0 1D EF 54 8E D9 85 97 14 DD 48'
KeyUsage Extension	Digital Signature ('80')
Extension for Certificate Policy	'2.23.146.1.2.1.7' (id-rspRole-ds-auth)
Extension for subjectAltName	SM-DS OID = '2.999.15'
Extension for CRL Distribution Points	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 19: CERT.DSauth.ECDSA**

### 3.5.1.2 SM-DS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for Authentication as defined in Annex A.

File name	Description
SK_S_SM_DSauth_ECDSA_NIST.pem	NIST P-256 Private Key of the SM-DS for creating signatures for SM-DS authentication
PK_S_SM_DSauth_ECDSA_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DSauth_ECDSA_NIST.der)
CERT_S_SM_DSauth_ECDSA_NIST.der	Certificate of the SM-DS for its Public NIST P-256 key used for SM-DS authentication
SK_S_SM_DSauth_ECDSA_BRP.pem	Brainpool P256r1 Private Key of the SM-DS for creating signatures for SM-DS authentication
PK_S_SM_DSauth_ECDSA_BRP.pem	Brainpool P256r1 Public Key of the SM-DS (part of the CERT_S_SM_DSauth_ECDSA_BRP.der)
CERT_S_SM_DSauth_ECDSA_BRP.der	Certificate of the SM-DS for its Public Brainpool P256r1 key used for SM-DS authentication

**Table 20: DSauth Keys and Certificates**



### 3.5.1.3 Input data for generation

The SK.DSauth.ECDSA and PK.DSauth.ECDSA are generated using the command lines as described in section 2.2.

The CERT.DSauth.ECDSA is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DSauth-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.5.1.1 for serialNumber data field.

<days> set with value defined in section 3.5.1.1 for validity data field.

<cert\_ext\_file\_name>: DSauth-ext.cnf as defined in Annex A.

## 3.5.2 TLS

### 3.5.2.1 SM-DS n°1 TLS Certificate: definition of data to be signed

Field	Value
Version	2
serialNumber	'1223334444'
Signature	SHA256ECDSA
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3years)
Subject	o = 'RSPTEST' cn = 'testrootsmds.gsma.com'
subjectPublicKeyInfo	algorithm.algorithm= '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (Prime256v1) or '1.3.36.3.3.2.8.1.1.7' (BrainpoolP256r1) subjectPublicKey = < PK.DS.TLS value>
Extensions	(Sequence)
Extension for Authority Key Identifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for Prime256v1 or BrainpoolP256r1
Extension for Subject Key Identifier	NIST: 'A0 36 C1 62 75 35 1E C7 B0 15 53 A1 3F 83 E2 8D 44 00 BD 0A' Brainpool: '73 99 CA C7 B1 5F AB 2F F9 33 CF 2D 22 15 E4 84 4A DE F8 05'
Extension for Key usage	Critical digitalSignature ('80')
Extension for Certificate Policies	'2.23.146.1.2.1.6' (id-rspRole-ds-tls)

Extension for Extended Key usage	Critical TLS Web Server Authentication , TLS Web Client Authentication
Extension for subjectAltName	DNS= testrootsmds.gsma.com SM-DS OID = '2.999.15'
Extension for CRL Distribution Points	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 21: CERT.DS.TLS for SM-DS n°1**

### 3.5.2.2 SM-DS n°1 TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS n°1 for securing TLS connection
PK_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS n°1 (part of the CERT_S_SM_DS_TLS_NIST.der)
CERT_SM_DS_TLS_NIST.der	Certificate of the SM-DS n°1 based on NIST P-256 for securing TLS
SK_SM_DS_TLS_BRP.pem	Brainpool P256r1 Private key of the SM-DS n°1 for securing TLS connection
PK_SM_DS_TLS_BRP.pem	Brainpool P256r1 Public Key of the SM-DS n°1 (part of the CERT_S_SM_DP_TLS_BRP.der)
CERT_SM_DS_TLS_BRP.der	Certificate of the SM-DS n°1 based on Brainpool P256r1 for securing TLS

**Table 22: DS\_TLS Keys and Certificates for SM-DS n°1**

### 3.5.2.3 Input data for generation

The SK.DS.TLS and PK.DS.TLS are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.5.2.1 for `serialNumber` data field.

<days> set with value defined in section 3.5.2.1 for `validity` data field.

<cert\_ext\_file\_name>: CERT\_SM\_DS\_TLS.ext.cnf as defined in Annex A.

### 3.5.2.4 SM-DS n°2 TLS Certificate: definition of data to be signed

Field	Value
Version	2
serialNumber	'122333444455555'
Signature	SHA256ECDSA
Issuer	<Value of CERT.CI.ECDSA."subject" field>
Validity	1095 days (3years)
Subject	o = 'RSPTEST' cn = 'testsmds1.gsma.com'
subjectPublicKeyInfo	algorithm.algorithm= '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.7' (Prime256v1) subjectPublicKey = < PK.DS.TLS value> (see Section 3.5.2.2)
Extensions	(Sequence)
Extension for Authority Key Identifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for Prime256v1
Extension for Subject Key Identifier	NIST: '53 82 04 27 91 71 ed 3d 0a 79 c0 ad 61 a5 35 31 2c 86 48 6c'
Extension for Key usage	Critical digitalSignature ('80')
Extension for Certificate Policies	'2.23.146.1.2.1.6' (id-rspRole-ds-tls)
Extension for Extended Key usage	Critical TLS Web Server Authentication , TLS Web Client Authentication
Extension for subjectAltName	DNS= testsmds1.gsma.com SM-DS OID = '2.999.15.2'
Extension for CRL Distribution Points	<Value of CERT.CI.ECDSA."crlDistributionPoints" field>

**Table 23: CERT.DS2.TLS**

### 3.5.2.5 SM-DS n°2 TLS Keys and Certificate

Hereafter the generated SM-DS n°2 keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS2_TLS_NIST.pem	NIST P-256 Private key of the SM-DS n°2 for securing TLS connection
PK_S_SM_DS2_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS n°2 (part of the CERT_S_SM_DS2_TLS_NIST.der)
CERT_S_SM_DS2_TLS_NIST.der	CERT.DS.TLS certificate of the S_SM-DS n°2, based on NIST P-256

**Table 24: DS\_TLS Keys and Certificates for SM-DS n°2**

### 3.5.2.6 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS2\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS2\_TLS.ext.cnf as defined in Annex A.

## 4 Test Certificates and keys – Invalid test cases

The sections below describe

- The data structure and content of the certificates used for running the invalid test cases in SGP.23;
- how such certificates are derived: both the toolchain and the input data are described.

### 4.1 eUICC

Void

### 4.2 SM-DP+

#### 4.2.1 DPauth

##### 4.2.1.1 DPAuth – Invalid Signature

###### 4.2.1.1.1 SM-DP+ Certificate for Authentication: definition of data to be signed

All the data to be signed are the same as the ones defined in 3.4.1.1.

###### 4.2.1.1.2 SM-DP+ Certificate

Hereafter the SM-DP+ certificates for Authentication with invalid signature as defined in Annex A.

File name	Description
CERT_S_SM_DPauth_INV_SIGN_NIST.der	Certificate of the SM-DP+ with invalid signature for its Public NIST P-256 key used for SM-DP+ authentication
CERT_S_SM_DPauth_INV_SIGN_BRP.der	Certificate of the SM-DP+ with invalid signature for its Public Brainpool P256r1 key used for SM-DP+ authentication

**Table 25: DPauth\_INV\_SIGN Certificates**

**4.2.1.1.3 Input data for generation**

Few bytes of the generated signatures contained in the DER files have been manually changed as follow:

- NIST signature: 10 bytes are replaced by random values
- Brainpool signature: 8 bytes are replaced by random values

**4.2.1.2 DPAuth – Invalid Curve**

The Elliptic Curve NIST P-192 is chosen for triggering the Authenticate and Download Error Code `unsupportedCurve(3)` as defined in SGP.22 [1].

**4.2.1.2.1 SM-DP+ Certificate for Authentication: definition of data to be signed**

Field	Value
Version	See section 3.4.1.1
serialNumber	900
Signature	See section 3.4.1.1
Issuer	See section 3.4.1.1
Validity	See section 3.4.1.1
Subject	See section 3.4.1.1
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.1' (prime192v1) subjectPublicKey= <PK.DPauth.ECDSA value> (see 4.3.1.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	See section 3.4.1.1
Extension for subjectKeyIdentifier	NIST (prime192v1): '9B 3A 9E 3D 46 E7 8F 19 27 29 A8 EF 4A 46 20 6A 2C CA B2 D2'
Extension for keyUsage	See section 3.4.1.1
Extension for certificatePolicies	See section 3.4.1.1
Extension for subjectAltName	See section 3.4.1.1
Extension for crlDistributionPoints	See section 3.4.1.1

**Table 26: CERT.DPauth.ECDSA with Invalid Curve**

#### 4.2.1.2.2 SM-DP+ Keys and Certificate

Hereafter the SM-DP+ certificates and keys for Authentication with invalid curve as defined in Annex A.

File name	Description
SK_S_SM_DPauth_ECDSA_NIST192.pem	NIST P-192 Private Key of the SM-DP+ for creating signatures for SM-DP+ authentication
PK_S_SM_DPauth_ECDSA_NIST192.pem	NIST P-192 Public Key of the SM-DP+ (part of the CERT_S_SM_DPauth_INV_CURVE_NIST192.der)
CERT_S_SM_DPauth_INV_CURVE_NIST192.der	Certificate of the SM-DP+ for its Public NIST P-192 key used for SM-DP+ authentication

**Table 27: DPauth Keys and Certificates with invalid curve**

#### 4.2.1.2.3 Input data for generation

Command lines for the generation of the SK.DPauth.ECDSA and the corresponding PK.DPauth.ECDSA for NIST P-192 curve:

```
openssl ecparam -name prime192v1 -genkey -out SK_S_SM_DPauth_ECDSA_NIST192.pem
openssl ec -in SK_S_SM_DPauth_ECDSA_NIST192.pem -pubout -out
    PK_S_SM_DPauth_ECDSA_NIST192.pem
```

The CERT.DPauth.ECDSA based on NIST P-192 curve is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 4.3.1.1 for serialNumber data field.

<days> set with value defined in section 4.3.1.1 for validity data field.

<cert\_ext\_file\_name>: DPauth-ext.cnf as defined in Annex A.

### 4.2.2 DPpb

#### 4.2.2.1 DPpb – Invalid Signature

##### 4.2.2.1.1 SM-DP+ Certificate for Profile Binding: definition of data to be signed

All the data to be signed are the same as the ones defined in 3.4.2.1.

##### 4.2.2.1.2 SM-DP+ Certificate

Hereafter the SM-DP+ certificates for Profile Package Binding with invalid signature as defined in Annex A.

File name	Description
CERT_S_SM_DPpb_INV_SIGN_NIST.der	Certificate of the SM-DP+ with invalid signature for its Public NIST P-256 key used for Profile Package Binding
CERT_S_SM_DPpb_INV_SIGN_BRP.der	Certificate of the SM-DP+ with invalid signature for its Public Brainpool P256r1 key used for Profile Package Binding

**Table 28: DPpb Certificates with invalid signature**

#### 4.2.2.1.3 Input data for generation

Few bytes of the generated signatures contained in the DER files have been manually changed as follow:

- NIST signature: 10 bytes are replaced by random values
- Brainpool signature: 8 bytes are replaced by random values

#### 4.2.2.2 DPpb – Invalid Curve

##### 4.2.2.2.1 SM-DP+ Certificate for Profile Binding: definition of data to be signed

Field	Value
Version	See section 3.4.2.1
serialNumber	901
Signature	See section 3.4.2.1
Issuer	See section 3.4.2.1
Validity	See section 3.4.2.1
Subject	See section 3.4.2.1
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.1' (prime192v1) subjectPublicKey= <PK.DPauth.ECDSA value> (see 4.3.2.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	See section 3.4.2.1
Extension for subjectKeyIdentifier	NIST (prime192v1): B5:49:B2:F1:2B:FB:70:B8:BE:10:3E:A5:6E:D9:D8:21:1E:62:AB: 89
Extension for keyUsage	See section 3.4.2.1
Extension for certificatePolicies	See section 3.4.2.1
Extension for subjectAltName	See section 3.4.2.1

Extension for crlDistributionPoints	See section 3.4.2.1
--	---------------------

**Table 29: CERT.DPpb.ECDSA with invalid curve**

#### 4.2.2.2.2 SM-DP+ Keys and Certificate

Hereafter the SM-DP+ certificates and keys for Profile Binding with invalid curve as defined in Annex A.

File name	Description
SK_S_SM_DPpb_ECDSA_NIST192.pem	NIST P-192 Private Key of the SM-DP+ for creating signatures for Profile Package Binding
PK_S_SM_DPpb_ECDSA_NIST192.pem	NIST P-192 Public Key of the SM-DP+ (part of the CERT_S_SM_DPpb_INV_CURVE_NIST192.der)
CERT_S_SM_DPpb_INV_CURVE_NIST192.der	Certificate of the SM-DP+ for its Public NIST P-192 key used for Profile Package Binding

**Table 30: DPpb Keys and Certificates with invalid curve**

#### 4.2.2.2.3 Input data for generation

Command lines for the generation of the SK.DPpb.ECDSA and the corresponding PK.DPpb.ECDSA for NIST P-192 curve:

```
openssl ecparam -name prime192v1 -genkey -out SK_S_SM_DPpb_ECDSA_NIST192.pem
openssl ec -in SK_S_SM_DPpb_ECDSA_NIST192.pem -pubout -out
    PK_S_SM_DPpb_ECDSA_NIST192.pem
```

The CERT.DPpb.ECDSA based on NIST P-192 curve is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DP-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 4.3.2.1 for serialNumber data field.

<days> set with value defined in section 4.3.2.1 for validity data field.

<cert\_ext\_file\_name>: DPpb-ext.cnf as defined in Annex A.

### 4.2.3 TLS

#### 4.2.3.1 TLS – Invalid Signature

##### 4.2.3.1.1 SM-DP+ TLS Certificate: Definition of data to be signed

All the data to be signed are the same as the ones defined in 3.4.3.1.



#### 4.2.3.1.2 SM-DP+ Certificate

Hereafter the SM-DP+ TLS certificates with invalid signature as defined in Annex A.

File name	Description
CERT_S_SM_DP_TLS_NIST.der	Certificate of the SM-DP+ with invalid signature for its Public NIST P-256 key
CERT_S_SM_DP_TLS_BRP.der	Certificate of the SM-DP+ with invalid signature for its Public Brainpool P256r1 key

**Table 31: DP\_TLS Certificates with invalid signature**

#### 4.2.3.1.3 Input data for generation

Few bytes of the generated signatures contained in the DER files have been manually changed as follow:

- Least significant byte of CERT\_S\_SM\_DP\_TLS\_NIST.der signature increased by 1
- Least significant byte of CERT\_S\_SM\_DP\_TLS\_BRP.der signature increased by 1

#### 4.2.3.2 TLS – Invalid Curve

##### 4.2.3.2.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.4.3
serialNumber	Same as in section 3.4.3
Signature	Same as in section 3.4.3
Issuer	Same as in section 3.4.3
Validity	Same as in section 3.4.3
Subject	Same as in section 3.4.3
subjectPublicKeyInfo	algorithm.algorithm = '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters = '1.3.132.0.34' (secp384r1) subjectPublicKey = < PK.DP.TLS value> (see 3.4.3.2)
Extensions	Same as in section 3.4.3
Extension for authorityKeyIdentifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for secp384r1
Extension for subjectKeyIdentifier	NIST (secp384r1): '0a 8f 46 e4 bd df e3 3f b0 1c 4b 0c c6 2f 14 0b 3b 11 91 c6'
Extension for keyUsage	Same as in section 3.4.3
Extension for certificatePolicies	Same as in section 3.4.3
Extension for extendedKeyUsage	Same as in section 3.4.3

Extension subjectAltName	for	Same as in section 3.4.3
Extension for crlDistributionPoints		Same as in section 3.4.3

**Table 32: CERT\_S\_SM\_DP\_TLS\_INV\_CURVE**

#### 4.2.3.2.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_CERT_CI_S_SM_DP_NIST_P384.pem	NIST P-384 Private CI key of the SM-DP+ for securing TLS connection with
PK_CERT_CI_S_SM_DP_NIST_P384.pem	NIST P-384 Public CI Key of the SM-DP+
SK_CERT_S_SM_DP_TLS_INV_CURVE.pem	NIST P-384 Private key of the SM-DP+ for securing TLS connection with
PK_CERT_S_SM_DP_TLS_INV_CURVE.pem	NIST P-384 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_INV_CURVE.der)
CERT_S_SM_DP_TLS_INV_CURVE.der	CERT.DP.TLS certificate of the S_SM-DP+, based on NIST P-384 curve

**Table 33: DP\_TLS Keys and Certificates with invalid curve**

#### 4.2.3.2.3 Input data for generation

The Private Key is generated using the following command line:

```
openssl ecparam -name secp384r1 -genkey -out <sk_file_name>
```

The Public Key is generated as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP\_TLS.ext.cnf as defined in Annex A.

### 4.2.3.3 TLS – Invalid Certificate Policy

#### 4.2.3.3.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.4.3
serialNumber	Same as in section 3.4.3
Signature	Same as in section 3.4.3
Issuer	Same as in section 3.4.3
Validity	Same as in section 3.4.3
Subject	Same as in section 3.4.3
subjectPublicKeyInfo	Same as in section 3.4.3
Extensions	Same as in section 3.4.3
Extension for authorityKeyIdentifier	Same as in section 3.4.3
Extension for subjectKeyIdentifier	Same as in section 3.4.3
Extension for keyUsage	Same as in section 3.4.3
Extension for certificatePolicies	'2.23.146.1.2.1.4' (id-rspRole-dp-auth)
Extension for extendedKeyUsage	Same as in section 3.4.3
Extension for subjectAltName	Same as in section 3.4.3
Extension for crlDistributionPoints	Same as in section 3.4.3

**Table 34: CERT\_S\_SM\_DP\_TLS\_INV\_CERT\_POL**

#### 4.2.3.3.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_NIST.der)
CERT_S_SM_DP_TLS_INV_CERT_POL.der	CERT.DP.TLS certificate of the S_SM-DP+ with invalid 'Certificate Policies' extension (OID set to 'id-rspRole-dp-auth'), formatted as X.509 certificate.

**Table 35: DS\_TLS Keys and Certificate with invalid certificatePolicies extension**

#### 4.2.3.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP\_TLS\_INV\_CERT\_POL.ext.cnf as defined in Annex A.

#### 4.2.3.4 TLS – Missing Critical Extension

##### 4.2.3.4.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.4.3
serialNumber	Same as in section 3.4.3
Signature	Same as in section 3.4.3
Issuer	Same as in section 3.4.3
Validity	Same as in section 3.4.3
Subject	Same as in section 3.4.3
subjectPublicKeyInfo	Same as in section 3.4.3
Extensions	Same as in section 3.4.3
Extension for authorityKeyIdentifier	Same as in section 3.4.3
Extension for subjectKeyIdentifier	Same as in section 3.4.3
Extension for keyUsage	Same as in section 3.4.3
Extension for certificatePolicies	Same as in section 3.4.3
Extension for extendedKeyUsage	Absent
Extension for subjectAltName	Same as in section 3.4.3
Extension for crlDistributionPoints	Same as in section 3.4.3

**Table 36: CERT\_S\_SM\_DP\_TLS\_INV\_CRITICAL\_EXT**

#### 4.2.3.4.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_NIST.der)
CERT_S_SM_DP_TLS_INV_CRITICAL_EXT.der	CERT.DP.TLS certificate of the S_SM-DP+ with one of the critical extensions not present, formatted as X.509 certificate.

**Table 37: DP\_TLS Keys and Certificates with critical extension not present**

#### 4.2.3.4.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP\_TLS\_INV\_CRITICAL\_EXT.ext.cnf as defined in Annex A.

#### 4.2.3.5 TLS – Invalid Extended Key Usage

##### 4.2.3.5.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.4.3
serialNumber	Same as in section 3.4.3
Signature	Same as in section 3.4.3
Issuer	Same as in section 3.4.3
Validity	Same as in section 3.4.3
Subject	Same as in section 3.4.3
subjectPublicKeyInfo	Same as in section 3.4.3

Extensions	Same as in section 3.4.3
Extension for authorityKeyIdentifier	Same as in section 3.4.3
Extension for subjectKeyIdentifier	Same as in section 3.4.3
Extension for keyUsage	Same as in section 3.4.3
Extension for certificatePolicies	Same as in section 3.4.3
Extension for extendedKeyUsage	Critical TLS Client Authentication
Extension for subjectAltName	Same as in section 3.4.3
Extension for crlDistributionPoints	Same as in section 3.4.3

**Table 38: CERT\_S\_SM\_DP\_TLS\_INV\_EXT\_KEY\_USAGE**

#### 4.2.3.5.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_NIST.der)
CERT_S_SM_DP_TLS_INV_EXT_KEY_USAGE.der	CERT.DP.TLS certificate of the S_SM-DP+ with invalid 'extended key usage' extension (not set to 'id-kp-serverAuth'), formatted as X.509 certificate.

#### 4.2.3.5.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP\_TLS\_INV\_EXT\_KEY\_USAGE.ext.cnf as defined in Annex A.

### 4.2.3.6 TLS – Invalid Key Usage

#### 4.2.3.6.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.4.3
serialNumber	Same as in section 3.4.3
Signature	Same as in section 3.4.3
Issuer	Same as in section 3.4.3
Validity	Same as in section 3.4.3
Subject	Same as in section 3.4.3
subjectPublicKeyInfo	Same as in section 3.4.3
Extensions	Same as in section 3.4.3
Extension for authorityKeyIdentifier	Same as in section 3.4.3
Extension for subjectKeyIdentifier	Same as in section 3.4.3
Extension for keyUsage	Critical 'keyAgreement' ('08')
Extension for certificatePolicies	Same as in section 3.4.3
Extension for extendedKeyUsage	Same as in section 3.4.3
Extension for subjectAltName	Same as in section 3.4.3
Extension for crlDistributionPoints	Same as in section 3.4.3

**Table 39: CERT\_S\_SM\_DP\_TLS\_INV\_EXT\_KEY\_USAGE**

#### 4.2.3.6.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_NIST.der)

CERT_S_SM_DP_TLS_INV_KEY_USAG E.der	CERT.DP.TLS certificate of the S_SM-DP+ with invalid 'key usage' extension (not set to 'digitalSignature'), formatted as X.509 certificate.
--	---

**Table 40: DP TLS Keys and Certificates with invalid 'key usage' extension**

#### 4.2.3.6.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DP\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.Cl.ECDSA and SK.Cl.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DP\_TLS\_INV\_KEY\_USAGE.ext.cnf as defined in Annex A.

#### 4.2.3.7 TLS – Expired Certificate

##### 4.2.3.7.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.4.3.1
serialNumber	Same as in section 3.4.3.1
signature	Same as in section 3.4.3.1
issuer	Same as in section 3.4.3.1
validity	expired on 1st Jul 2017
subject	Same as in section 3.4.3.1
subjectPublicKeyInfo	Same as in section 3.4.3.1
Extensions	Same as in section 3.4.3.1
Extension for authorityKeyIdentifier	Same as in section 3.4.3.1
Extension for subjectKeyIdentifier	Same as in section 3.4.3.1
Extension for keyUsage	Same as in section 3.4.3.1
Extension for certificatePolicies	Same as in section 3.4.3.1



Extension for extendedKeyUsage	Same as in section 3.4.3.1
Extension for subjectAltName	Same as in section 3.4.3.1
Extension for crlDistributionPoints	Same as in section 3.4.3.1

**Table 41: CERT\_S\_SM\_DP\_TLS\_EXPIRED**

#### 4.2.3.7.2 SM-DP+ TLS Keys and Certificate

Hereafter the generated SM-DP+ keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DP_TLS_NIST.pem	NIST P-256 Private key of the SM-DP+ for securing TLS connection
PK_S_SM_DP_TLS_NIST.pem	NIST P-256 Public Key of the SM-DP+ (part of the CERT_S_SM_DP_TLS_NIST.der)
CERT_S_SM_DP_TLS_EXPIRED.der	Expired CERT.DP.TLS certificate of the S_SM-DP+ with a valid signature, correctly formatted as X.509 certificate.

**Table 42: DP TLS Keys and Certificates with invalid curve**

#### 4.2.3.7.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following changes:

```
openssl ca -batch -config <config_file> -in <csr_file_name> -extensions
<ext_section_name> -cert <ca_cert_file_name> -keyfile <ca_sk_file_name> -notext -
out <cert_pem_file_name> -startdate <validity_start_date> -enddate
<validity_end_date>
```

Preconditions:

- Following entries are present in the indicated <config\_file> under the default CA section:

```
...
database = $ENV::OPENSSL_HOME/indexTlsCert.txt
serial   = $ENV::OPENSSL_HOME/serialTlsCert
...
```

- Following files are present in OpenSSL home folder and are empty:
  - indexTlsCert.txt

- indexTlsCert.txt.attr

- The text file 'serialTlsCert' is present in OpenSSL home folder and contains the desired serial number as hex string.
- Following extension to be referenced by <ext\_section\_name> sections are present in the indicated <config\_file> for SM-DP+ certificate:

```
[ extensions_CERT_S_SM_DP_TLS ]
```

```
keyUsage = critical, digitalSignature
```

```
extendedKeyUsage = critical, serverAuth, clientAuth
```

```
certificatePolicies = 2.23.146.1.2.1.3
```

```
subjectKeyIdentifier = hash
```

```
authorityKeyIdentifier = keyid:always,issuer
```

```
subjectAltName = DNS:testsmdpplus1.gsma.com, RID:2.999.10
```

```
    crlDistributionPoints=URI:http://ci.test.gsma.com/CRL-A.crl,
```

```
URI:http://ci.test.gsma.com/CRL-B.crl
```

- <validity\_start\_date> and <validity\_end\_date> are formatted YYMMDDHHMMSSZ, e.g. '170301154500Z' for 'Mar 1 15:45:00 2017 GMT'.

### 4.3 SM-DS: Invalid signature

#### 4.3.1 DSauth

##### 4.3.1.1 DSauth – Invalid Signature

###### 4.3.1.1.1 SM-DS Certificate for Authentication: definition of data to be signed

All the data to be signed are the same as the ones defined in 3.5.1.1.

###### 4.3.1.1.2 SM-DS Certificate

Hereafter the SM-DS certificates for Authentication with invalid signature as defined in Annex A.

File name	Description
CERT_S_SM_DSauth_INV_SIGN_NIST.der	Certificate of the SM-DS with invalid signature for its Public NIST P-256 key used for SM-DP+ authentication
CERT_S_SM_DSauth_INV_SIGN_BRP.der	Certificate of the SM-DS with invalid signature for its Public Brainpool P256r1 key used for SM-DP+ authentication

**Table 43: DS TLS Certificates with invalid signature**

###### 4.3.1.1.3 Input data for generation

Few bytes of the generated signatures contained in the DER files have been manually changed as follow:

- NIST signature: 10 bytes are replaced by random values
- Brainpool signature: 8 bytes are replaced by random values

#### 4.3.1.2 DSauth - Invalid curve

The Elliptic Curve NIST P-192 is chosen for triggering the Authenticate Error Code `unsupportedCurve(3)` as defined in SGP.22 [1].

##### 4.3.1.2.1 SM-DS Certificate for Authentication: definition of data to be signed

Field	Value
Version	See section 3.5.1.1
serialNumber	903
Signature	See section 3.5.1.1
Issuer	See section 3.5.1.1
Validity	See section 3.5.1.1
Subject	See section 3.5.1.1
subjectPublicKeyInfo	algorithm.algorithm='1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters= '1.2.840.10045.3.1.1' (prime192v1) subjectPublicKey= <PK.DPauth.ECDSA value> (see 4.4.1.2)
Extensions	(Sequence)
Extension for authorityKeyIdentifier	See section 3.5.1.1
Extension for subjectKeyIdentifier	NIST (prime192v1): 61:20:11:BC:54:84:9B:EE:AF:59:79:49:4E:FC:56:2F:FB:3E:0D:7 2
Extension for keyUsage	See section 3.5.1.1
Extension for certificatePolicies	See section 3.5.1.1
Extension for subjectAltName	See section 3.5.1.1
Extension for crlDistributionPoints	See section 3.5.1.1

**Table 44: CERT.DSauth.ECDSA with Invalid Curve**

##### 4.3.1.2.2 SM-DS Keys and Certificate

Hereafter the SM-DS certificates and keys for Authentication with invalid curve as defined in Annex A.

File name	Description
SK_S_SM_DSauth_ECDSA_NIST192.pem	NIST P-192 Private Key of the SM-DS for creating signatures for SM-DS authentication

PK_S_SM_DSauth_ECDSA_NIST192.pem	NIST P-192 Public Key of the SM-DS (part of the CERT_S_SM_DSauth_INV_CURVE_NIST192.der)
CERT_S_SM_DSauth_INV_CURVE_NIST192.der	Certificate of the SM-DS for its Public NIST P-192 key used for SM-DS authentication

#### 4.3.1.2.3 Input data for generation

Command lines for the generation of the SK.DSauth.ECDSA and the corresponding PK.DSauth.ECDSA for NIST P-192 curve:

```
openssl ecparam -name prime192v1 -genkey -out SK_S_SM_DSauth_ECDSA_NIST192.pem
openssl ec -in SK_S_SM_DSauth_ECDSA_NIST192.pem -pubout -out
    PK_S_SM_DSauth_ECDSA_NIST192.pem
```

The CERT.DSauth.ECDSA based on NIST P-192 curve is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: DSauth-csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 4.4.1.1 for serialNumber data field.

<days> set with value defined in section 4.4.1.1 for validity data field.

<cert\_ext\_file\_name>: DSauth-ext.cnf as defined in Annex A.

### 4.3.2 TLS

#### 4.3.2.1 TLS – Invalid Signature

##### 4.3.2.1.1 SM-DS TLS Certificate: definition of data to be signed

All the data to be signed are the same as the ones defined in 3.5.2.1.

##### 4.3.2.1.2 SM-DS Certificate

Hereafter the SM-DS TLS certificates with invalid signature as defined in Annex A.

File name	Description
CERT_S_SM_DS_TLS_NIST.der	Certificate of the SM-DS with invalid signature for its Public NIST P-256 key
CERT_S_SM_DS_TLS_BRP.der	Certificate of the SM-DS with invalid signature for its Public Brainpool P256r1 key

#### 4.3.2.1.3 Input data for generation

Few bytes of the generated signatures contained in the DER files have been manually changed as follow:

- Least significant byte of CERT\_S\_SM\_DS\_TLS\_NIST.der signature increased by 1
- Least significant byte of CERT\_S\_SM\_DS\_TLS\_BRP.der signature increased by 1

#### 4.3.2.2 TLS – Invalid Curve

##### 4.3.2.2.1 SM-DS TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.5.2
serialNumber	Same as in section 3.5.2
signature	Same as in section 3.5.2
issuer	Same as in section 3.5.2
validity	Same as in section 3.5.2
subject	Same as in section 3.5.2
subjectPublicKeyInfo	algorithm.algorithm = '1.2.840.10045.2.1' (id-ecPublicKey) algorithm.parameters = '1.3.132.0.34' (secp384r1) subjectPublicKey = < PK.DS.TLS value> (see 3.4.3.2)
Extensions	Same as in section 3.5.2
Extension for authorityKeyIdentifier	<Value of CERT.CI.ECDSA."subjectKeyIdentifier" field> for secp384r1
Extension for subjectKeyIdentifier	NIST (secp384r1): '0a 8f 46 e4 bd df e3 3f b0 1c 4b 0c c6 2f 14 0b 3b 11 91 c6'
Extension for keyUsage	Same as in section 3.5.2
Extension for certificatePolicies	Same as in section 3.5.2
Extension for extendedKeyUsage	Same as in section 3.5.2
Extension for subjectAltName	Same as in section 3.5.2
Extension for crlDistributionPoints	Same as in section 3.5.2

**Table 45: CERT\_S\_SM\_DS\_TLS\_INV\_CURVE**

##### 4.3.2.2.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_CERT_CI_S_SM_DP_NIST_P384.pem	NIST P-384 Private CI key of the SM-DP+ for securing TLS connection with
PK_CERT_CI_S_SM_DP_NIST_P384.pem	NIST P-384 Public CI Key of the SM-DP+
SK_CERT_S_SM_DP_TLS_INV_CURVE.pem	NIST P-384 Private key of the SM-DP+ for securing TLS connection with
PK_CERT_S_SM_DP_TLS_INV_CURVE.pem	NIST P-384 Public Key of the SM-DP+ (part of the CERT_S_SM_DS_TLS_INV_CURVE.der)
CERT_S_SM_DS_TLS_INV_CURVE.der	CERT.DS.TLS certificate of the S_SM-DS, based on NIST P-384 curve

#### 4.3.2.2.3 Input data for generation

The Private and Public Keys are the same as for CERT\_S\_SM\_DP\_TLS\_INV\_CURVE.der.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS\_TLS.ext.cnf as defined in Annex A.

#### 4.3.2.3 TLS – Invalid Certificate Policy

##### 4.3.2.3.1 SM-DS TLS Certificate: definition of data to be signed

Field	Value
Version	Same as in section 3.5.2
serialNumber	Same as in section 3.5.2
Signature	Same as in section 3.5.2
Issuer	Same as in section 3.5.2
validity	Same as in section 3.5.2
subject	Same as in section 3.5.2
subjectPublicKeyInfo	Same as in section 3.5.2
Extensions	Same as in section 3.5.2
Extension for authorityKeyIdentifier	Same as in section 3.5.2

Extension for subjectKeyIdentifier	Same as in section 3.5.2
Extension for keyUsage	Same as in section 3.5.2
Extension for certificatePolicies	'2.23.146.1.2.1.4' (id-rspRole-dp-auth)
Extension for extendedKeyUsage	Same as in section 3.5.2
Extension for subjectAltName	Same as in section 3.5.2
Extension for crlDistributionPoints	Same as in section 3.5.2

**Table 46: CERT\_S\_SM\_DS\_TLS\_INV\_CERT\_POL**

#### 4.3.2.3.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS for securing TLS connection
PK_S_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DS_TLS_NIST.der)
CERT_S_SM_DP_TLS_INV_CERT_POL.der	CERT.DS.TLS certificate of the S_SM-DS with invalid 'Certificate Policies' extension (OID set to 'id-rspRole-dp-auth'), formatted as X.509 certificate.

#### 4.3.2.3.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS\_TLS\_INV\_CERT\_POL.ext.cnf as defined in Annex A.

#### 4.3.2.4 TLS – Missing Critical Extension

##### 4.3.2.4.1 SM-DS TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.5.2
serialNumber	Same as in section 3.5.2
signature	Same as in section 3.5.2
issuer	Same as in section 3.5.2
validity	Same as in section 3.5.2
subject	Same as in section 3.5.2
subjectPublicKeyInfo	Same as in section 3.5.2
Extensions	Same as in section 3.5.2
Extension for authorityKeyIdentifier	Same as in section 3.5.2
Extension for subjectKeyIdentifier	Same as in section 3.5.2
Extension for keyUsage	Same as in section 3.5.2
Extension for certificatePolicies	Same as in section 3.5.2
Extension for extendedKeyUsage	Absent
Extension for subjectAltName	Same as in section 3.5.2
Extension for CrlDistributionPoints	Same as in section 3.5.2

**Table 47: CERT\_S\_SM\_DS\_TLS\_INV\_CRITICAL\_EXT**

##### 4.3.2.4.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS for securing TLS connection
PK_S_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DS_TLS_NIST.der)
CERT_S_SM_DS_TLS_INV_CRITICAL_EXT.der	CERT.DS.TLS certificate of the S_SM-DS with one of the critical extensions not present, formatted as X.509 certificate.



#### 4.3.2.4.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS\_TLS\_INV\_CRITICAL\_EXT.ext.cnf as defined in Annex A.

#### 4.3.2.5 TLS – Invalid Extended Key Usage

##### 4.3.2.5.1 SM-DP+ TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.5.2
serialNumber	Same as in section 3.5.2
signature	Same as in section 3.5.2
issuer	Same as in section 3.5.2
validity	Same as in section 3.5.2
subject	Same as in section 3.5.2
subjectPublicKeyInfo	Same as in section 3.5.2
Extensions	Same as in section 3.5.2
Extension for authorityKeyIdentifier	Same as in section 3.5.2
Extension for subjectKeyIdentifier	Same as in section 3.5.2
Extension for keyUsage	Same as in section 3.5.2
Extension for certificatePolicies	Same as in section 3.5.2
Extension for extendedKeyUsage	Critical TLS Client Authentication
Extension for subjectAltName	Same as in section 3.5.2
Extension for crlDistributionPoints	Same as in section 3.5.2

**Table 48: CERT\_S\_SM\_DS\_TLS\_INV\_EXT\_KEY\_USAGE**

#### 4.3.2.5.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS for securing TLS connection
PK_S_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DS_TLS_NIST.der)
CERT_S_SM_DS_TLS_INV_EXT_KEY_USAGE.der	CERT.DS.TLS certificate of the S_SM-DS with invalid 'extended key usage' extension (not set to 'id-kp-serverAuth'), formatted as X.509 certificate.

#### 4.3.2.5.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS\_TLS\_INV\_EXT\_KEY\_USAGE.ext.cnf as defined in Annex A.

#### 4.3.2.6 TLS – Invalid Key Usage

##### 4.3.2.6.1 SM-DS TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.5.2
serialNumber	Same as in section 3.5.2
signature	Same as in section 3.5.2
Issuer	Same as in section 3.5.2
Validity	Same as in section 3.5.2
Subject	Same as in section 3.5.2
subjectPublicKeyInfo	Same as in section 3.5.2
Extensions	Same as in section 3.5.2

Extension for authorityKeyIdentifier	Same as in section 3.5.2
Extension for subjectKeyIdentifier	Same as in section 3.5.2
Extension for keyUsage	Critical 'keyAgreement' ('08')
Extension certificatePolicies for	Same as in section 3.5.2
Extension for extendedKeyUsage	Same as in section 3.5.2
Extension for subjectAltName	Same as in section 3.5.2
Extension for crlDistributionPoints	Same as in section 3.5.2

**Table 49: CERT\_S\_SM\_DS\_TLS\_INV\_KEY\_USAGE**

#### 4.3.2.6.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS for securing TLS connection
PK_S_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DS_TLS_NIST.der)
CERT_S_SM_DS_TLS_INV_KEY_USAG E.der	CERT.DS.TLS certificate of the S_SM-DS with invalid 'key usage' extension (not set to 'digitalSignature'), formatted as X.509 certificate.

#### 4.3.2.6.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DP.TLS is generated using the command lines described in section 2.4 with the following input data:

<input\_csr\_file\_name>: CERT\_S\_SM\_DS\_TLS.csr.cnf as defined in Annex A.

<ca\_cert\_file\_name> and <ca\_sk\_file\_name>: files generated in section 3.1.2 (file containing the CERT.CI.ECDSA and SK.CI.ECDSA respectively).

<serial> set with value defined in section 3.4.3.1 for serialNumber data field.

<days> set with value defined in section 3.4.3.1 for validity data field.

<cert\_ext\_file\_name>: CERT\_S\_SM\_DS\_TLS\_INV\_KEY\_USAGE.ext.cnf as defined in Annex A.

#### 4.3.2.7 TLS – Expired Certificate

##### 4.3.2.7.1 SM-DS TLS Certificate: definition of data to be signed

Field	Value
version	Same as in section 3.5.2.1
serialNumber	Same as in section 3.5.2.1
signature	Same as in section 3.5.2.1
issuer	Same as in section 3.5.2.1
validity	expired on 1st Jul 2017
subject	Same as in section 3.5.2.1
subjectPublicKeyInfo	Same as in section 3.5.2.1
Extensions	Same as in section 3.5.2.1
Extension for authorityKeyIdentifier	Same as in section 3.5.2.1
Extension for subjectKeyIdentifier	Same as in section 3.5.2.1
Extension for keyUsage	Same as in section 3.5.2.1
Extension for certificatePolicies	Same as in section 3.5.2.1
Extension for extendedKeyUsage	Same as in section 3.5.2.1
Extension for subjectAltName	Same as in section 3.5.2.1
Extension for crlDistributionPoints	Same as in section 3.5.2.1

**Table 50: CERT\_S\_SM\_DS\_TLS\_EXPIRED**

##### 4.3.2.7.2 SM-DS TLS Keys and Certificate

Hereafter the generated SM-DS keys and certificates for TLS as defined in Annex A.

File name	Description
SK_S_SM_DS_TLS_NIST.pem	NIST P-256 Private key of the SM-DS for securing TLS connection
PK_S_SM_DS_TLS_NIST.pem	NIST P-256 Public Key of the SM-DS (part of the CERT_S_SM_DS_TLS_NIST.der)

CERT_S_SM_DS_TLS_EXPIRED.der	Expired CERT.DS.TLS certificate of the S_SM-DS with a valid signature, correctly formatted as X.509 certificate.
------------------------------	--

#### 4.3.2.7.3 Input data for generation

The Private and Public Keys are generated using the command lines as described in section 2.2.

The CERT.DS.TLS is generated using the command lines described in section 2.4 with the following changes:

```
openssl ca -batch -config <config_file> -in <csr_file_name> -extensions  
<ext_section_name> -cert <ca_cert_file_name> -keyfile <ca_sk_file_name> -notext -  
out <cert_pem_file_name> -startdate <validity_start_date> -enddate  
<validity_end_date>
```

Preconditions:

- Following entries are present in the indicated <config\_file> under the default CA section:  
...  
database = \$ENV::OPENSSL\_HOME/indexTlsCert.txt  
serial = \$ENV::OPENSSL\_HOME/serialTlsCert  
...  
• Following files are present in OpenSSL home folder and are empty:
  - indexTlsCert.txt
  - indexTlsCert.txt.attr
- The text file 'serialTlsCert' is present in OpenSSL home folder and contains the desired serial number as hex string.
- Following extension to be referenced by <ext\_section\_name> sections are present in the indicated <config\_file> for SM-DS certificate:

```
[ extensions_CERT_S_SM_DS_TLS ]  
keyUsage = critical, digitalSignature  
extendedKeyUsage = critical, serverAuth, clientAuth  
certificatePolicies = 2.23.146.1.2.1.6  
subjectKeyIdentifier = hash  
authorityKeyIdentifier = keyid:always,issuer  
subjectAltName = DNS:testrootsmds.gsma.com, RID:2.999.15  
                  crlDistributionPoints=URI:http://ci.test.gsma.com/CRL-A.crl,  
URI:http://ci.test.gsma.com/CRL-B.crl
```

- <validity\_start\_date> and <validity\_end\_date> are formatted YYMMDDHHMMSSZ, e.g. '170301154500Z' for 'Mar 1 15:45:00 2017 GMT'.

## **Annex A RSP Certificates and Keys Files (Normative)**

All certificates, keys and configuration files are provided within the SGP.26\_v1.1\_Files.ZIP package which accompanies the present document.

## Annex B Document Management

### B.1 Document History

Version	Date	Brief Description of Change	Approval Authority	Editor / Company
v1.0	9 June 2017	New PRD Publication	PSMC	Yolanda Sanz GSMA
V1.1	28 Sept 2017	The first minor version of SGP.26	RSPPLEN	Yolanda Sanz GSMA

### Other Information

Type	Description
Document Owner	Yolanda Sanz / GSMA
Editor / Company	Guido Abate / STMicroelectronics

It is our intention to provide a quality product for your use. If you find any errors or omissions, please contact us with your comments. You may notify us at [prd@gsma.com](mailto:prd@gsma.com)

Your comments or suggestions & questions are always welcome.